
NailGun Documentation

Release 0.32.0

Jeremy Audet

Nov 24, 2021

Contents

1	Examples	3
2	API Documentation	15
3	Quick Start	121
4	Why NailGun?	123
5	Scope and Limitations	125
6	Resources	127
7	Contributing	129
	Python Module Index	133
	Index	135

NailGun is a GPL-licensed Python library that facilitates easy usage of the Satellite 6 API. It lets you write code like this:

```
>>> org = Organization(id=1).read()
```

This page provides a summary of information about NailGun.

Contents

- *NailGun*
 - *Quick Start*
 - *Why NailGun?*
 - *Scope and Limitations*
 - *Resources*
 - *Contributing*
 - * *Nailgun Review Process*
 - * *Nailgun Release Process*

More in-depth coverage is provided in other sections.

CHAPTER 1

Examples

This page contains several examples of how to use NailGun. The examples progress from simple to more advanced. You can run any of the scripts presented in this document. This is the set-up procedure for scripts that use NailGun:

```
python3 -m venv env
source env/bin/activate
pip install nailgun
./some_script.py # some script of your choice
```

This is the set-up procedure for scripts that do not use NailGun:

```
python3 -m venv env
source env/bin/activate
pip install requests
./some_script.py # some script of your choice
```

Additionally, a video demonstration entitled [NailGun Hands On](#) is available.

Contents

- *Examples*
 - *Video Demonstration*
 - *Getting Started*
 - *Managing Server Configurations*
 - *Using More Methods*
 - * *get_fields*
 - * *create*
 - * *read*

```
* update
* search
- Helper Functions
  * to_json_serializable
- Using Lower Layers
```

1.1 Video Demonstration

Note that this video does not touch on features that were added after it was recorded on May 26 2015, such as the *update* method.

1.2 Getting Started

This script demonstrates how to create an organization, print out its attributes and delete it using NailGun:

```
#!/usr/bin/env python3
"""Create an organization, print out its attributes and delete it.

Use NailGun to accomplish this task.

"""
from pprint import pprint

from nailgun.config import ServerConfig
from nailgun.entities import Organization

def main():
    """Create an organization, print out its attributes and delete it."""
    server_config = ServerConfig(
        auth=('admin', 'changeme'), # Use these credentials...
        url='https://sat1.example.com', # ...to talk to this server.
    )
    org = Organization(server_config, name='junk org').create()
    pprint(org.get_values()) # e.g. {'name': 'junk org', ...}
    org.delete()

if __name__ == '__main__':
    main()
```

This script demonstrates how to do the same *without* NailGun:

```
#!/usr/bin/env python3
"""Create an organization, print out its attributes and delete it.

Use Requests and standard library modules to accomplish this task.

"""
import json
```

(continues on next page)

(continued from previous page)

```

from pprint import pprint

import requests

def main():
    """Create an organization, print out its attributes and delete it."""
    auth = ('admin', 'changeme')
    base_url = 'https://sat1.example.com'
    organization_name = 'junk org'
    args = {'auth': auth, 'headers': {'content-type': 'application/json'}}

    response = requests.post(
        f'{base_url}/katello/api/v2/organizations',
        json.dumps(
            {
                'name': organization_name,
                'organization': {'name': organization_name},
            }
        ),
        **args,
    )
    response.raise_for_status()
    pprint(response.json())
    response = requests.delete(
        f"{base_url}/katello/api/v2/organizations/{response.json()['id']}", **args
    )
    response.raise_for_status()

if __name__ == '__main__':
    main()

```

1.3 Managing Server Configurations

In the example shown above, a `nailgun.config.ServerConfig` object was created in the body of the script. However, inter-mixing configuration data and program logic in this manner is problematic:

- Placing sensitive information in to a code-base puts that information at risk of becoming public, especially when the code-base is version-controlled.
- Server-specific configuration information is likely to change frequently. Placing that information in to a code-base means subjecting that code-base to unnecessary churn, making it harder for developers to find useful information in a repository's change log.

NailGun addresses this issue by providing full support for configuration files. Here's a simple example of how to create a pair of configuration objects, save them to disk, and read them back again:

```

>>> from nailgun.config import ServerConfig
>>> ServerConfig('http://sat1.example.com').save('sat1')
>>> ServerConfig('http://sat2.example.com').save('sat2')
>>> set(ServerConfig.get_labels()) == set(('sat1', 'sat2'))
True
>>> sat1_cfg = ServerConfig.get('sat1')
>>> sat2_cfg = ServerConfig.get('sat2')

```

A label of “default” is used when saving or reading configuration objects if no explicit label is given. As a result, this is valid:

```
>>> from nailgun.config import ServerConfig
>>> ServerConfig('bogus url').save()
>>> ServerConfig.get().url == 'bogus url'
True
```

The use of “default” is especially useful if you have created numerous server configurations, but only want to work with one at a time:

```
>>> from nailgun.config import ServerConfig
>>> ServerConfig.get('sat1').save() # same as .save(label='default')
```

In addition, if no server configuration object is specified when instantiating an `nailgun.entity_mixins.Entity` object, the server configuration labeled “default” is used. With this in mind, here’s a revised version of the first script in section *Getting Started*:

```
#!/usr/bin/env python3
"""Create an organization, print out its attributes and delete it."""
from pprint import pprint

from nailgun.entities import Organization

def main():
    """Create an organization, print out its attributes and delete it."""
    org = Organization(name='junk org').create()
    pprint(org.get_values()) # e.g. {'name': 'junk org', ...}
    org.delete()

if __name__ == '__main__':
    main()
```

This works just fine in many use cases. But what if you do not want to save your server configuration to disk? This might be the case if multiple processes are using NailGun and each process should default to communicating with a different default server, or if you are working with a read-only file system. In this case, you can use `nailgun.entity_mixins.DEFAULT_SERVER_CONFIG`.

NailGun handles other use cases, too. For example, the XDG base directory specification is obeyed, meaning that you can do things like provide a system-wide configuration file or place user configuration data in an alternate location. Read `nailgun.config` for full details.

1.4 Using More Methods

The examples so far have only made use of a small set of classes and methods:

- The `ServerConfig` class and several of its methods.
- The `Organization` class and its `create`, `get_values` and `delete` methods.

However, there are several more very useful high-level methods that you should be aware of. In addition, there are aspects to the `create` method that have not been touched on.

- `get_fields`
- `create`
- `read`
- `update`
- `search`

1.4.1 `get_fields`

The `get_fields` method is closely related to the `get_values` method. The former tells you which values *may* be assigned to an entity, and the latter tells you what values *are* assigned to an entity. For example:

```
>>> from nailgun.entities import Product
>>> product = Product(name='junk product')
>>> product.get_values()
{'name': 'junk product'}
>>> product.get_fields()
{
  'description': <nailgun.entity_fields.StringField object at 0x7fb5bf25ee10>,
  'gpg_key': <nailgun.entity_fields.OneToOneField object at 0x7fb5bf1f1128>,
  'id': <nailgun.entity_fields.IntegerField object at 0x7fb5bd4bd748>,
  'label': <nailgun.entity_fields.StringField object at 0x7fb5bd48b7f0>,
  'name': <nailgun.entity_fields.StringField object at 0x7fb5bd48b828>,
  'organization': <nailgun.entity_fields.OneToOneField object at 0x7fb5bd498f60>,
  'sync_plan': <nailgun.entity_fields.OneToOneField object at 0x7fb5bd49eac8>,
}
```

Fields serve two purposes. First, they provide typing information mixins. For example, a server expects this JSON payload when creating a product:

```
{
  "name": "junk product",
  "organization_id": 5,
  ...
}
```

And a server will return this JSON payload when reading a product:

```
{
  "name": "junk product",
  "organization": {
    'id': 3,
    'label': 'c5f2646f-5975-48c4-b2a3-bf8398b44510',
    'name': 'junk org',
  },
  ...
}
```

Notice how the “organization” field is named and structured differently in the above two cases. NailGun can deal with this irregularity due to the presence of the `StringField` and `OneToOneField`. If you are ever fiddling with an entity’s definition, be careful to use the right field types. Otherwise, you may get some strange and hard-to-troubleshoot bugs.

Secondly, fields can generate random values for unit testing purposes. (This does *not* normally happen!) See the `create_missing` method for more information.

1.4.2 create

So far, we have only used brand new objects:

```
>>> from nailgun.entities import Organization
>>> org = entities.Organization(name='junk org').create()
```

However, we can also use existing objects:

```
>>> from nailgun.entities import Organization
>>> org = entities.Organization()
>>> org.name = 'junk org'
>>> org = org.create()
```

Note that the `create` method is side-effect free. As a result, the `org = org.create()` idiom is advisable. (The next section discusses this more.)

1.4.3 read

The `read` method fetches information about an entity. Typical usages of this method have already been shown, so this example goes in to more detail:

```
>>> from nailgun.entities import Organization
>>> org = Organization(id=418)
>>> response = org.read()
>>> for obj in (org, response):
...     type(obj)
...
<class 'nailgun.entities.Organization'>
<class 'nailgun.entities.Organization'>
>>> for obj in (org, response):
...     obj.get_values()
...
{'id': 418}
{
  'description': None,
  'id': 418,
  'label': 'junk_org',
  'name': 'junk org',
  'title': 'junk org',
}
```

Some notes on the above:

- The `read` method requires that an `id` attribute be present. Running `Organization().read()` will throw an exception.
- The `read` method is side-effect free. Rather than altering the object it is called on, it creates a new object, populates that object with attributes and returns the object. As a result, idioms like `org = org.read()` are advisable.

So far, we have only used brand new objects:

```
>>> from nailgun.entities import Organization
>>> org = Organization(id=418).read()
```

However, we can also use existing objects:

```
>>> from nailgun.entities import Organization
>>> org = Organization()
>>> org.id = 418
>>> org = org.read()
```

1.4.4 update

The update method updates an entity's values. For example:

```
>>> from nailgun.entities import Organization
>>> org = Organization(id=418).read()
>>> org.get_values()
{
  'description': None,
  'id': 418,
  'label': 'junk_org',
  'name': 'junk org',
  'title': 'junk org',
}
>>> org.name = 'junkier org'
>>> org.description = 'supercalifragilisticexpialidocious'
>>> org = org.update() # update all fields by default
>>> org.get_values()
{
  'description': 'supercalifragilisticexpialidocious',
  'id': 418,
  'label': 'junk_org',
  'name': 'junkier org',
  'title': 'junkier org',
}
>>> org.description = None
>>> org = org.update(['description']) # update only named fields
>>> org.get_values()
{
  'description': None,
  'id': 418,
  'label': 'junk_org',
  'name': 'junkier org',
  'title': 'junkier org',
}
```

Some notes on the above:

- By default, the update method updates all fields. However, it is also possible to update a subset of fields.
- The update method is side-effect free. As a result, idioms like `org = org.update()` are advisable.

So far, we have only called update on existing objects. However, we can also call update on brand new objects:

```
>>> from nailgun.entities import Organization
>>> Organization(
...     id=418,
```

(continues on next page)

(continued from previous page)

```
...     name='junkier org',
...     description='supercalifragilisticexpialidocious',
... ).update(['name', 'description'])
```

1.4.5 search

The search method searches for entities. By default, it searches for all entities of a given kind:

```
lc_envs = LifecycleEnvironment().search()
```

If any attributes have been set, they are used. This finds all lifecycle environments that have a name of “foo” and that belong to organization 1:

```
lc_envs = LifecycleEnvironment(name='foo', organization=1).search()
```

You can choose to use only some fields in a search. This finds all lifecycle environments that have a name of “foo”:

```
lc_envs = LifecycleEnvironment(name='foo', organization=1).search({'name'})
```

Other options are available, too. You can hard-code query parameters (especially useful for pagination), filter results locally and more. For examples of how to search, see [nailgun.entity_mixins.EntitySearchMixin.search\(\)](#). For examples of how search queries are generated, see [nailgun.entity_mixins.EntitySearchMixin.search_payload\(\)](#).

1.5 Helper Functions

Nailgun has also some helper functions for common operations.

1.5.1 to_json_serializable

This function parses nested nailgun entities, date, datetime, numbers, dict and list so the result can be parsed by json module:

```
>>> from nailgun import entities
>>> from nailgun.config import ServerConfig
>>> from datetime import date, datetime
>>> cfg=ServerConfig('https://foo.bar')
>>> dct = {'dict': {'objs':
[
    1, 'str', 2.5, date(2016, 12, 13),
    datetime(2016, 12, 14, 1, 2, 3)
]}}}
>>> entities.to_json(dct)
{'dict':
  {'objs': [1, 'str', 2.5, '2016-12-13', '2016-12-14 01:02:03']}
}
>>> env = entities.Environment(cfg, id=1, name='env')
>>> entities.to_json(env)
{'id': 1, 'name': 'env'}
>>> location = entities.Location(cfg, name='loc')
>>> hostgroup = entities.HostGroup(
```

(continues on next page)

(continued from previous page)

```

        cfg, name='hgroup', id=2, location=[location])
>>> entities.to_json_serializable(hostgroup)
{'location': [{'name': 'loc'}], 'name': 'hgroup', 'id': 2}
>>> mixed = [regular_object, env, hostgroup]
>>> entities.to_json_serializable(mixed)
[
  {'dict': {'objs': [1, 'str', 2.5, '2016-12-13', '2016-12-13']}},
  {'id': 1, 'name': 'env'},
  {'location': [{'name': 'loc'}], 'name': 'hgroup', 'id': 2}
]
>>> import json
>>> json.dumps(entities.to_json_serializable(mixed))
'{"dict": {"objs": [1, "str", 2.5, "2016-12-13", "2016-12-13"]}, {"id": 1, "name":
↪"env"}, {"location": [{"name": "loc"}], "name": "hgroup", "id": 2}]'

```

1.6 Using Lower Layers

This section demonstrates how to create a user account. To make things interesting, there are some extra considerations:

- The user account must belong to the organization labeled “Default_Organization”.
- The user account must be named “Alice” and have the password “hackme”.
- The user account must be created on a pair of satellites.

Two sets of code that accomplish this task are listed. The first body of code shows how to accomplish the task with NailGun. The second body of code does not make use of NailGun, and instead relies entirely on `Requests` and standard library modules.

```

#!/usr/bin/env python3
"""Create an identical user account on a pair of satellites."""
from pprint import pprint

from nailgun.config import ServerConfig
from nailgun.entities import Organization
from nailgun.entities import User

def main():
    """Create an identical user account on a pair of satellites."""
    server_configs = ServerConfig.get('sat1'), ServerConfig.get('sat2')
    for server_config in server_configs:
        org = Organization(server_config).search(query={'search': 'name="Default_
↪Organization"})[
        0
        ]
        # The LDAP authentication source with an ID of 1 is internal. It is
        # nearly guaranteed to exist and be functioning.
        user = User(
            server_config,
            auth_source=1, # or: AuthSourceLDAP(server_config, id=1),
            login='Alice',
            mail='alice@example.com',
            organization=[org],

```

(continues on next page)

(continued from previous page)

```

        password='hackme',
    ).create()
    pprint(user.get_values()) # e.g. {'login': 'Alice', ...}

if __name__ == '__main__':
    main()

```

The code above makes use of NailGun. The code below makes use of Requests and standard library modules.

```

#!/usr/bin/env python3
"""Create an identical user account on a pair of satellites.

If you'd like to test out this script, you can quickly set up an environment
like so::

    python3 -m venv env
    source env/bin/activate
    pip install requests
    ./create_user_plain.py # copy this script to the current directory

"""
import json
from pprint import pprint

import requests

def main():
    """Create an identical user account on a pair of satellites."""
    server_configs = (
        {'url': url, 'auth': ('admin', 'changeme'), 'verify': False}
        for url in ('https://sat1.example.com', 'https://sat2.example.com')
    )
    for server_config in server_configs:
        response = requests.post(
            f'{server_config["url"]}/api/v2/users',
            json.dumps(
                {
                    'user': {
                        'auth_source_id': 1,
                        'login': 'Alice',
                        'mail': 'alice@example.com',
                        'organization_ids': [
                            get_organization_id(server_config, 'Default_Organization')
                        ],
                        'password': 'hackme',
                    }
                }
            ),
            auth=server_config['auth'],
            headers={'content-type': 'application/json'},
            verify=server_config['verify'],
        )
        response.raise_for_status()
        pprint(response.json())

```

(continues on next page)

(continued from previous page)

```

def get_organization_id(server_config, label):
    """Return the ID of the organization with label ``label``.

    :param server_config: A dict of information about the server being talked
        to. The dict should include the keys "url", "auth" and "verify".
    :param label: A string label that will be used when searching. Every
        organization should have a unique label.
    :returns: An organization ID. (Typically an integer.)

    """
    response = requests.get(
        f'{server_config["url"]}/katello/api/v2/organizations',
        data=json.dumps({"search": f"label={label}"}),
        auth=server_config["auth"],
        headers={"content-type": "application/json"},
        verify=server_config["verify"],
    )
    response.raise_for_status()
    decoded = response.json()
    if decoded['subtotal'] != 1:
        print(
            f'Expected to find one organization, but instead found {decoded["subtotal"]}. '
            f'Search results: {decoded["results"]}'
        )
        exit(1)
    return decoded['results'][0]['id']

if __name__ == '__main__':
    main()

```

What's different between the two scripts?

First, both scripts pass around `server_config` objects (see `nailgun.config.ServerConfig`). However, the NailGun script does not include any hard-coded parameters. Instead, configurations are read from disk. This makes the script more secure (it can be published publicly without any information leakage) and maintainable (server details can change independent of programming logic).

Second, the sans-NailGun script relies entirely on convention when placing values in to and retrieving values from the `server_config` objects. This is easy to get wrong. For example, one piece of code might place a value named `'verify_ssl'` in to a dictionary and a second piece of code might retrieve a value named `'verify'`. This is a mistake, but you won't know about it until runtime. In contrast, the `ServerConfig` objects have an explicit set of possible instance attributes, and tools such as Flake can use this information when linting code. (Similarly, NailGun's entity objects such as `Organization` and `User` have an explicit set of possible instance attributes.) Thus, NailGun allows for more effective static analysis.

Third, NailGun automatically checks HTTP status codes for you when you call methods such as `create`. In contrast, the sans-NailGun script requires that the user call `raise_for_status` or some equivalent every time a response is received. Thus, NailGun makes it harder for undetected errors to creep in to code and cause trouble.

Fourth, there are several hard-coded paths present in the sans-NailGun script: `'/katello/api/v2/organizations'` and `'/api/v2/users'`. This is a hassle. Developers need to look up a path every time they write an API call, and it's easy to make a mistake and waste time troubleshooting the resultant error. NailGun shields the developer from this issue — not a single path is present!

Fifth, the NailGun script shields developers from idiosyncrasies in JSON request formats. Notice how no nested dict

is necessary when issuing a GET request for organizations, but a nested dict is necessary when issuing a POST request for users. Differences like this abound. NailGun packages data for you.

Sixth, and perhaps most obviously, the NailGun script is *significantly* shorter! This makes it easier to focus on high-level business logic instead of worrying about implementation details.

This is the NailGun API documentation. It is mostly auto generated from the source code. A good place to start reading is *nailgun*.

The *nailgun* namespace is the public API. The *tests* is not part of the public API, and it is documented here for easy reference for developers.

2.1 nailgun

The root of the NailGun namespace.

NailGun's modules are organized in to a tree of dependencies, where each module only knows about the modules below it in the tree and no module knows about others at the same level in the tree. The modules can be visualized like this:

```
nailgun.entities
├─ nailgun.entity_mixins
│   └─ nailgun.entity_fields
│   └─ nailgun.config
│   └─ nailgun.client
```

If this is your first time working with NailGun, please read several of the *Examples* before the documentation here.

2.1.1 nailgun.entities

This module defines all entities which Foreman exposes.

Each class in this module allows you to work with a certain set of logically related API paths exposed by the server. For example, *nailgun.entities.Host* lets you work with the `/api/v2/hosts` API path and sub-paths. Each class attribute corresponds an attribute of that entity. For example, the `Host.name` class attribute represents the name of a host. These class attributes are used by the various mixins, such as *nailgun.entity_mixins.EntityCreateMixin*.

Several classes contain work-arounds for bugs. These bugs often affect only specific server releases, and ideally, the work-arounds should only be attempted if communicating with an affected server. However, work-arounds can only be conditionally triggered if NailGun has a facility for determining which software version the server is running. Until then, the safe route will be taken, and all work-arounds will be attempted all the time. Each method that makes use of a work-around notes so in its docstring.

`nailgun.entity_mixins.Entity` provides more insight into the inner workings of entity classes.

exception `nailgun.entities.APIResponseError`

Indicates an error if response returns unexpected result.

class `nailgun.entities.AbstractComputeResource` (*server_config=None, **kwargs*)

A representation of a Compute Resource entity.

associate (*synchronous=True, timeout=None, **kwargs*)

Associate the host

Parameters `kwargs` – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

available_flavors (*synchronous=True, timeout=None, **kwargs*)

Get flavors available to be added to the compute resource

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

available_images (*synchronous=True, timeout=None, **kwargs*)

Get images available to be added to the compute resource

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

available_networks (*synchronous=True, timeout=None, **kwargs*)

Get networks available to be selected for host provisioning

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

available_zones (*synchronous=True, timeout=None, **kwargs*)

Get images available to be added to the compute resource

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

create_payload ()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

images (*synchronous=True, timeout=None, **kwargs*)

Get images created in a compute resource

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`. The format of the returned path depends on the value of `which`:

available_images `/api/compute_resources/:id/available_images`

available_flavors `/api/compute_resources/:id/available_flavors`

available_zones /api/compute_resources/:id/available_zones

available_networks /api/compute_resources/:id/available_networks

images /api/compute_resources/:id/images

associate /api/compute_resources/:id/associate

Otherwise, call `super`.

update (*fields=None*)

Fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1250922](#).

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.AbstractContentViewFilter` (*server_config=None, **kwargs*)

A representation of a Content View Filter entity.

class `nailgun.entities.ActivationKey` (*server_config=None, **kwargs*)

A representation of a Activation Key entity.

add_host_collection (*synchronous=True, timeout=None, **kwargs*)

Helper for associating host collection with activation key.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

add_subscriptions (*synchronous=True, timeout=None, **kwargs*)

Helper for adding subscriptions to activation key.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

content_override (*synchronous=True, timeout=None, **kwargs*)

Override the content of an activation key.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

copy (*synchronous=True, timeout=None, **kwargs*)

Copy provided activation key.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

add_subscriptions /activation_keys/<id>/add_subscriptions

copy /activation_keys/<id>/copy

content_override /activation_keys/<id>/content_override

product_content /activation_keys/<id>/product_content

releases /activation_keys/<id>/releases

remove_subscriptions /activation_keys/<id>/remove_subscriptions

subscriptions /activation_keys/<id>/subscriptions

`super` is called otherwise.

product_content (*synchronous=True, timeout=None, **kwargs*)

Helper for showing content available for activation key.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

remove_host_collection (*synchronous=True, timeout=None, **kwargs*)

Helper for disassociating host collection from the activation key.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

remove_subscriptions (*synchronous=True, timeout=None, **kwargs*)

Helper for removing subscriptions from an activation key.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

subscriptions (*synchronous=True, timeout=None, **kwargs*)

Helper for retrieving subscriptions on an activation key.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

class `nailgun.entities.Architecture` (*server_config=None, **kwargs*)

A representation of a Architecture entity.

create_payload()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

update (*fields=None*)

Fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1234964](#).

class `nailgun.entities.ArfReport` (*server_config=None, **kwargs*)

A representation of a Arf Report entity.

Read Arf report `ArfReport(id=<id>).read()` # Delete Arf report `ArfReport(id=<id>).delete()` # Download Arf report in HTML `ArfReport(id=<id>).download_html()`

download_html (*synchronous=True, timeout=None, **kwargs*)

Download ARF report in HTML

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`. The format of the returned path depends on the value of `which`:

download_html `/api/compliance/arf_reports/:id/download_html`

Otherwise, call `super`.

class `nailgun.entities.Audit` (*server_config=None, **kwargs*)

A representation of Audit entity.

class `nailgun.entities.AuthSourceLDAP` (*server_config=None, **kwargs*)

A representation of a AuthSourceLDAP entity.

create_missing()

Possibly set several extra instance attributes.

If `onthe-fly_register` is set and is true, set the following instance attributes:

- `account_password`
- `account_firstname`
- `account_lastname`
- `attr_login`
- `attr_mail`

read (*entity=None, attrs=None, ignore=None, params=None*)

Do not read the `account_password` attribute. Work around a bug.

For more information, see [Bugzilla #1243036](#).

class `nailgun.entities.AzureRMComputeResource` (*server_config=None, **kwargs*)
A representation for compute resources with AzureRM provider

read (*entity=None, attrs=None, ignore=None, params=None*)
Make sure, `secret_key` is in the ignore list for read

class `nailgun.entities.Bookmark` (*server_config=None, **kwargs*)
A representation of a Bookmark entity.

class `nailgun.entities.Capsule` (*server_config=None, **kwargs*)
A representation of a Capsule entity.

content_add_lifecycle_environment (*synchronous=True, timeout=None, **kwargs*)
Helper to associate lifecycle environment with capsule

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

content_get_sync (*synchronous=True, timeout=None, **kwargs*)
Helper to get content sync status on capsule

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

content_lifecycle_environments (*synchronous=True, timeout=None, **kwargs*)
Helper to get all the lifecycle environments, associated with capsule

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

content_sync (*synchronous=True, timeout=None, **kwargs*)
 Helper to sync content on a capsule

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)
 Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

content_lifecycle_environments `/capsules/<id>/content/lifecycle_environments`

content_sync `/capsules/<id>/content/sync`

`super` is called otherwise.

class `nailgun.entities.CommonParameter` (*server_config=None, **kwargs*)
 A representation of a Common Parameter entity.

class `nailgun.entities.CompliancePolicies` (*server_config=None, **kwargs*)
 A representation of a Policy entity.

update (*fields=None*)
 Fetch a complete set of attributes for this entity.
 For more information, see [Bugzilla #1746934](#).

class `nailgun.entities.ComputeAttribute` (*server_config=None, **kwargs*)
 A representation of a Compute Attribute entity.

class `nailgun.entities.ComputeProfile` (*server_config=None, **kwargs*)
 A representation of a Compute Profile entity.

class `nailgun.entities.ConfigGroup` (*server_config=None, **kwargs*)
 A representation of a Config Group entity.

class `nailgun.entities.ContentCredential` (*server_config=None, **kwargs*)
 A representation of a Content Credential entity.

class `nailgun.entities.ContentUpload` (*server_config=None, **kwargs*)
 A representation of a Content Upload entity.

path (*which=None*)
 Extend `nailgun.entity_mixins.Entity.path`.

read (*entity=None, attrs=None, ignore=None, params=None*)

Provide a default value for *entity*.

By default, `nailgun.entity_mixins.EntityReadMixin.read` provides a default value for *entity* like so:

```
entity = type(self)()
```

However, `ContentUpload` requires that a *repository* be provided, so this technique will not work. Do this instead:

```
entity = type(self)(repository=self.repository.id)
```

update (*fields=None, **kwargs*)

Update the current entity.

Make an HTTP PUT call to `self.path('base')`. Return the response.

Parameters **fields** – An iterable of field names. Only the fields named in this iterable will be updated. No fields are updated if an empty iterable is passed in. All fields are updated if `None` is passed in.

Returns A `requests.response` object.

upload (*filepath, content_type=None, filename=None*)

Upload content.

Parameters

- **filepath** – path to the file that should be chunked and uploaded
- **content_type** – type of content
- **filename** – name of the file on the server, defaults to the last part of the `filepath` if not set

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

Raises `nailgun.entities.APIResponseError` – If the response has a status other than "success".

class `nailgun.entities.ContentView` (*server_config=None, **kwargs*)

A representation of a Content View entity.

copy (*synchronous=True, timeout=None, **kwargs*)

Clone provided content view.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to `requests`.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

delete_from_environment (*environment, synchronous=True, timeout=None*)

Delete this content view version from an environment.

This method acts much like `nailgun.entity_mixins.EntityDeleteMixin.delete()`. The documentation on that method describes how the deletion procedure works in general. This method differs only in accepting an `environment` parameter.

Parameters environment – A `nailgun.entities.Environment` object. The environment's `id` parameter *must* be specified. As a convenience, an environment ID may be passed in instead of an `Environment` object.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

content_view_versions /content_views/<id>/content_view_versions

publish /content_views/<id>/publish

`super` is called otherwise.

publish (*synchronous=True, timeout=None, **kwargs*)

Helper for publishing an existing content view.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

read (*entity=None, attrs=None, ignore=None, params=None*)

Fetch an attribute missing from the server's response.

For more information, see [Bugzilla #1237257](#).

Add `content_view_component` to the response if needed, as `nailgun.entity_mixins.EntityReadMixin.read()` can't initialize `content_view_component`.

search (*fields=None, query=None, filters=None*)

Search for entities.

Parameters

- **fields** – A set naming which fields should be used when generating a search query. If `None`, all values on the entity are used. If an empty set, no values are used.
- **query** – A dict containing a raw search query. This is melded in to the generated search query like so: `{generated: query}.update({manual: query})`.
- **filters** – A dict. Used to filter search results locally.

Returns A list of entities, all of type `type(self)`.

class `nailgun.entities.ContentViewComponent` (*server_config=None, **kwargs*)

A representation of a Content View Components entity.

add (*synchronous=True, timeout=None, **kwargs*)
Add provided Content View Component.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)
Extend `nailgun.entity_mixins.Entity.path`. The format of the returned path depends on the value of *which*:

add `/content_view_components/add`

remove `/content_view_components/remove`

Otherwise, call `super`.

read (*entity=None, attrs=None, ignore=None, params=None*)
Add `composite_content_view` to the response if needed, as `nailgun.entity_mixins.EntityReadMixin.read()` can’t initialize `composite_content_view`.

remove (*synchronous=True, timeout=None, **kwargs*)
remove provided Content View Component.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

class `nailgun.entities.ContentViewFilterRule` (*server_config=None, **kwargs*)
A representation of a Content View Filter Rule entity.

create_payload ()
Reset `errata_id` from DB ID to `errata_id`.

read (*entity=None, attrs=None, ignore=None, params=None*)
Do not read certain fields.

Do not expect the server to return the `content_view_filter` attribute. This has no practical impact, as the attribute must be provided when a `nailgun.entities.ContentViewFilterRule` is instantiated.

Also, ignore any field that is not returned by the server. For more information, see [Bugzilla #1238408](#).

search_payload (*fields=None, query=None*)
Reset `errata_id` from DB ID to `errata_id`.

update_payload (*fields=None*)
Reset `errata_id` from DB ID to `errata_id`.

class `nailgun.entities.ContentViewVersion` (*server_config=None, **kwargs*)
A representation of a Content View Version non-entity.

incremental_update (*synchronous=True, timeout=None, **kwargs*)
Helper for incrementally updating a content view version.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)
Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

incremental_update `/content_view_versions/incremental_update`

promote `/content_view_versions/<id>/promote`

`super` is called otherwise.

promote (*synchronous=True, timeout=None, **kwargs*)
Helper for promoting an existing published content view.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

class `nailgun.entities.DiscoveredHost` (*server_config=None, **kwargs*)
A representation of a Foreman Discovered Host entity.

auto_provision (*synchronous=True, timeout=None, **kwargs*)
Helper for auto-provisioning of the discovered host

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

auto_provision_all (*synchronous=True, timeout=None, **kwargs*)

Helper for auto-provisioning of all discovered hosts

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

create_payload ()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

facts (*synchronous=True, timeout=None, **kwargs*)

Helper to update facts for discovered host, and create the host.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

facts /discovered_hosts/facts

refresh_facts /discovered_hosts/<id>/refresh_facts

reboot /discovered_hosts/<id>/reboot

super is called otherwise.

read (*entity=None, attrs=None, ignore=None, params=None*)

Make sure, *ip*, *mac*, *root_pass* and *hostgroup* are in the ignore list for read

reboot (*synchronous=True, timeout=None, **kwargs*)

Helper to reboot the discovered host

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

reboot_all (*synchronous=True, timeout=None, **kwargs*)

Helper for rebooting all discovered hosts

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

refresh_facts (*synchronous=True, timeout=None, **kwargs*)

Helper to refresh facts for discovered host

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

update_payload (*fields=None*)
Wrap submitted data within an extra dict.

class `nailgun.entities.DiscoveryRule` (*server_config=None, **kwargs*)
A representation of a Foreman Discovery Rule entity.

Note: The `search_` field is named as such due to a naming conflict with `nailgun.entity_mixins.Entity.path()`.

create (*create_missing=None*)
Do extra work to fetch a complete set of attributes for this entity.
For more information, see [Bugzilla #1381129](#).

create_payload ()
Wrap submitted data within an extra dict.
For more information, see [Bugzilla #1151220](#).
In addition, rename the `search_` field to `search`.

read (*entity=None, attrs=None, ignore=None, params=None*)
Work around a bug. Rename `search` to `search_`.
For more information on the bug, see [Bugzilla #1257255](#).

update (*fields=None*)
Fetch a complete set of attributes for this entity.
For more information, see [Bugzilla #1381129](#).

update_payload (*fields=None*)
Wrap submitted data within an extra dict.

class `nailgun.entities.DockerContentViewFilter` (*server_config=None, **kwargs*)
A representation of a Content View Filter of type “docker”.

class `nailgun.entities.Domain` (*server_config=None, **kwargs*)
A representation of a Domain entity.

create (*create_missing=None*)
Manually fetch a complete set of attributes for this entity.
For more information, see [Bugzilla #1219654](#).

create_missing ()
Customize the process of auto-generating instance attributes.
By default, `nailgun.entity_fields.StringField.gen_value()` can produce strings in both lower and upper cases, but domain name should be always in lower case due logical reason.

create_payload ()
Wrap submitted data within an extra dict.
For more information, see [Bugzilla #1151220](#).

read (*entity=None, attrs=None, ignore=None, params=None*)
Deal with weirdly named data returned from the server.
For more information, see [Bugzilla #1233245](#).

update (*fields=None*)
Fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1234999](#).

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.Environment` (*server_config=None, **kwargs*)

A representation of a Environment entity.

create_payload ()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

list_sparams (*synchronous=True, timeout=None, **kwargs*)

List all smart class parameters

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`. The format of the returned path depends on the value of *which*:

smart_class_parameters `/api/environments/:environment_id/smart_class_parameters`

Otherwise, call `super`.

update (*fields=None*)

Fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1262029](#).

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.Errata` (*server_config=None, **kwargs*)

A representation of an Errata entity.

compare (*synchronous=True, timeout=None, **kwargs*)

Compare errata from different content view versions

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

compare `/katello/api/errata/compare`

Otherwise, call `super`.

read (*entity=None, attrs=None, ignore=None, params=None*)

Following fields are only accessible for filtering search results and are never returned by the server: `content_view_version_id`, `environment_id`, `repository_id`.

class `nailgun.entities.ErratumContentViewFilter` (*server_config=None, **kwargs*)

A representation of a Content View Filter of type “erratum”.

class `nailgun.entities.ExternalUserGroup` (*server_config=None, **kwargs*)

A representation of a External Usergroup entity.

`usergroup` must be passed in when this entity is instantiated.

Raises `TypeError` if `usergroup` is not passed in.

```
# Create external usergroup ExternalUserGroup(name='foobargroup', usergroup=usergroup, auth_source=auth).create()
# Read external usergroup ExternalUserGroup(id=<id>, usergroup=usergroup).read() # Delete
external usergroup ExternalUserGroup(id=<id>, usergroup=usergroup).delete() # Refresh
external usergroup ExternalUserGroup(id=<id>, usergroup=usergroup).refresh()
```

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

refresh `/api/usergroups/:usergroup_id/external_usergroups/:id/refresh`

read (*entity=None, attrs=None, ignore=None, params=None*)

Ignore `usergroup` from `read` and alter `auth_source_ldap` with `auth_source`

refresh (*synchronous=True, timeout=None, **kwargs*)

Refresh external usergroup.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to `requests`.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

class `nailgun.entities.File` (*server_config=None, **kwargs*)

A representation of a Package entity.

class `nailgun.entities.Filter` (*server_config=None, **kwargs*)

A representation of a Filter entity.

create_payload()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

read (*entity=None, attrs=None, ignore=None, params=None*)

Deal with different named data returned from the server

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.ForemanStatus` (*server_config=None, **kwargs*)

A representation of the Foreman Status entity.

class `nailgun.entities.ForemanTask` (*server_config=None, **kwargs*)

A representation of a Foreman task.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

bulk_resume /foreman_tasks/api/tasks/bulk_resume

bulk_search /foreman_tasks/api/tasks/bulk_search

summary /foreman_tasks/api/tasks/summary

Otherwise, call `super`.

poll (*poll_rate=None, timeout=None*)

Return the status of a task or timeout.

There are several API calls that trigger asynchronous tasks, such as synchronizing a repository, or publishing or promoting a content view. It is possible to check on the status of a task if you know its UUID. This method polls a task once every `poll_rate` seconds and, upon task completion, returns information about that task.

Parameters

- **poll_rate** – Delay between the end of one task check-up and the start of the next check-up. Defaults to `nailgun.entity_mixins.TASK_POLL_RATE`.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.

Returns Information about the asynchronous task.

Raises `nailgun.entity_mixins.TaskTimeoutError` if the task completes with any result other than “success”.

Raises `nailgun.entity_mixins.TaskFailedError` if the task finishes with any result other than “success”.

Raises `requests.exceptions.HTTPError` If the API returns a message with an HTTP 4XX or 5XX status code.

summary (*synchronous=True, timeout=None, **kwargs*)

Helper to view a summary of tasks.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.

- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

class `nailgun.entities.GCEComputeResource` (*server_config=None, **kwargs*)
A representation of a Google Compute Resource entity.

class `nailgun.entities.GPGKey` (*server_config=None, **kwargs*)
A representation of a GPG Key entity.

class `nailgun.entities.HTTPProxy` (*server_config=None, **kwargs*)
A representation of a HTTP Proxy entity.

create_payload ()

Wrap submitted data within an extra dict. For more information, see [Bugzilla #1151220](#).

read (*entity=None, attrs=None, ignore=None, params=None*)

Make sure, password, organization and location is in the ignore list for read. For more information, see [Bugzilla #1779642](#).

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.Host` (*server_config=None, **kwargs*)
A representation of a Host entity.

add_puppetclass (*synchronous=True, timeout=None, **kwargs*)
Add a Puppet class to host

Here is an example of how to use this method:: `host.add_puppetclass(data={'puppetclass_id': puppet.id})`

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

bulk_add_subscriptions (*synchronous=True, timeout=None, **kwargs*)
Add subscriptions to one or more hosts

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.

- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

bulk_available_incremental_updates (*synchronous=True, timeout=None, **kwargs*)
Get available_incremental_updates for one or more hosts

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

bulk_destroy (*synchronous=True, timeout=None, **kwargs*)
Destroy the set of hosts

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

bulk_remove_subscriptions (*synchronous=True, timeout=None, **kwargs*)
Remove subscriptions from one or more hosts

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

bulk_resolve_traces (*synchronous=True, timeout=None, **kwargs*)

Resolve traces for the specified set of hosts

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

bulk_traces (*synchronous=True, timeout=None, **kwargs*)

List services that need restarting for the specified set of hosts

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

create (*create_missing=None*)

Manually fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1449749](#).

create_missing ()

Create a bogus managed host.

The exact set of attributes that are required varies depending on whether the host is managed or inherits values from a host group and other factors. Unfortunately, the rules for determining which attributes should be filled in are mildly complex, and it is hard to know which scenario a user is aiming for.

Populate the values necessary to create a bogus managed host. The resultant dependency graph will look, in part, like this:

```

    .-> medium -----
    |-> architecture <-V-
host --> operatingsystem -|
    |-> ptable <-----'
    |-> domain
    '-> environment
  
```

If nested entities were passed by *id* (i.e. entity was only initialized and not read, and therefore contains only *id* field) perform additional read request.

create_payload()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

delete_puppetclass (*synchronous=True, timeout=None, **kwargs*)

Remove a Puppet class from host

Here is an example of how to use this method:: `host.delete_puppetclass(data={'puppetclass_id': puppet.id})`

Constructs path: `/api/hosts/:hostgroup_id/puppetclass_ids/:id`

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

disassociate (*synchronous=True, timeout=None, **kwargs*)

Disassociate the host

Parameters **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

enc (*synchronous=True, timeout=None, **kwargs*)

Return external node classifier (ENC) information

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

errata (*synchronous=True, timeout=None, **kwargs*)

List errata available for the host

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

errata_applicability (*synchronous=True, timeout=None, **kwargs*)

Force regenerate errata applicability

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

errata_apply (*synchronous=True, timeout=None, **kwargs*)

Schedule errata for installation

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

get_facts (*synchronous=True, timeout=None, **kwargs*)

List all fact values of a given host

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

get_values ()

Correctly set the `owner_type` attribute.

install_content (*synchronous=True, timeout=None, **kwargs*)

Install content on one or more hosts

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

list_sparams (*synchronous=True, timeout=None, **kwargs*)

List all smart class parameters

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

list_smart_variables (*synchronous=True, timeout=None, **kwargs*)

List all smart variables

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

module_streams (*synchronous=True, timeout=None, **kwargs*)

List module_streams available for the host

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

owner_type

Return `_owner_type`.

packages (*synchronous=True, timeout=None, **kwargs*)

List packages installed on the host

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`. The format of the returned path depends on the value of `which`:

bulk/install_content `/api/hosts/:host_id/bulk/install_content`

errata `/api/hosts/:host_id/errata`

power `/api/hosts/:host_id/power`

errata/apply `/api/hosts/:host_id/errata/apply`

puppetclass_ids `/api/hosts/:host_id/puppetclass_ids`

smart_class_parameters `/api/hosts/:host_id/smart_class_parameters`

smart_variables `/api/hosts/:host_id/smart_class_variables`

module_streams `/api/hosts/:host_id/module_streams`

disassociate `/api/hosts/:host_id/disassociate`

Otherwise, call `super`.

power (*synchronous=True, timeout=None, **kwargs*)

Power the host off or on

Parameters **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

read (*entity=None, attrs=None, ignore=None, params=None*)

Deal with oddly named and structured data returned by the server.

For more information, see [Bugzilla #1235019](#) and [Bugzilla #1449749](#).

content_facet_attributes are returned only in case any of facet attributes were actually set.

traces_status and *traces_status_label* are returned only in case when katello-host-tools-tracer is installed on the host

Also add image to the response if needed, as `nailgun.entity_mixins.EntityReadMixin.read()` can’t initialize image.

resolve_traces (*synchronous=True, timeout=None, **kwargs*)

Resolve traces for the host

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

search (*fields=None, query=None, filters=None*)

Search for entities.

Parameters

- **fields** – A set naming which fields should be used when generating a search query. If `None`, all values on the entity are used. If an empty set, no values are used.
- **query** – A dict containing a raw search query. This is melded in to the generated search query like so: `{generated: query}.update({manual: query})`.
- **filters** – A dict. Used to filter search results locally.

Returns A list of entities, all of type `type(self)`.

traces (*synchronous=True, timeout=None, **kwargs*)

List services that need restarting for the host

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.

- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

update (*fields=None*)

Fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1235049](#).

Warning: Several attributes cannot be updated. See [Bugzilla #1235041](#).

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

upload_facts (*synchronous=True, timeout=None, **kwargs*)

Upload facts for a host, creating the host if required

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

class `nailgun.entities.HostCollection` (*server_config=None, **kwargs*)

A representation of a Host Collection entity.

create (*create_missing=None*)

Manually fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1654383](#).

create_payload ()

Rename `system_ids` to `system_uuids`.

class `nailgun.entities.HostCollectionErrata` (*server_config=None, **kwargs*)

A representation of a Host Collection Errata entity.

class `nailgun.entities.HostCollectionPackage` (*server_config=None, **kwargs*)

A representation of a Host Collection Package entity.

class `nailgun.entities.HostGroup` (*server_config=None, **kwargs*)

A representation of a Host Group entity.

add_puppetclass (*synchronous=True, timeout=None, **kwargs*)

Add a Puppet class to host group

Here is an example of how to use this method:: `hostgroup.add_puppetclass(data={'puppetclass_id': puppet.id})`

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

clone (*synchronous=True, timeout=None, **kwargs*)

Helper to clone an existing host group

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

create (*create_missing=None*)

Do extra work to fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1235377](#).

create_payload ()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

delete_puppetclass (*synchronous=True, timeout=None, **kwargs*)

Remove a Puppet class from host group

Here is an example of how to use this method:: `hostgroup.delete_puppetclass(data={'puppetclass_id': puppet.id})`

Constructs path: `/api/hostgroups/:hostgroup_id/puppetclass_ids/:id`

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

list_sparams (*synchronous=True, timeout=None, **kwargs*)

List all smart class parameters

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

list_smart_variables (*synchronous=True, timeout=None, **kwargs*)

List all smart variables

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`. The format of the returned path depends on the value of `which`:

clone `/api/hostgroups/:hostgroup_id/clone`

puppetclass_ids `/api/hostgroups/:hostgroup_id/puppetclass_ids`

rebuild_config `/api/hostgroups/:hostgroup_id/rebuild_config`

smart_class_parameters `/api/hostgroups/:hostgroup_id/smart_class_parameters`

smart_class_variables `/api/hostgroups/:hostgroup_id/smart_variables`

Otherwise, call `super`.

read (*entity=None, attrs=None, ignore=None, params=None*)

Deal with several bugs.

For more information, see:

- [Bugzilla #1235377](#)
- [Bugzilla #1235379](#)

- [Bugzilla #1450379](#)

rebuild_config (*synchronous=True, timeout=None, **kwargs*)

Helper to 'Rebuild orchestration config' of an existing host group

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

update (*fields=None*)

Deal with several bugs.

For more information, see:

- [Bugzilla #1235378](#)
- [Bugzilla #1235380](#)

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.HostPackage` (*server_config=None, **kwargs*)

A representation of a Host Package entity.

class `nailgun.entities.HostSubscription` (*server_config=None, **kwargs*)

A representation of a Host Subscription entity.

add_subscriptions (*synchronous=True, timeout=None, **kwargs*)

Helper for adding subscriptions to host

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

add_subscriptions `/hosts/<id>/add_subscriptions`

remove_subscriptions `/hosts/<id>/remove_subscriptions`

`super` is called otherwise.

remove_subscriptions (*synchronous=True, timeout=None, **kwargs*)

Helper for removing subscriptions from host

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

subscriptions (*synchronous=True, timeout=None, **kwargs*)

Helper for getting subscriptions from host

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

class `nailgun.entities.Image` (*server_config=None, **kwargs*)

A representation of a Image entity.

create_payload ()

Wrap submitted data within an extra dict.

read (*entity=None, attrs=None, ignore=None, params=None*)

Provide a default value for entity.

By default, `nailgun.entity_mixins.EntityReadMixin.read` provides a default value for entity like so:

```
entity = type(self) ()
```

However, `Image` requires that an `compute_resource` be provided, so this technique will not work. Do this instead:

```
entity = type(self) (compute_resource=self.compute_resource.id)
```

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.Interface` (*server_config=None, **kwargs*)

A representation of a Interface entity.

`host` must be passed in when this entity is instantiated.

Raises `TypeError` if `host` is not passed in.

read (*entity=None, attrs=None, ignore=None, params=None*)

Provide a default value for `entity`.

By default, `nailgun.entity_mixins.EntityReadMixin.read` provides a default value for `entity` like so:

```
entity = type(self)()
```

However, `Interface` requires that a `host` must be provided, so this technique will not work. Do this instead:

```
entity = type(self)(host=self.host)
```

In addition, some of interface fields are specific to its `type` and are never returned for different `type` so ignoring all the redundant fields.

search_normalize (*results*)

Append `host_id` to search results to be able to initialize found `Interface` successfully

class `nailgun.entities.JobInvocation` (*server_config=None, **kwargs*)

A representation of a Job invocation entity.

run (*synchronous=True, **kwargs*)

Helper to run existing job template

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **kwargs** – Arguments to pass to requests. 'data' supports next fields:
 - required:** `job_template_id/feature`, `targeting_type`, `search_query/bookmark_id`, `inputs`
 - optional:** `description_format`, `concurrency_control` `scheduling`, `ssh`, `recurrence`, `execution_timeout_interval`

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

class `nailgun.entities.JobTemplate` (*server_config=None, **kwargs*)

A representation of a Job Template entity.

create_payload ()

Wrap submitted data within an extra dict.

read (*entity=None, attrs=None, ignore=None, params=None*)

Ignore the template inputs when initially reading the job template. Look up each `TemplateInput` entity separately and afterwards add them to the `JobTemplate` entity.

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.KatelloStatus` (*server_config=None, **kwargs*)

A representation of a Status entity.

class `nailgun.entities.LibvirtComputeResource` (*server_config=None, **kwargs*)

A representation of a Libvirt Compute Resource entity.

class `nailgun.entities.LifecycleEnvironment` (*server_config=None, **kwargs*)

A representation of a Lifecycle Environment entity.

create_missing ()

Automatically populate additional instance attributes.

When a new lifecycle environment is created, it must either:

- Reference a parent lifecycle environment in the tree of lifecycle environments via the `prior` field, or
- have a name of “Library”.

Within a given organization, there can only be a single lifecycle environment with a name of ‘Library’. This lifecycle environment is at the root of a tree of lifecycle environments, so its `prior` field is blank.

This method finds the ‘Library’ lifecycle environment within the current organization and points to it via the `prior` field. This is not done if the current lifecycle environment has a name of ‘Library’.

class `nailgun.entities.Location` (*server_config=None, **kwargs*)

A representation of a Location entity.

create (*create_missing=None*)

Manually fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1216236](#).

create_payload ()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

read (*entity=None, attrs=None, ignore=None, params=None*)

Work around a bug in the server’s response.

Do not read the `realm` attribute. See [Bugzilla #1216234](#).

update (*fields=None*)

Fetch a complete set of attributes for this entity.

Beware of [Bugzilla #1236008](#): “Cannot use HTTP PUT to associate location with media”

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.Media` (*server_config=None, **kwargs*)

A representation of a Media entity.

Note: The `path_` field is named as such due to a naming conflict with `nailgun.entity_mixins.Entity.path()`.

create (*create_missing=None*)

Manually fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1219653](#).

create_payload()

Wrap submitted data within an extra dict and rename `path_`.

For more information on wrapping submitted data, see [Bugzilla #1151220](#).

read (*entity=None, attrs=None, ignore=None, params=None*)

Rename `path` to `path_`.

update (*fields=None*)

Fetch a complete set of attributes for this entity.

Beware of [Bugzilla #1261047](#): “PUT /api/v2/medium/:id doesn’t return all attributes”

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.Model` (*server_config=None, **kwargs*)

A representation of a Model entity.

class `nailgun.entities.ModuleStream` (*server_config=None, **kwargs*)

A representation of a Module Stream entity.

class `nailgun.entities.ModuleStreamContentViewFilter` (*server_config=None, **kwargs*)

A representation of a Content View Filter of type “modulemd”.

class `nailgun.entities.OSDefaultTemplate` (*server_config=None, **kwargs*)

A representation of a OS Default Template entity.

read (*entity=None, attrs=None, ignore=None, params=None*)

Fetch as many attributes as possible for this entity. Since `operatingsystem` is needed to instantiate, prepare the entity accordingly.

update_payload (*fields=None*)

Wrap payload in `os_default_template` relates to [Redmine #21169](#).

class `nailgun.entities.OVirtComputeResource` (*server_config=None, **kwargs*)

A representation for compute resources with Ovirt provider

read (*entity=None, attrs=None, ignore=None, params=None*)

Make sure, `password` is in the `ignore` list for read

class `nailgun.entities.OperatingSystem` (*server_config=None, **kwargs*)

A representation of a Operating System entity.

`major` is listed as a string field in the API docs, but only numeric values are accepted, and they may be no longer than 5 digits long. Also see [Bugzilla #1122261](#).

`title` field is valid despite not being listed in the API docs. This may be changed in future as both `title` and `description` fields share similar purpose. See [Bugzilla #1290359](#) for more details.

create_payload()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.OperatingSystemParameter` (*server_config=None, **kwargs*)

A representation of a parameter for an operating system.

`organization` must be passed in when this entity is instantiated.

Raises `TypeError` if `operatingsystem` is not passed in.

read (*entity=None, attrs=None, ignore=None, params=None*)

Provide a default value for *entity*.

By default, `nailgun.entity_mixins.EntityReadMixin.read` provides a default value for *entity* like so:

```
entity = type(self)()
```

However, `OperatingSystemParameter` requires that an `operatingsystem` be provided, so this technique will not work. Do this instead:

```
entity = type(self)(operatingsystem=self.operatingsystem.id)
```

class `nailgun.entities.Organization` (*server_config=None, **kwargs*)

A representation of an Organization entity.

create (*create_missing=None*)

Do extra work to fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1230873](#).

download_debug_certificate (*synchronous=True, timeout=None, **kwargs*)

Get debug certificate for particular organization.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of *which*:

download_debug_certificate /organizations/<id>/download_debug_certificate

simple_content_access/enable /organizations/<id>/simple_content_access/enable

simple_content_access/disable /organizations/<id>/simple_content_access/disable

simple_content_access/eligible /organizations/<id>/simple_content_access/eligible

subscriptions /organizations/<id>/subscriptions

subscriptions/upload /organizations/<id>/subscriptions/upload

subscriptions/delete_manifest /organizations/<id>/subscriptions/delete_manifest

subscriptions/refresh_manifest /organizations/<id>/subscriptions/refresh_manifest

sync_plans /organizations/<id>/sync_plans

rh_cloud/report /organizations/<id>/report

rh_cloud/inventory_sync /organizations/<id>/inventory_sync

Otherwise, call `super`.

read (*entity=None, attrs=None, ignore=None, params=None*)
Fetch as many attributes as possible for this entity.

Do not read the `realm` attribute. For more information, see [Bugzilla #1230873](#).

rh_cloud_download_report (*destination, **kwargs*)
Download RHCloud Inventory report.

Parameters

- **destination** – File path where report will be saved. e.g. `robot-telo_tmp_dir.joinpath(f'report_{gen_alphanumeric()}.tar.xz')`
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

rh_cloud_generate_report (*synchronous=True, timeout=None, **kwargs*)
Start RHCloud Inventory report generation process

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

rh_cloud_inventory_sync (*synchronous=True, timeout=None, **kwargs*)
Start inventory synchronization

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

sca_disable (*synchronous=True, timeout=None, **kwargs*)
Disable simple content access mode for particular organization.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

sca_eligible (*synchronous=True, timeout=None, **kwargs*)

Determine if the organization is eligible for simple content access mode.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

sca_enable (*synchronous=True, timeout=None, **kwargs*)

Enable simple content access mode for particular organization.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.

Returns The server’s response, with all content decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

update (*fields=None*)

Fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1232871](#).

<p>Warning: Several attributes cannot be updated. See Bugzilla #1230865.</p>

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.OverrideValue` (*server_config=None, **kwargs*)

A representation of a Override Value entity.

create_payload ()

Remove `smart_class_parameter_id` or `smart_variable_id`

read (*entity=None, attrs=None, ignore=None, params=None*)

Provide a default value for entity.

By default, `nailgun.entity_mixins.EntityReadMixin.read` provides a default value for `entity` like so:

```
entity = type(self)()
```

However, *OverrideValue* requires that an `smart_class_parameter` or `smart_variable` be provided, so this technique will not work. Do this instead:

```
entity = type(self) (
    smart_class_parameter=self.smart_class_parameter)
entity = type(self) (smart_variable=self.smart_variable)
```

class `nailgun.entities.Package` (*server_config=None, **kwargs*)

A representation of a Package entity.

class `nailgun.entities.PackageGroup` (*server_config=None, **kwargs*)

A representation of a Package Group entity.

class `nailgun.entities.PackageGroupContentViewFilter` (*server_config=None, **kwargs*)

A representation of a Content View Filter of type “package_group”.

class `nailgun.entities.Parameter` (*server_config=None, **kwargs*)

A representation of a Parameter entity.

read (*entity=None, attrs=None, ignore=None, params=None*)

Ignore path related fields as they’re never returned by the server and are only added to entity to be able to use proper path.

class `nailgun.entities.PartitionTable` (*server_config=None, **kwargs*)

A representation of a Partition Table entity.

Currently a Partition Table with one character in name cannot be created. For more information, see [Bugzilla #1229384](#).

Note: Having a name length of 2 had failures again. Updating the length to 4.

class `nailgun.entities.Permission` (*server_config=None, **kwargs*)

A representation of a Permission entity.

class `nailgun.entities.Ping` (*server_config=None, **kwargs*)

A representation of a Ping entity.

class `nailgun.entities.Product` (*server_config=None, **kwargs*)

A representation of a Product entity.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

sync `/products/<product_id>/sync`

`super` is called otherwise.

read (*entity=None, attrs=None, ignore=None, params=None*)

Fetch an attribute missing from the server’s response.

Also add sync plan to the response if needed, as `nailgun.entity_mixins.EntityReadMixin.read()` can’t initialize sync plan.

For more information, see [Bugzilla #1237283](#) and [nailgun#261](#).

search (*fields=None, query=None, filters=None*)
Search for entities with missing attribute

Parameters

- **fields** – A set naming which fields should be used when generating a search query. If `None`, all values on the entity are used. If an empty set, no values are used.
- **query** – A dict containing a raw search query. This is melded in to the generated search query like so: `{generated: query}.update({manual: query})`.
- **filters** – A dict. Used to filter search results locally.

Returns A list of entities, all of type `type(self)`.

For more information, see [Bugzilla #1237283](#) and [nailgun#261](#).

sync (*synchronous=True, timeout=None, **kwargs*)
Synchronize *repositories* in this product.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

class `nailgun.entities.ProductBulkAction` (*server_config=None, **kwargs*)
A representation of a Products bulk actions entity.

destroy (*synchronous=True, timeout=None, **kwargs*)
Helper to destroy one or more products.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

http_proxy (*synchronous=True, timeout=None, **kwargs*)
Helper to update the http proxy configuration on the repositories of one or more products.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

destroy `/products/bulk/destroy`

sync `/products/bulk/sync`

sync_plan `/products/bulk/sync_plan`

http_proxy `/products/bulk/http_proxy`

`super` is called otherwise.

sync (*synchronous=True, timeout=None, **kwargs*)

Helper to sync one or more products.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

sync_plan (*synchronous=True, timeout=None, **kwargs*)

Helper to sync one or more products.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

class `nailgun.entities.ProvisioningTemplate` (*server_config=None, **kwargs*)

A representation of a Provisioning Template entity.

build_pxe_default (*synchronous=True, timeout=None, **kwargs*)

Helper to build pxe default template.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

clone (*synchronous=True, timeout=None, **kwargs*)

Helper to clone an existing provision template

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

create_missing ()

Customize the process of auto-generating instance attributes.

Populate `template_kind` if:

- this template is not a snippet, and
- the `template_kind` instance attribute is unset.

create_payload ()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

build_pxe_default /provisioning_templates/build_pxe_default

clone /provisioning_templates/clone

revision /provisioning_templates/revision

`super` is called otherwise.

read (*entity=None, attrs=None, ignore=None, params=None*)

Provide a default value for `entity`.

By default, `nailgun.entity_mixins.EntityReadMixin.read` provides a default value for `entity` like so:

```
entity = type(self)()
```

However, `ProvisioningTemplate` requires that an `audit_comment` is provided, so this technique will not work.

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.PuppetClass` (*server_config=None, **kwargs*)

A representation of a Puppet Class entity.

list_scparams (*synchronous=True, timeout=None, **kwargs*)

List of smart class parameters for a specific Puppet class

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

list_smart_variables (*synchronous=True, timeout=None, **kwargs*)

List all smart variables

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`. The format of the returned path depends on the value of `which`:

smart_class_parameters `/api/puppetclasses/:puppetclass_id/smart_class_parameters`

Otherwise, call `super`.

search_normalize (*results*)

Flattens results. `nailgun.entity_mixins.EntitySearchMixin.search_normalize()` expects structure like `list(dict_1(name: class_1), dict_2(name: class_2))`, while Puppet Class entity returns dictionary with lists of subclasses split by main puppet class.

class `nailgun.entities.RHCIDeployment` (*server_config=None, **kwargs*)

A representation of a RHCI deployment entity.

deploy (*synchronous=True, timeout=None, **kwargs*)

Kickoff the RHCI deployment.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

deploy `/deployments/<id>/deploy`

`super` is called otherwise.

read (*entity=None, attrs=None, ignore=None, params=None*)

Normalize the data returned by the server.

The server’s JSON response is in this form:

```
{
  "organizations": [...],
  "lifecycle_environments": [...],
  "discovered_hosts": [...],
  "deployment": {...},
}
```

The inner “deployment” dict contains information about this entity. The response does not contain a value for the `rhev_engine_host` argument.

class `nailgun.entities.RPMContentViewFilter` (*server_config=None, **kwargs*)

A representation of a Content View Filter of type “rpm”.

class `nailgun.entities.Realm` (*server_config=None, **kwargs*)

A representation of a Realm entity.

create (*create_missing=None*)

Do extra work to fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1232855](#).

class `nailgun.entities.RecurringLogic` (*server_config=None, **kwargs*)

A representation of a Recurring logic entity.

cancel (*synchronous=True, timeout=None, **kwargs*)

Helper for canceling a recurring logic

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.RecurringLogic.path`. The format of the returned path depends on the value of `which`:

cancel `/foreman_tasks/api/recurring_logics/:id/cancel`

Otherwise, call `super`.

class `nailgun.entities.RegistrationCommand` (*server_config=None, **kwargs*)

A representation of a Role entity.

create_payload ()

Wrap submitted data within an extra dict. In addition, rename the `activation_keys_ids` field to `activation_keys`.

read (*entity=None, attrs=None, ignore=None, params=None*)

Override `nailgun.entity_mixins.EntityReadMixin.read()` to ignore all the fields and returns ‘registration_command’ output in dict

class `nailgun.entities.Report` (*server_config=None, **kwargs*)

A representation of a Report entity.

class `nailgun.entities.ReportTemplate` (*server_config=None, **kwargs*)

A representation of a Report Template entity.

clone (*synchronous=True, timeout=None, **kwargs*)

Helper to clone an existing report template

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

create_payload()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

generate (*synchronous=True, timeout=None, **kwargs*)

Helper to generate an existing report template

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

clone /report_templates/<id>/clone

generate /report_templates/<id>/generate

`super` is called otherwise.

report_data (*synchronous=True, timeout=None, **kwargs*)

Helper to call `report_data` on an existing scheduled report

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

schedule_report (*synchronous=True, timeout=None, **kwargs*)

Helper to schedule an existing report template

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.

- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.Repository` (*server_config=None, **kwargs*)

A representation of a Repository entity.

create_missing ()

Conditionally mark `docker_upstream_name` as required.

Mark `docker_upstream_name` as required if `content_type` is “docker”.

errata (*synchronous=True, timeout=None, **kwargs*)

List errata inside repository.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

files (*synchronous=True, timeout=None, **kwargs*)

List files associated with repository

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

import_uploads (*content_type=None, uploads=None, upload_ids=None, synchronous=True, timeout=None, **kwargs*)

Import uploads into a repository

It expects either a list of uploads or `upload_ids` (but not both).

Parameters

- **content_type** – content type (‘deb’, ‘docker_manifest’, ‘file’, ‘ostree’, ‘rpm’, ‘srpm’)

- **uploads** – Array of uploads to be imported
- **upload_ids** – Array of upload ids to be imported
- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

module_streams (*synchronous=True, timeout=None, **kwargs*)

List module_streams associated with repository

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

packages (*synchronous=True, timeout=None, **kwargs*)

List packages associated with repository

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

errata /repositories/<id>/errata

files /repositories/<id>/files

packages /repositories/<id>/packages

module_streams /repositories/<id>/module_streams

remove_content /repositories/<id>/remove_content

sync /repositories/<id>/sync

upload_content /repositories/<id>/upload_content

import_uploads /repositories/<id>/import_uploads

`super` is called otherwise.

read (*entity=None, attrs=None, ignore=None, params=None*)

Ignore `organization` field as it's never returned by the server and is only added to `entity` to be able to use `organization` path dependent helpers and also `upstream_password` as it is not returned for security reasons.

remove_content (*synchronous=True, timeout=None, **kwargs*)

Remove content from a repository

It expects `content/packages/docker` manifests ids sent as data. Here is an example of how to use this method:

```
repository.remove_content(data={'ids': [package.id]})
```

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

sync (*synchronous=True, timeout=None, **kwargs*)

Helper for syncing an existing repository.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

upload_content (*synchronous=True, timeout=None, **kwargs*)

Upload a file or files to the current repository.

Here is an example of how to upload content:

```
with open('my_content.rpm') as content:
    repo.upload_content(files={'content': content})
```

This method accepts the same keyword arguments as Requests. As a result, the following examples can be adapted for use here:

- [POST a Multipart-Encoded File](#)
- [POST Multiple Multipart-Encoded Files](#)

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

Raises `nailgun.entities.APIResponseError` – If the response has a status other than “success”.

class `nailgun.entities.RepositorySet` (*server_config=None, **kwargs*)

A representation of a Repository Set entity

available_repositories (***kwargs*)

Lists available repositories for the repository set

Parameters **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

disable (*synchronous=True, timeout=None, **kwargs*)

Disables the RedHat Repository

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

enable (*synchronous=True, timeout=None, **kwargs*)

Enables the RedHat Repository

RedHat Repos needs to be enabled first, so that we can sync it.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of *which*:

available_repositories `/repository_sets/<id>/available_repositories`

enable `/repository_sets/<id>/enable`

disable `/repository_sets/<id>/disable`

`super` is called otherwise.

read (*entity=None, attrs=None, ignore=None, params=None*)

Provide a default value for *entity*.

By default, `nailgun.entity_mixins.EntityReadMixin.read` provides a default value for *entity* like so:

```
entity = type(self)()
```

However, `RepositorySet` requires that a *product* be provided, so this technique will not work. Do this instead:

```
entity = type(self)(product=self.product.id)
```

class `nailgun.entities.Role` (*server_config=None, **kwargs*)

A representation of a Role entity.

clone (*synchronous=True, timeout=None, **kwargs*)

Helper to clone an existing Role

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

create_payload()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`. The format of the returned path depends on the value of *which*:

clone `/api/roles/:role_id/clone`

Otherwise, call `super`.

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.RoleLDAPGroups` (*server_config=None, **kwargs*)

A representation of a Role LDAP Groups entity.

class `nailgun.entities.SSHKey` (*server_config=None, **kwargs*)

A representation of a SSH Key entity.

`user` must be passed in when this entity is instantiated.

Raises `TypeError` if `user` is not passed in.

read (*entity=None, attrs=None, ignore=None, params=None*)

Provide a default value for `entity`.

By default, `nailgun.entity_mixins.EntityReadMixin.read` provides a default value for `entity` like so:

```
entity = type(self)()
```

However, `SSHKey` requires that an `user` be provided, so this technique will not work. Do this instead:

```
entity = type(self)(user=self.user.id)
```

search_normalize (*results*)

Append `user id` to search results to be able to initialize found `User` successfully

class `nailgun.entities.ScapContents` (*server_config=None, **kwargs*)

A representation of a ScapContents entity.

create (*create_missing=None*)

Do extra work to fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1381129](#).

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`. The format of the returned path depends on the value of *which*:

xml `api/compliance/scap_contents/:id/xml`

Otherwise, call `super`.

read (*entity=None, attrs=None, ignore=None, params=None*)

Override `nailgun.entity_mixins.EntityReadMixin.read()` to ignore the `scap_file`

update (*fields=None*)

Fetch a complete set of attributes for this entity.

xml (*synchronous=True, timeout=None, **kwargs*)

Download an SCAP content as XML

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

class `nailgun.entities.Setting` (*server_config=None, **kwargs*)

A representation of a Setting entity.

read (*entity=None, attrs=None, ignore=None, params=None*)

Override `nailgun.entity_mixins.EntityReadMixin.read()` to ignore the `created_at` and `updated_at`

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.SmartClassParameters` (*server_config=None, **kwargs*)

A representation of a Smart Class Parameters.

read (*entity=None, attrs=None, ignore=None, params=None*)

Do not read the `hidden_value` attribute.

class `nailgun.entities.SmartProxy` (*server_config=None, **kwargs*)

A representation of a Smart Proxy entity.

import_puppetclasses (*synchronous=True, timeout=None, **kwargs*)

Import puppet classes from puppet Capsule.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`. The format of the returned path depends on the value of `which`:

refresh `/api/smart_proxies/:id/refresh`

Otherwise, call `super`.

read (*entity=None, attrs=None, ignore=None, params=None*)

Ignore `download_policy` field as it's never returned by the server.

For more information, see [Bugzilla #1486609](#).

refresh (*synchronous=True, timeout=None, **kwargs*)
Refresh Capsule features

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

update (*fields=None*)
Fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1262037](#).

update_payload (*fields=None*)
Wrap submitted data within an extra dict.

class `nailgun.entities.SmartVariable` (*server_config=None, **kwargs*)
A representation of a Smart Variable entity.

create_payload ()
Wrap submitted data within an extra dict.

read (*entity=None, attrs=None, ignore=None, params=None*)
Do not read the `hidden_value` attribute.

update_payload (*fields=None*)
Wrap submitted data within an extra dict.

class `nailgun.entities.Snapshot` (*server_config=None, **kwargs*)
A representation of a Snapshot entity. Foreman_snapshot as mentioned in the plugin: https://github.com/ATIX-AG/foreman_snapshot_management # Read Snapshot `Snapshot(host=<host_id>, id=<snapshot_id>).read()` # Search Snapshots `Snapshot(host=<host_id>).search()` # Create Snapshot `Snapshot(host=<host_id>, name=<snapshot_name>).create()` # Update Snapshot `Snapshot(host=<host_id>, id=<snapshot_id>, description=<snapshot_description>).update()` # Revert Snapshot `Snapshot(host=<host_id>, id=<snapshot_id>).revert()` # Delete Snapshot `Snapshot(host=<host_id>, id=<snapshot_id>).delete()`

path (*which=None*)
Extend `nailgun.entity_mixins.Entity.path`. `revert /api/v2/hosts/<host-id>/snapshots/<snapshot-id>/revert`

read (*entity=None, attrs=None, ignore=None, params=None*)
Provide a default value for entity.

By default, `nailgun.entity_mixins.EntityReadMixin.read` provides a default value for entity like so:

```
entity = type(self)()
```

However, `Snapshot` requires that an `host` be provided, so this technique will not work. Do this instead:


```
entity = type(self) (host=self.host)
```

revert (***kwargs*)

Rollbacks the Snapshot

Makes HTTP PUT call to revert the snapshot.

search_normalize (*results*)

Append host id to search results to be able to initialize found *Snapshot* successfully

class `nailgun.entities.Srpms` (*server_config=None, **kwargs*)

A representation of a Srpms entity.

class `nailgun.entities.Status` (*server_config=None, **kwargs*)

A representation of a Status entity.

class `nailgun.entities.Subnet` (*server_config=None, **kwargs*)

A representation of a Subnet entity.

create_payload ()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

In addition, rename the `from_` field to `from`.

read (*entity=None, attrs=None, ignore=None, params=None*)

Fetch as many attributes as possible for this entity.

Do not read the `discovery` attribute. For more information, see [Bugzilla #1217146](#).

In addition, rename the `from_` field to `from`.

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class `nailgun.entities.Subscription` (*server_config=None, **kwargs*)

A representation of a Subscription entity.

delete_manifest (*synchronous=True, timeout=1500, **kwargs*)

Delete manifest from Red Hat provider.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

manifest_history (*synchronous=True, timeout=None, **kwargs*)

Obtain manifest history for subscriptions.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

delete_manifest `/katello/api/v2/organizations/:organization_id/subscriptions/delete_manifest`

manifest_history `/katello/api/v2/organizations/:organization_id/subscriptions/manifest_history`

refresh_manifest `/katello/api/v2/organizations/:organization_id/subscriptions/refresh_manifest`

upload `/katello/api/v2/organizations/:organization_id/subscriptions/upload`

read (*entity=None, attrs=None, ignore=None, params=None*)

Ignore `organization` field as it’s never returned by the server and is only added to entity to be able to use organization path dependent helpers.

refresh_manifest (*synchronous=True, timeout=1500, **kwargs*)

Refresh previously imported manifest for Red Hat provider.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

upload (*synchronous=True, timeout=1500, **kwargs*)

Upload a subscription manifest.

Here is an example of how to use this method:

```
with open('my_manifest.zip') as manifest:
    sub.upload({'organization_id': org.id}, manifest)
```

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.

- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

class `nailgun.entities.SyncPlan` (*server_config=None, **kwargs*)

A representation of a Sync Plan entity.

organization must be passed in when this entity is instantiated.

Raises `TypeError` if `organization` is not passed in.

add_products (*synchronous=True, timeout=None, **kwargs*)

Add products to this sync plan.

Note: The `synchronous` argument has no effect in certain versions of Satellite. See [Bugzilla #1199150](#).

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

create_payload ()

Convert `sync_date` to a string.

The `sync_date` instance attribute on the current object is not affected. However, the `'sync_date'` key in the dict returned by `create_payload` is a string.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

add_products `/katello/api/v2/organizations/:organization_id/sync_plans/:sync_plan_id/add_products`

remove_products `/katello/api/v2/organizations/:organization_id/sync_plans/:sync_plan_id/remove_products`

read (*entity=None, attrs=None, ignore=None, params=None*)

Provide a default value for `entity`.

By default, `nailgun.entity_mixins.EntityReadMixin.read` provides a default value for `entity` like so:

```
entity = type(self)()
```

However, *SyncPlan* requires that an organization be provided, so this technique will not work. Do this instead:

```
entity = type(self)(organization=self.organization.id)
```

remove_products (*synchronous=True, timeout=None, **kwargs*)
Remove products from this sync plan.

Note: The `synchronous` argument has no effect in certain versions of Satellite. See [Bugzilla #1199150](#).

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

update_payload (*fields=None*)
Convert `sync_date` to a string if datetime object provided.

class `nailgun.entities.TailoringFile` (*server_config=None, **kwargs*)
A representation of a Tailoring File entity.

create (*create_missing=None*)
Do extra work to fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1381129](#).

create_payload (***kwargs*)
Wrap submitted data within an extra dict.

read (*entity=None, attrs=None, ignore=None, params=None*)
Ignore `scap_file` field.

update (*fields=None*)
Fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1234964](#).

class `nailgun.entities.Template` (*server_config=None, **kwargs*)
A representation of a Template entity.

exports (*synchronous=True, timeout=None, **kwargs*)
Helper to export templates

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.

- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

imports (*synchronous=True, timeout=None, **kwargs*)
Helper to import templates

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server’s response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)
Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

import /templates/import

export /templates/export

class `nailgun.entities.TemplateCombination` (*server_config=None, **kwargs*)
A representation of a Template Combination entity.

class `nailgun.entities.TemplateInput` (*server_config=None, **kwargs*)
A representation of a Template Input entity.

read (*entity=None, attrs=None, ignore=None, params=None*)
Create a JobTemplate object before calling `read()` ignore ‘advanced’

class `nailgun.entities.TemplateKind` (*server_config=None, **kwargs*)
A representation of a Template Kind entity.

Unusually, the `/api/v2/template_kinds/:id` path is totally unsupported.

class `nailgun.entities.User` (*server_config=None, **kwargs*)
A representation of a User entity.

The LDAP authentication source with an ID of 1 is internal. It is nearly guaranteed to exist and be functioning. Thus, `auth_source` is set to “1” by default for a practical reason: it is much easier to use internal authentication than to spawn LDAP authentication servers for each new user.

create_payload ()
Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

read (*entity=None, attrs=None, ignore=None, params=None*)
Do not read the password argument.

update (*fields=None*)

Fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1235012](#).

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

class nailgun.entities.**UserGroup** (*server_config=None, **kwargs*)

A representation of a User Group entity.

create (*create_missing=None*)

Do extra work to fetch a complete set of attributes for this entity.

For more information, see [Bugzilla #1301658](#).

create_payload ()

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

read (*entity=None, attrs=None, ignore=None, params=None*)

Work around [Redmine #9594](#).

An HTTP GET request to path ('self') does not return the admin attribute, even though it should.

Also see [Bugzilla #1197871](#).

update_payload (*fields=None*)

Wrap submitted data within an extra dict.

For more information, see [Bugzilla #1151220](#).

class nailgun.entities.**VMWareComputeResource** (*server_config=None, **kwargs*)

A representation for compute resources with Vmware provider

read (*entity=None, attrs=None, ignore=None, params=None*)

Make sure, password is in the ignore list for read

class nailgun.entities.**VirtWhoConfig** (*server_config=None, **kwargs*)

A representation of a VirtWho Config entity.

create_payload ()

Wraps config in extra dict

deploy_script (*synchronous=True, timeout=None, **kwargs*)

Helper for Config's deploy_script method.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

get_organization_configs (*synchronous=True, timeout=None, **kwargs*)

Unusually, the `/foreman_virt_who_configure/api/v2/organizations/`

:organization_id/configs path is totally unsupported. Support to List of virt-who configurations per organization.

Parameters

- **synchronous** – What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return the server's response otherwise.
- **timeout** – Maximum number of seconds to wait until timing out. Defaults to `nailgun.entity_mixins.TASK_TIMEOUT`.
- **kwargs** – Arguments to pass to requests.

Returns The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` If the server responds with an HTTP 4XX or 5XX message.

path (*which=None*)

Extend `nailgun.entity_mixins.Entity.path`.

The format of the returned path depends on the value of `which`:

deploy_script `/foreman_virt_who_configure/api/v2/configs/:id/deploy_script`

configs `/foreman_virt_who_configure/api/v2/organizations/:organization_id/configs`

`super` is called otherwise.

read (*entity=None, attrs=None, ignore=None, params=None*)

Override `nailgun.entity_mixins.EntityReadMixin.read()` to ignore the `hypervisor_password`

update_payload (*fields=None*)

Wraps config in extra dict

2.1.2 nailgun.entity_mixins

Defines a set of mixins that provide tools for interacting with entities.

exception `nailgun.entity_mixins.BadValueError`

Indicates that an inappropriate value was assigned to an entity.

`nailgun.entity_mixins.CREATE_MISSING = False`

Used by `nailgun.entity_mixins.EntityCreateMixin.create_raw()`.

This is the default value for the `create_missing` argument to `nailgun.entity_mixins.EntityCreateMixin.create_raw()`. Keep in mind that this variable also affects methods which call `create_raw`, such as `nailgun.entity_mixins.EntityCreateMixin.create_json()`.

`nailgun.entity_mixins.DEFAULT_SERVER_CONFIG = None`

A `nailgun.config.ServerConfig` object.

Used by `nailgun.entity_mixins.Entity`.

class `nailgun.entity_mixins.Entity` (*server_config=None, **kwargs*)

A representation of a logically related set of API paths.

This class is rather useless as is, and it is intended to be subclassed. Subclasses can specify two useful types of information:

- `fields`

- metadata

Fields and metadata are represented by the `_fields` and `_meta` instance attributes, respectively. Here is an example of how to define and instantiate an entity:

```
>>> class User(Entity):
...     def __init__(self, server_config=None, **kwargs):
...         self._fields = {
...             'name': StringField(),
...             'supervisor': OneToOneField('User'),
...             'subordinate': OneToManyField('User'),
...         }
...         self._meta = {'api_path': 'api/users'}
...         return super(User, self).__init__(server_config, **kwargs)
...
>>> user = User(
...     name='Alice',
...     supervisor=User(id=1),
...     subordinate=[User(id=3), User(id=4)],
... )
>>> user.name == 'Alice'
True
>>> user.supervisor.id = 1
True
```

The canonical procedure for initializing foreign key fields, shown above, is powerful but verbose. It is tiresome to write statements such as `[User(id=3), User(id=4)]`. As a convenience, entity IDs may be given:

```
>>> User(name='Alice', supervisor=1, subordinate=[3, 4])
>>> user.name == 'Alice'
True
>>> user.supervisor.id = 1
True
```

An entity object is useless if you are unable to use it to communicate with a server. The solution is to provide a `nailgun.config.ServerConfig` when instantiating a new entity.

1. If the `server_config` argument is specified, then that is used.
2. Otherwise, if `nailgun.entity_mixins.DEFAULT_SERVER_CONFIG` is set, then that is used.
3. Otherwise, call `nailgun.config.ServerConfig.get()`.

An entity's server configuration is stored as a private instance variable and is used by mixin methods, such as `nailgun.entity_mixins.Entity.path()`. For more information on server configuration objects, see `nailgun.config.BaseServerConfig`.

Raises

- `nailgun.entity_mixins.NoSuchFieldError` – If a value is assigned to a non-existent field.
- `nailgun.entity_mixins.BadValueError` – If an inappropriate value is assigned to a field.

compare (*other*, *filter_fcn*=None)

Returns True if properties can be compared in terms of eq. Entity's Fields can be filtered accordingly to 'filter_fcn'. This callable receives field's name as first parameter and field itself as second parameter. It must return True if field's value should be included on comparison and False otherwise. If not provided field's marked as unique will not be compared by default. 'id' and 'name' are examples of unique fields commonly ignored. Check Entities fields for fields marked with 'unique=True'

Parameters

- **other** – entity to compare
- **filter_fcn** – callable

Returns boolean**get_fields()**

Return a copy of the fields on the current object.

Returns A dict mapping field names to :class:'nailgun.entity_fields.Field' objects.**get_values()**

Return a copy of field values on the current object.

This method is almost identical to `vars(self).copy()`. However, only instance attributes that correspond to a field are included in the returned dict.

Returns A dict mapping field names to user-provided values.**path** (*which=None*)

Return the path to the current entity.

Return the path to base entities of this entity's type if:

- which is 'base', or
- which is None and instance attribute `id` is unset.

Return the path to this exact entity if instance attribute `id` is set and:

- which is 'self', or
- which is None.

Raise *NoSuchPathError* otherwise.

Child classes may choose to extend this method, especially if a child entity offers more than the two URLs supported by default. If extended, then the extending class should check for custom parameters before calling `super`:

```
def path(self, which):
    if which == 'custom':
        return urljoin(...)
    super(ChildEntity, self).__init__(which)
```

This will allow the extending method to accept a custom parameter without accidentally raising a *NoSuchPathError*.

Parameters **which** – A string. Optional. Valid arguments are 'self' and 'base'.**Returns** A string. A fully qualified URL.**Raises** *nailgun.entity_mixins.NoSuchPathError* – If no path can be built.**to_json()**

Create a JSON encoded string with Entity properties. Ex:

```
>>> from nailgun import entities, config
>>> kwargs = {
...     'id': 1,
...     'name': 'Nailgun Org',
... }
>>> org = entities.Organization(config.ServerConfig('foo'), **kwargs)
```

(continues on next page)

(continued from previous page)

```
>>> org.to_json()
'{"id": 1, "name": "Nailgun Org"}'
```

Returns str**to_json_dict** (*filter_fcn=None*)

Create a dict with Entity properties for json encoding. It can be overridden by subclasses for each standard serialization doesn't work. By default it call `_to_json_dict` on OneToOne fields and build a list calling the same method on each OneToMany object's fields.

Fields can be filtered accordingly to 'filter_fcn'. This callable receives field's name as first parameter and fields itself as second parameter. It must return True if field's value should be included on dict and False otherwise. If not provided field will not be filtered.

Returns dct**class** `nailgun.entity_mixins.EntityCreateMixin`

This mixin provides the ability to create an entity.

The methods provided by this class work together. The call tree looks like this:

```
create
├─ create_json
│   └─ create_raw
│       ├── create_missing
│       └─ create_payload
```

In short, here is what the methods do:

`create_missing()` Populate required fields with random values. Required fields that already have a value are not populated. This method is not called by default.

`create_payload()` Assemble a payload of data that can be encoded and sent to the server.

`create_raw()` Make an HTTP POST request to the server, including the payload.

`create_json()` Check the server's response for errors and decode the response.

`create()` Create a `nailgun.entity_mixins.Entity` object representing the created entity and populate its fields with data returned from the server.

See the individual methods for more detailed information.

create (*create_missing=None*)

Create an entity.

Call `create_json()`, use the response to populate a new object of type `type(self)` and return that object.

This method requires that a method named "read" be available on the current object. A method named "read" will be available if `EntityReadMixin` is present in the inheritance tree, and using the method provided by that mixin is the recommended technique for making a "read" method available.

This method makes use of `EntityReadMixin.read()` for two reasons. First, calling that method is simply convenient. Second, the server frequently returns weirdly structured, inconsistently named or straight-up broken responses, and quite a bit of effort has gone in to decoding server responses so `EntityReadMixin.read()` can function correctly. Calling `read` allows this method to re-use the decoding work that has been done for that method.

Returns An instance of type `type(self)`.

Return type *nailgun.entity_mixins.Entity*

Raises `AttributeError` if a method named “read” is not available on the current object.

create_json (*create_missing=None*)

Create an entity.

Call `create_raw()`. Check the response status code, decode JSON and return the decoded JSON as a dict.

Returns A dict. The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` if the response has an HTTP 4XX or 5XX status code.

Raises `ValueError` If the response JSON can not be decoded.

create_missing ()

Automagically populate all required instance attributes.

Iterate through the set of all required class *nailgun.entity_fields.Field* defined on `type(self)` and create a corresponding instance attribute if none exists. Subclasses should override this method if there is some relationship between two required fields.

Returns Nothing. This method relies on side-effects.

create_payload ()

Create a payload of values that can be sent to the server.

See `_payload()`.

create_raw (*create_missing=None*)

Create an entity.

Possibly call `create_missing()`. Then make an HTTP POST call to `self.path('base')`. The request payload consists of whatever is returned by `create_payload()`. Return the response.

Parameters `create_missing` – Should `create_missing()` be called? In other words, should values be generated for required, empty fields? Defaults to *nailgun.entity_mixins.CREATE_MISSING*.

Returns A `requests.response` object.

class *nailgun.entity_mixins.EntityDeleteMixin*

This mixin provides the ability to delete an entity.

The methods provided by this class work together. The call tree looks like this:

```
delete → delete_raw
```

In short, here is what the methods do:

delete_raw() Make an HTTP DELETE request to the server.

delete() Check the server’s response for errors and decode the response.

delete (*synchronous=True, timeout=None*)

Delete the current entity.

Call `delete_raw()` and check for an HTTP 4XX or 5XX response. Return either the JSON-decoded response or information about a completed foreman task.

Parameters `synchronous` – A boolean. What should happen if the server returns an HTTP 202 (accepted) status code? Wait for the task to complete if `True`. Immediately return a response otherwise.

Returns A dict. Either the JSON-decoded response or information about a foreman task.

Raises `requests.exceptions.HTTPError` if the response has an HTTP 4XX or 5XX status code.

Raises `ValueError` If an HTTP 202 response is received and the response JSON can not be decoded.

Raises `nailgun.entity_mixins.TaskTimeoutError` – If an HTTP 202 response is received, `synchronous` is `True` and the task times out.

`delete_raw()`

Delete the current entity.

Make an HTTP DELETE call to `self.path('base')`. Return the response.

Returns A `requests.response` object.

class `nailgun.entity_mixins.EntityReadMixin`

This mixin provides the ability to read an entity.

The methods provided by this class work together. The call tree looks like this:

```
read → read_json → read_raw
```

In short, here is what the methods do:

`read_raw()` Make an HTTP GET request to the server.

`read_json()` Check the server's response for errors and decode the response.

`read()` Create a `nailgun.entity_mixins.Entity` object representing the created entity and populate its fields with data returned from the server.

See the individual methods for more detailed information.

read (*entity=None, attrs=None, ignore=None, params=None*)

Get information about the current entity.

1. Create a new entity of type `type(self)`.
2. Call `read_json()` and capture the response.
3. Populate the entity with the response.
4. Return the entity.

Step one is skipped if the `entity` argument is specified. Step two is skipped if the `attrs` argument is specified. Step three is modified by the `ignore` argument.

All of an entity's one-to-one and one-to-many relationships are populated with objects of the correct type. For example, if `SomeEntity.other_entity` is a one-to-one relationship, this should return `True`:

```
isinstance(
    SomeEntity(id=N).read().other_entity,
    nailgun.entity_mixins.Entity
)
```

Additionally, both of these commands should succeed:

```
SomeEntity(id=N).read().other_entity.id
SomeEntity(id=N).read().other_entity.read().other_attr
```

In the example above, `other_entity.id` is the **only** attribute with a meaningful value. Calling `other_entity.read` populates the remaining entity attributes.

Parameters

- **entity** (`nailgun.entity_mixins.Entity`) – The object to be populated and returned. An object of type `type(self)` by default.
- **attrs** – A dict. Data used to populate the object’s attributes. The response from `nailgun.entity_mixins.EntityReadMixin.read_json()` by default.
- **ignore** – A set of attributes which should not be read from the server. This is mainly useful for attributes like a password which are not returned.

Returns An instance of type `type(self)`.

Return type `nailgun.entity_mixins.Entity`

read_json (*params=None*)

Get information about the current entity.

Call `read_raw()`. Check the response status code, decode JSON and return the decoded JSON as a dict.

Returns A dict. The server’s response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` if the response has an HTTP 4XX or 5XX status code.

Raises `ValueError` If the response JSON can not be decoded.

read_raw (*params=None*)

Get information about the current entity.

Make an HTTP GET call to `self.path('self')`. Return the response.

Returns A `requests.response` object.

class `nailgun.entity_mixins.EntitySearchMixin`

This mixin provides the ability to search for entities.

The methods provided by this class work together. The call tree looks like this:

```

search
├── search_json
│   └── search_raw
│       └── search_payload
├── search_normalize
└── search_filter

```

In short, here is what the methods do:

search_payload() Assemble a search query that can be encoded and sent to the server.

search_raw() Make an HTTP GET request to the server, including the payload.

search_json() Check the server’s response for errors and decode the response.

search_normalize() Normalize search results so they can be used to create new entities.

search() Create one or more `nailgun.entity_mixins.Entity` objects representing the found entities and populate their fields.

search_filter() Read all entities and locally filter them.

See the individual methods for more detailed information.

search (*fields=None, query=None, filters=None*)

Search for entities.

At its simplest, this method searches for all entities of a given kind. For example, to ask for all *nailgun.entities.LifecycleEnvironment* entities:

```
LifecycleEnvironment().search()
```

Values on an entity are used to generate a search query, and the `fields` argument can be used to specify which fields should be used when generating a search query:

```
lc_env = LifecycleEnvironment(name='foo', organization=1)
results = lc_env.search() # Search by name and organization.
results = lc_env.search({'name', 'organization'}) # Same.
results = lc_env.search({'name'}) # Search by name.
results = lc_env.search({'organization'}) # Search by organization
results = lc_env.search(set()) # Search for all lifecycle envs.
results = lc_env.search({'library'}) # Error!
```

In some cases, the simple search queries that can be generated by NailGun are not sufficient. In this case, you can pass in a raw search query instead. For example, to search for all lifecycle environments with a name of ‘foo’:

```
LifecycleEnvironment().search(query={'search': 'name="foo"'})
```

The example above is rather pointless: it is easier and more concise to use a generated query. But — and this is a **very** important “but” — the manual search query is melded in to the generated query. This can be used to great effect:

```
LifecycleEnvironment(name='foo').search(query={'per_page': 50})
```

For examples of what the final search queries look like, see *search_payload()*. (That method also accepts the `fields` and `query` arguments.)

In some cases, the server’s search facilities may be insufficient, or it may be inordinately difficult to craft a search query. In this case, you can filter search results locally. For example, to ask the server for a list of all lifecycle environments and then locally search through the results for the lifecycle environment named “foo”:

```
LifecycleEnvironment().search(filters={'name': 'foo'})
```

Be warned that filtering locally can be **very** slow. NailGun must `read()` every single entity returned by the server before filtering results. This is because the values used in the filtering process may not have been returned by the server in the initial response to the search.

The fact that all entities are read when `filters` is specified can be used to great effect. For example, this search returns a fully populated list of every single lifecycle environment:

```
LifecycleEnvironment().search(filters={})
```

Parameters

- **fields** – A set naming which fields should be used when generating a search query. If `None`, all values on the entity are used. If an empty set, no values are used.
- **query** – A dict containing a raw search query. This is melded in to the generated search query like so: `{generated: query}.update({manual: query})`.

- **filters** – A dict. Used to filter search results locally.

Returns A list of entities, all of type `type(self)`.

static search_filter (*entities, filters*)

Read all `entities` and locally filter them.

This method can be used like so:

```
entities = EntitySearchMixin(entities, {'name': 'foo'})
```

In this example, only entities where `entity.name == 'foo'` holds true are returned. An arbitrary number of field names and values may be provided as filters.

Note: This method calls `EntityReadMixin.read()`. As a result, this method only works when called on a class that also inherits from `EntityReadMixin`.

Parameters

- **entities** – A list of `Entity` objects. All list items should be of the same type.
- **filters** – A dict in the form `{field_name: field_value, ...}`.

Raises `nailgun.entity_mixins.NoSuchFieldError` – If any of the fields named in `filters` do not exist on the entities being filtered.

Raises `NotImplementedError` If any of the fields named in `filters` are a `nailgun.entity_fields.OneToOneField` or `nailgun.entity_fields.OneToOneManyField`.

search_json (*fields=None, query=None*)

Search for entities.

Call `search_raw()`. Check the response status code, decode JSON and return the decoded JSON as a dict.

Warning: Subclasses that override this method should not alter the `fields` or `query` arguments. (However, subclasses that override this method may still alter the server's response.) See `search_normalize()` for details.

Parameters

- **fields** – See `search()`.
- **query** – See `search()`.

Returns A dict. The server's response, with all JSON decoded.

Raises `requests.exceptions.HTTPError` if the response has an HTTP 4XX or 5XX status code.

Raises `ValueError` If the response JSON can not be decoded.

search_normalize (*results*)

Normalize search results so they can be used to create new entities.

See `search()` for an example of how to use this method. Here's a simplified example:

```
results = self.search_json()
results = self.search_normalize(results)
entity = SomeEntity(some_cfg, **results[0])
```

At this time, it is possible to parse all search results without knowing what search query was sent to the server. However, it is possible that certain responses can only be parsed if the search query is known. If that is the case, this method will be given a new `payload` argument, where `payload` is the query sent to the server.

As a precaution, the following is highly recommended:

- `search()` may alter fields and query at will.
- `search_payload()` may alter fields and query in an idempotent manner.
- No other method should alter fields or query.

Parameters `results` – A list of dicts, where each dict is a set of attributes for one entity. The contents of these dicts are as is returned from the server.

Returns A list of dicts, where each dict is a set of attributes for one entity. The contents of these dicts have been normalized and can be used to instantiate entities.

search_payload (*fields=None, query=None*)

Create a search query.

Do the following:

1. Generate a search query. By default, all values returned by `nailgun.entity_mixins.Entity.get_values()` are used. If `fields` is specified, only the named values are used.
2. Merge query in to the generated search query.
3. Return the result.

The rules for generating a search query can be illustrated by example. Let's say that we have an entity with an `nailgun.entity_fields.IntegerField`, a `nailgun.entity_fields.OneToOneField` and a `nailgun.entity_fields.OneToManyField`:

```
>>> some_entity = SomeEntity(id=1, one=2, many=[3, 4])
>>> fields = some_entity.get_fields()
>>> isinstance(fields['id'], IntegerField)
True
>>> isinstance(fields['one'], OneToOneField)
True
>>> isinstance(fields['many'], OneToManyField)
True
```

This method appends “_id” and “_ids” on to the names of each `OneToOneField` and `OneToManyField`, respectively:

```
>>> some_entity.search_payload()
{'id': 1, 'one_id': 2, 'many_ids': [3, 4]}
```

By default, all fields are used. But you can specify a set of field names to use:

```
>>> some_entity.search_payload({'id'})
{'id': 1}
>>> some_entity.search_payload({'one'})
{'one_id': 2}
```

(continues on next page)

(continued from previous page)

```
>>> some_entity.search_payload({'id', 'one'})
{'id': 1, 'one_id': 2}
```

If a query is specified, it is merged in to the generated query:

```
>>> some_entity.search_payload(query={'id': 5})
{'id': 5, 'one_id': 2, 'many_ids': [3, 4]}
>>> some_entity.search_payload(query={'per_page': 1000})
{'id': 1, 'one_id': 2, 'many_ids': [3, 4], 'per_page': 1000}
```

Warning: This method currently generates an extremely naive search query that will be wrong in many cases. In addition, Satellite currently accepts invalid search queries without complaint. Make sure to check the API documentation for your version of Satellite against what this method produces.

Parameters

- **fields** – See [search\(\)](#).
- **query** – See [search\(\)](#).

Returns A dict that can be encoded as JSON and used in a search.

search_raw (*fields=None, query=None*)

Search for entities.

Make an HTTP GET call to `self.path('base')`. Return the response.

Warning: Subclasses that override this method should not alter the `fields` or `query` arguments. (However, subclasses that override this method may still alter the server's response.) See [search_normalize\(\)](#) for details.

Parameters

- **fields** – See [search\(\)](#).
- **query** – See [search\(\)](#).

Returns A `requests.response` object.

class `nailgun.entity_mixins.EntityUpdateMixin`

This mixin provides the ability to update an entity.

The methods provided by this class work together. The call tree looks like this:

```
update → update_json → update_raw → update_payload
```

In short, here is what the methods do:

update_payload() Assemble a payload of data that can be encoded and sent to the server. Set `self.updatable_fields` (list of strings) to limit the fields that can be updated.

update_raw() Make an HTTP PUT request to the server, including the payload.

update_json() Check the server's response for errors and decode the response.

update () Create a `nailgun.entity_mixins.Entity` object representing the created entity and populate its fields.

See the individual methods for more detailed information.

update (fields=None)

Update the current entity.

Call `update_json ()`, use the response to populate a new object of type `type (self)` and return that object.

This method requires that `nailgun.entity_mixins.EntityReadMixin.read ()` or some other identical method be available on the current object. A more thorough explanation is available at `nailgun.entity_mixins.EntityCreateMixin.create ()`.

Parameters fields – An iterable of field names. Only the fields named in this iterable will be updated. No fields are updated if an empty iterable is passed in. All fields are updated if `None` is passed in.

Raises `KeyError` if asked to update a field but no value is available for that field on the current entity.

update_json (fields=None)

Update the current entity.

Call `update_raw ()`. Check the response status code, decode JSON and return the decoded JSON as a dict.

Parameters fields – See `update ()`.

Returns A dict consisting of the decoded JSON in the server's response.

Raises `requests.exceptions.HTTPError` if the response has an HTTP 4XX or 5XX status code.

Raises `ValueError` If the response JSON can not be decoded.

update_payload (fields=None)

Create a payload of values that can be sent to the server.

By default, this method behaves just like `_payload ()`. However, one can also specify a certain set of fields that should be returned. For more information, see `update ()`.

update_raw (fields=None)

Update the current entity.

Make an HTTP PUT call to `self.path ('base')`. The request payload consists of whatever is returned by `update_payload ()`. Return the response.

Parameters fields – See `update ()`.

Returns A `requests.response` object.

exception `nailgun.entity_mixins.MissingValueError`

Indicates that no value can be found for a field.

exception `nailgun.entity_mixins.NoSuchFieldError`

Indicates that the referenced field does not exist.

exception `nailgun.entity_mixins.NoSuchPathError`

Indicates that the requested path cannot be constructed.

`nailgun.entity_mixins.TASK_POLL_RATE = 5`

Default for `poll_rate` argument to `nailgun.entity_mixins._poll_task ()`.

`nailgun.entity_mixins.TASK_TIMEOUT = 300`

Default for timeout argument to `nailgun.entity_mixins._poll_task()`.

exception `nailgun.entity_mixins.TaskFailedError` (*message*, *task_id*)

Indicates that a task finished with a result other than “success”.

exception `nailgun.entity_mixins.TaskTimedOutError` (*message*, *task_id*)

Indicates that a task did not finish before the timeout limit.

`nailgun.entity_mixins._get_entity_id` (*field_name*, *attrs*)

Find the ID for a one to one relationship.

The server may return JSON data in the following forms for a `nailgun.entity_fields.OneToOneField`:

```
'user': None
'user': {'name': 'Alice Hayes', 'login': 'ahayes', 'id': 1}
'user_id': 1
'user_id': None
```

Search *attrs* for a one to one *field_name* and return its ID.

Parameters

- **field_name** – A string. The name of a field.
- **attrs** – A dict. A JSON payload as returned from a server.

Returns Either an entity ID or None.

`nailgun.entity_mixins._get_entity_ids` (*field_name*, *attrs*)

Find the IDs for a one to many relationship.

The server may return JSON data in the following forms for a `nailgun.entity_fields.OneToOneField`:

```
'user': [{'id': 1, ...}, {'id': 42, ...}]
'users': [{'id': 1, ...}, {'id': 42, ...}]
'user_ids': [1, 42]
```

Search *attrs* for a one to many *field_name* and return its ID.

Parameters

- **field_name** – A string. The name of a field.
- **attrs** – A dict. A JSON payload as returned from a server.

Returns An iterable of entity IDs.

`nailgun.entity_mixins._get_server_config` ()

Search for a `nailgun.config.ServerConfig`.

Returns `nailgun.entity_mixins.DEFAULT_SERVER_CONFIG` if it is not None, or whatever is returned by `nailgun.config.ServerConfig.get ()` otherwise.

Return type `nailgun.config.ServerConfig`

`nailgun.entity_mixins._make_entities_from_ids` (*entity_cls*, *entity_objs_and_ids*, *server_config*)

Given an iterable of entities and/or IDs, return a list of entities.

Parameters

- **entity_cls** – An `Entity` subclass.

- **entity_obj_or_id** – An iterable of `nailgun.entity_mixins.Entity` objects and/or entity IDs. All of the entities in this iterable should be of type `entity_cls`.

Returns A list of `entity_cls` objects.

`nailgun.entity_mixins._make_entity_from_id(entity_cls, entity_obj_or_id, server_config)`
Given an entity object or an ID, return an entity object.

If the value passed in is an object that is a subclass of `Entity`, return that value. Otherwise, create an object of the type that `field` references, give that object an ID of `field_value`, and return that object.

Parameters

- **entity_cls** – An `Entity` subclass.
- **entity_obj_or_id** – Either a `nailgun.entity_mixins.Entity` object or an entity ID.

Returns An `entity_cls` object.

Return type `nailgun.entity_mixins.Entity`

`nailgun.entity_mixins._payload(fields, values)`
Implement the `*_payload` methods.

It's frequently useful to create a dict of values that can be encoded to JSON and sent to the server. Unfortunately, there are mismatches between the field names used by NailGun and the field names the server expects. This method provides a default translation that works in many cases. For example:

```
>>> from nailgun.entities import Product
>>> product = Product(name='foo', organization=1)
>>> set(product.get_fields())
{
    'description',
    'gpg_key',
    'id',
    'label',
    'name',
    'organization',
    'sync_plan',
}
>>> set(product.get_values())
{'name', 'organization'}
>>> product.create_payload()
{'organization_id': 1, 'name': 'foo'}
```

Parameters

- **fields** – A value like what is returned by `nailgun.entity_mixins.Entity.get_fields()`.
- **values** – A value like what is returned by `nailgun.entity_mixins.Entity.get_values()`.

Returns A dict mapping field names to field values.

`nailgun.entity_mixins._poll_task(task_id, server_config, poll_rate=None, timeout=None)`
Implement `nailgun.entities.ForemanTask.poll()`.

See `nailgun.entities.ForemanTask.poll()` for a full description of how this method acts. Other methods may also call this method, such as `nailgun.entity_mixins.EntityDeleteMixin.delete()`.

Certain mixins benefit from being able to poll the server after performing an operation. However, this module cannot use `nailgun.entities.ForemanTask.poll()`, as that would be a circular import. Placing the implementation of `nailgun.entities.ForemanTask.poll()` here allows both that method and the mixins in this module to use the same logic.

`nailgun.entity_mixins.to_json_serializable(obj)`

Transforms obj into a json serializable object.

Parameters `obj` – entity or any json serializable object

Returns serializable object

2.1.3 nailgun.entity_fields

The basic components of the NailGun ORM.

Each of the fields in this module corresponds to some type of information that Satellite tracks. When paired the classes in `nailgun.entity_mixins`, it is possible to represent the entities that Satellite manages. For a concrete example of how this works, see `nailgun.entity_mixins.Entity`.

Fields are typically used declaratively in an entity's `__init__` function and are otherwise left untouched, except by the mixin methods. For example, `nailgun.entity_mixins.EntityReadMixin.read()` looks at the fields on an entity to determine what information it should expect the server to return.

A secondary use of fields is to generate random data. For example, you could call `User.get_fields()['login'].gen_value()` to generate a random login. (`gen_value` is implemented at `StringField.gen_value()`) Beware that the `gen_value` methods strive to produce the most outrageous values that are still legal, so they will often return nonsense UTF-8 values, which is unpleasant to work with manually.

```
class nailgun.entity_fields.BooleanField(required=False, choices=None, default=<object
                                     object>, unique=False)
```

Field that represents a boolean

```
gen_value()
```

Return a value suitable for a `BooleanField`.

```
class nailgun.entity_fields.DateField(min_date=None, max_date=None, *args, **kwargs)
```

Field that represents a date

```
gen_value()
```

Return a value suitable for a `DateField`.

```
class nailgun.entity_fields.DateTimeField(min_date=None, max_date=None, *args,
                                           **kwargs)
```

Field that represents a datetime

```
gen_value()
```

Return a value suitable for a `DateTimeField`.

```
class nailgun.entity_fields.DictField(required=False, choices=None, default=<object ob-
                                     ject>, unique=False)
```

Field that represents a set of key-value pairs.

```
gen_value()
```

Return a value suitable for a `DictField`.

```
class nailgun.entity_fields.EmailField(required=False, choices=None, default=<object ob-
                                     ject>, unique=False)
```

Field that represents an email

gen_value()

Return a value suitable for a *EmailField*.

class `nailgun.entity_fields.Field`(*required=False, choices=None, default=<object object>, unique=False*)

Base class to implement other fields

Record this field's attributes.

Parameters

- **required** – A boolean. Determines whether a value must be submitted to the server when creating or updating an entity.
- **choices** – A tuple of values that this field may be populated with.
- **default** – Entity classes that inherit from *nailgun.entity_mixins.EntityCreateMixin* use this field.

class `nailgun.entity_fields.FloatField`(*required=False, choices=None, default=<object object>, unique=False*)

Field that represents a float

gen_value()

Return a value suitable for a *FloatField*.

class `nailgun.entity_fields.IPAddressField`(*length=(1, 30), str_type='utf8',* *), *args, **kwargs*)

Field that represents an IP address

gen_value()

Return a value suitable for a *IPAddressField*.

class `nailgun.entity_fields.IntegerField`(*min_val=None, max_val=None,* *), *args, **kwargs*)

Field that represents an integer.

gen_value()

Return a value suitable for a *IntegerField*.

class `nailgun.entity_fields.ListField`(*required=False, choices=None, default=<object object>, unique=False*)

Field that represents a list of strings

class `nailgun.entity_fields.MACAddressField`(*length=(1, 30), str_type='utf8',* *), *args, **kwargs*)

Field that represents a MAC address

gen_value()

Return a value suitable for a *MACAddressField*.

class `nailgun.entity_fields.NetmaskField`(*length=(1, 30), str_type='utf8',* *), *args, **kwargs*)

Field that represents a netmask

gen_value()

Return a value suitable for a *NetmaskField*.

class `nailgun.entity_fields.OneToManyField`(*entity, *args, **kwargs*)

Field that represents a reference to zero or more other entities.

Parameters **entity** (*nailgun.entity_mixins.Entity*) – The entities to which this field points.

gen_value()

Return the class that this field references.

class `nailgun.entity_fields.OneToOneField`(*entity*, *args, **kwargs)

Field that represents a reference to another entity.

All parameters not documented here are passed to *Field*.

Parameters **entity** (`nailgun.entity_mixins.Entity`) – The entity to which this field points.

gen_value()

Return the class that this field references.

class `nailgun.entity_fields.StringField`(*length*=(1, 30), *str_type*=('utf8',), *args, **kwargs)

Field that represents a string.

The default length of string fields is short for two reasons:

1. Foreman's database backend limits many fields to 255 bytes in length. As a result, length should be no longer than 85 characters long, as 85 unicode characters may be up to 255 bytes long.
2. Humans have to read through the error messages produced by this library. Long error messages are hard to read through, and that hurts productivity. Thus, a length even shorter than 85 chars is desirable.

Parameters

- **length** – Either a (*min_len*, *max_len*) tuple or an *exact_len* integer.
- **str_type** – The types of characters to generate when *StringField.gen_value()* is called. May be a single string type (e.g. 'utf8') or a tuple of string types. This argument is passed through to FauxFactory's *gen_string* method, so this method accepts all string types which that method does.

gen_value()

Return a value suitable for a *StringField*.

class `nailgun.entity_fields.URLField`(*length*=(1, 30), *str_type*=('utf8',), *args, **kwargs)

Field that represents an URL

gen_value()

Return a value suitable for a *URLField*.

2.1.4 nailgun.config

Tools for managing and presenting server connection configurations.

NailGun needs to know certain facts about the remote server in order to do anything useful. For example, NailGun needs to know the URL of the remote server (e.g. 'https://example.com:250') and how to authenticate with the remote server. `nailgun.config.ServerConfig` eases the task of managing and presenting that information.

class `nailgun.config.BaseServerConfig`(*url*, *auth*=None, *version*=None)

A set of facts for communicating with a Satellite server.

This object stores a set of facts that can be used when communicating with a Satellite server, regardless of whether that communication takes place via the API, CLI or UI. `nailgun.config.ServerConfig` is more specialized and adds attributes that are useful when communicating with the API.

Parameters

- **url** – A string. The URL of a server. For example: 'https://example.com:250'.

- **auth** – Credentials to use when communicating with the server. For example: (*'username'*, *'password'*). No instance attribute is created if no value is provided.
- **version** – A string, such as *'6.0'* or *'6.1'*, indicating the Satellite version the server is running. This version number is parsed by `packaging.version.parse` before being stored locally. This allows for version comparisons:

```
>>> from nailgun.config import ServerConfig
>>> from packaging.version import parse
>>> cfg = ServerConfig('http://sat.example.com', version='6.0')
>>> cfg.version == parse('6.0')
True
>>> cfg.version == parse('6.0.0')
True
>>> cfg.version < parse('10.0')
True
>>> '6.0' < '10.0'
False
```

If no version number is provided, then no instance attribute is created, and it is assumed that the server is running an up-to-date nightly build.

Warning: This class will likely be moved to a separate Python package in a future release of NailGun. Be careful about making references to this class, as those references will likely need to be changed.

classmethod delete (*label='default', path=None*)

Delete a server configuration.

This method is thread safe.

Parameters

- **label** – A string. The configuration identified by `label` is deleted.
- **path** – A string. The configuration file to be manipulated. Defaults to what is returned by `nailgun.config._get_config_file_path()`.

Returns None

classmethod get (*label='default', path=None*)

Read a server configuration from a configuration file.

Parameters

- **label** – A string. The configuration identified by `label` is read.
- **path** – A string. The configuration file to be manipulated. Defaults to what is returned by `nailgun.config._get_config_file_path()`.

Returns A brand new `nailgun.config.BaseServerConfig` object whose attributes have been populated as appropriate.

Return type `BaseServerConfig`

classmethod get_labels (*path=None*)

Get all server configuration labels.

Parameters **path** – A string. The configuration file to be manipulated. Defaults to what is returned by `nailgun.config._get_config_file_path()`.

Returns Server configuration labels, where each label is a string.

save (*label='default', path=None*)

Save the current connection configuration to a file.

This method is thread safe.

Parameters

- **label** – A string. An identifier for the current configuration. This allows multiple configurations with unique labels to be saved in a single file. If a configuration identified by `label` already exists in the destination configuration file, it is replaced.
- **path** – A string. The configuration file to be manipulated. By default, an XDG-compliant configuration file is used. A configuration file is created if one does not exist already.

Returns None

exception `nailgun.config.ConfigFileError`

Indicates an error occurred when locating a configuration file.

Warning: This class will likely be moved to a separate Python package in a future release of NailGun. Be careful about making references to this class, as those references will likely need to be changed.

class `nailgun.config.ServerConfig` (*url, auth=None, version=None, verify=None*)

Extend `nailgun.config.BaseServerConfig`.

This class adds functionality that is useful specifically when working with the API. For example, it stores the additional `verify` instance attribute and adds logic useful for presenting information to the methods in `nailgun.client`.

Parameters **verify** – A boolean. Should SSL be verified when communicating with the server?
No instance attribute is created if no value is provided.

classmethod **get** (*label='default', path=None*)

Read a server configuration from a configuration file.

This method extends `nailgun.config.BaseServerConfig.get()`. Please read up on that method before trying to understand this one.

The entity classes rely on the requests library to be a transport mechanism. The methods provided by that library, such as `get` and `post`, accept an `auth` argument. That argument must be a tuple:

Auth tuple to enable Basic/Digest/Custom HTTP Auth.

However, the JSON decoder does not recognize a tuple as a type, and represents sequences of elements as a tuple. Compensate for that by converting `auth` to a two element tuple if it is a two element list.

This override is done here, and not in the base class, because the base class may be extracted out into a separate library and used in other contexts. In those contexts, the presence of a list may not matter or may be desirable.

get_client_kwargs ()

Get kwargs for use with the methods in `nailgun.client`.

This method returns a dict of attributes that can be unpacked and used as kwargs via the `**` operator. For example:

```
cfg = ServerConfig.get()
client.get(f'{cfg.url}/api/v2', **cfg.get_client_kwargs())
```

This method is useful because client code may not know which attributes should be passed from a `ServerConfig` object to one of the `nailgun.client` functions. Consider that the example above could also be written like this:

```
cfg = ServerConfig.get()
client.get(f'{cfg.url}/api/v2', auth=cfg.auth, verify=cfg.verify)
```

But this latter approach is more fragile. It will break if `cfg` does not have an `auth` or `verify` attribute.

`nailgun.config._get_config_file_path(xdg_config_dir, xdg_config_file)`

Search `XDG_CONFIG_DIRS` for a config file and return the first found.

Search each of the standard XDG configuration directories for a configuration file. Return as soon as a configuration file is found. Beware that by the time client code attempts to open the file, it may be gone or otherwise inaccessible.

Parameters

- `xdg_config_dir` – A string. The name of the directory that is suffixed to the end of each of the `XDG_CONFIG_DIRS` paths.
- `xdg_config_file` – A string. The name of the configuration file that is being searched for.

Returns A `str` path to a configuration file.

Raises `nailgun.config.ConfigFileError` – When no configuration file can be found.

2.1.5 `nailgun.client`

Wrappers for methods in the `Requests` module.

The functions in this module wrap `functions` from the `Requests` module. Each function is modified with the following behaviours:

1. It sets the ‘content-type’ header to ‘application/json’, so long as no content-type is already set.
2. It encodes its `data` argument as JSON (using the `json` module) if the ‘content-type’ header is ‘application/json’.
3. It logs information about the request before it is sent.
4. It logs information about the response when it is received.

`nailgun.client.delete(url, **kwargs)`

A wrapper for `requests.delete`. Sends a DELETE request.

`nailgun.client.get(url, params=None, **kwargs)`

A wrapper for `requests.get`.

`nailgun.client.head(url, **kwargs)`

A wrapper for `requests.head`.

`nailgun.client.patch(url, data=None, **kwargs)`

A wrapper for `requests.patch`. Sends a PATCH request.

`nailgun.client.post(url, data=None, json=None, **kwargs)`

A wrapper for `requests.post`.

`nailgun.client.put(url, data=None, **kwargs)`

A wrapper for `requests.put`. Sends a PUT request.

`nailgun.client.request` (*method, url, **kwargs*)
A wrapper for `requests.request`.

2.2 tests

Unit tests for NailGun.

2.2.1 tests.test_client

Unit tests for `nailgun.client`.

class `tests.test_client.ClientTestCase` (*methodName='runTest'*)
Tests for functions in `nailgun.client`.

setUp ()

Hook method for setting up the test fixture before exercising it.

test_client_request ()

Test `nailgun.client.request` ().

Make the same assertions as `tests.test_client.ClientTestCase.test_clients` ().

test_clients ()

Test all the wrappers except `nailgun.client.request` ().

The following functions are tested:

- `nailgun.client.delete` ()
- `nailgun.client.get` ()
- `nailgun.client.head` ()
- `nailgun.client.patch` ()
- `nailgun.client.post` ()
- `nailgun.client.put` ()

Assert that:

- The wrapper function passes the correct parameters to `requests`.
- The wrapper function returns whatever `requests` returns.

test_identical_args ()

Check that the wrapper functions have the correct signatures.

For example, `nailgun.client.delete` () should have the same signature as `requests.delete`.

class `tests.test_client.ContentTypeIsJsonTestCase` (*methodName='runTest'*)
Tests for function `_content_type_is_json`.

test_false ()

Assert True is returned when content-type is not JSON.

test_false_with_no_headers ()

If no headers passed should return None

test_true ()

Assert True is returned when content-type is JSON.

```
class tests.test_client.SetContentTypeTestCase (methodName='runTest')
    Tests for function _set_content_type.

    test_existing_value ()
        Assert that no content-type is provided if one is set.

    test_files_in_kwargs ()
        Assert that no content-type is provided if files are given.

    test_no_value ()
        Assert that a content-type is provided if none is set.
```

2.2.2 tests.test_config

Unit tests for `nailgun.config`.

```
class tests.test_config.BaseServerConfigTestCase (methodName='runTest')
    Tests for nailgun.config.BaseServerConfig.

    test_delete ()
        Test nailgun.config.BaseServerConfig.delete().

        Assert that the method reads the config file before writing, and that it writes out a correct config file.

    test_get ()
        Test nailgun.config.BaseServerConfig.get().

        Assert that the method extracts the asked-for section from a configuration file and correctly populates a new BaseServerConfig object. Also assert that the auth attribute is a list. (See the docstring for nailgun.config.ServerConfig.get().)

    test_get_labels ()
        Test nailgun.config.BaseServerConfig.get_labels().

        Assert that the method returns the correct labels.

    test_init ()
        Test instantiating nailgun.config.BaseServerConfig.

        Assert that only provided values become object attributes.

    test_save ()
        Test nailgun.config.BaseServerConfig.save().

        Assert that the method reads the config file before writing, and that it writes out a correct config file.

class tests.test_config.ReprTestCase (methodName='runTest')
    Test method nailgun.config.BaseServerConfig.__repr__.

    test_bsc_v1 ()
        Test nailgun.config.BaseServerConfig.

        Assert that __repr__ works correctly when url is specified.

    test_bsc_v2 ()
        Test nailgun.config.BaseServerConfig.

        Assert that __repr__ works correctly when url and auth are specified.

    test_bsc_v3 ()
        Test nailgun.config.BaseServerConfig.

        Assert that __repr__ works correctly when url and version are specified.
```

```

test_sc_v1 ()
    Test nailgun.config.ServerConfig.

    Assert that __repr__ works correctly when only a URL is passed in.

test_sc_v2 ()
    Test nailgun.config.ServerConfig.

    Assert that __repr__ works correctly when url and auth are specified.

test_sc_v3 ()
    Test nailgun.config.ServerConfig.

    Assert that __repr__ works correctly when url and version are specified.

test_sc_v4 ()
    Test nailgun.config.ServerConfig.

    Assert that __repr__ works correctly when url and verify are specified.

class tests.test_config.ServerConfigTestCase (methodName='runTest')
    Tests for nailgun.config.ServerConfig.

test_get ()
    Test nailgun.config.ServerConfig.get ().

    Assert that the auth attribute is a tuple.

test_get_client_kwargs ()
    Test nailgun.config.ServerConfig.get_client_kwargs ().

    Assert that:
    

- get_client_kwargs returns all of the instance attributes from its object except the “url” attribute, and
- no instance attributes from the object are removed.

test_init ()
    Test instantiating nailgun.config.ServerConfig.

    Assert that only provided values become object attributes.

test_raise_config_file_error ()
    Should raise error if path not found

```

2.2.3 tests.test_entities

Tests for *nailgun.entities*.

```

class tests.test_entities.ContentUploadTestCase (methodName='runTest')
    Tests for nailgun.entities.ContentUpload.

setUp ()
    Set self.repo.

test_content_upload_create ()
    Test nailgun.entities.ContentUpload.create.

    Make the (mock) server return a “success” status. Make the same assertions as for tests.test_entities.GenericTestCase.test_generic ().

```

test_content_upload_delete()

Test `nailgun.entities.ContentUpload.delete`.

Make the (mock) server return a “success” status. Make the same assertions as for `tests.test_entities.GenericTestCase.test_generic()`.

test_content_upload_no_filename()

Test `nailgun.entities.ContentUpload.upload` without a filename.

Make the (mock) server return a “success” status. Make the same assertions as for `tests.test_entities.GenericTestCase.test_generic()`.

test_content_upload_update()

Test `nailgun.entities.ContentUpload.update`.

Make the (mock) server return a “success” status. Make the same assertions as for `tests.test_entities.GenericTestCase.test_generic()`.

test_content_upload_upload()

Test `nailgun.entities.ContentUpload.upload`.

Make the (mock) server return a “success” status. Make the same assertions as for `tests.test_entities.GenericTestCase.test_generic()`.

class tests.test_entities.ContentViewComponentTestCase (*methodName='runTest'*)

Tests for `nailgun.entities.ContentViewComponent`.

setUp()

Set a server configuration at `self.cfg`.

test_add()

Check that helper method is sane.

Assert that:

- Method has a correct signature.
- Method calls `client.*` once.
- Method calls `entities._handle_response` once.

test_remove()

Check that helper method is sane.

Assert that:

- Method has a correct signature.
- Method calls `client.*` once.
- Method calls `entities._handle_response` once.

class tests.test_entities.ContentViewTestCase (*methodName='runTest'*)

Tests for `nailgun.entities.ContentView`.

setUp()

Hook method for setting up the test fixture before exercising it.

test_read()

Check that helper method is sane.

test_search()

Check that helper method is sane.

class tests.test_entities.CreateMissingTestCase (*methodName='runTest'*)

Tests for extensions of `create_missing`.

```
classmethod setUpClass()
    Set a server configuration at cls.cfg.

test_auth_source_ldap_v1()
    Test AuthSourceLDAP (onthe-fly-register=False).create_missing()

test_auth_source_ldap_v2()
    Test AuthSourceLDAP (onthe-fly-register=True).create_missing().

test_auth_source_ldap_v3()
    Does AuthSourceLDAP.create_missing overwrite fields?

test_domain_v1()
    Test Domain (name='UPPER').

test_domain_v2()
    Test Domain().

test_external_usergroup()
    Test ExternalUserGroup()

test_host_v1()
    Test Host().

test_host_v2()
    Test Host() with providing all the optional entities unlinked

test_host_v3()
    Test Host() providing optional entities with id only. Check that additional read was called for that
    entities.

test_lifecycle_environment_v1()
    Test LifecycleEnvironment (name='Library').

test_lifecycle_environment_v2()
    Test LifecycleEnvironment (name='not Library').

test_lifecycle_environment_v3()
    What happens when the “Library” lifecycle env cannot be found?

test_provisioning_template_v1()
    Test ProvisioningTemplate (snippet=True).

test_provisioning_template_v2()
    Test ProvisioningTemplate (snippet=False).

test_provisioning_template_v3()
    Test ProvisioningTemplate (snippet=False, template_kind=...).

test_report_template_v1()
    Test ReportTemplate (name='testName').

test_report_template_v2()
    Test ReportTemplate().

test_report_template_v3()
    Test ReportTemplate (default=True).

test_report_template_v4()
    Test ReportTemplate (default=False).

test_repository_v1()
    Test Repository (content_type='docker').
```

```
test_repository_v2()  
    TestRepository(content_type='not docker').
```

```
class tests.test_entities.CreatePayloadTestCase (methodName='runTest')
```

Tests for extensions of `create_payload`.

Several classes extend the `create_payload` method and make it do things like rename attributes or wrap the submitted dict of data in a second hash. It is possible to mess this up in a variety of ways. For example, an extended method could try to rename an attribute that does not exist. This class attempts to find such issues by creating an entity, calling `nailgun.entity_mixins.EntityCreateMixin.create_payload()` and asserting that a dict is returned.

```
classmethod setUpClass()  
    Set a server configuration at cls.cfg.
```

```
test_content_view_filter_rule()  
    Create a nailgun.entities.ContentViewFilterRule.
```

```
test_discovery_rule()  
    Create a nailgun.entities.DiscoveryRule.
```

```
test_external_usergroup_payload()  
    Call create_payload on a nailgun.entities.ExternalUserGroup.
```

```
test_host_collection()  
    Create a nailgun.entities.HostCollection.
```

```
test_image()  
    Create a nailgun.entities.Image.
```

```
test_job_template()  
    Create a nailgun.entities.JobTemplate.
```

```
test_media()  
    Create a nailgun.entities.Media.
```

```
test_no_attributes()  
    Instantiate an entity and call create_payload on it.
```

```
test_override_value()  
    Create a nailgun.entities.OverrideValue.
```

```
test_subnet()  
    Create a nailgun.entities.Subnet.
```

```
test_sync_plan()  
    Call create_payload on a nailgun.entities.SyncPlan.
```

```
class tests.test_entities.CreateTestCase (methodName='runTest')  
    Tests for nailgun.entity_mixins.EntityCreateMixin.create().
```

```
classmethod setUpClass()  
    Set a server configuration at cls.cfg.
```

```
test_generic()  
    Call create on a variety of entities.
```

```
class tests.test_entities.FileTestCase (methodName='runTest')  
    Class with entity File tests
```

```
test_to_json()  
    Check json serialisation on nested entities
```



```
class tests.test_entities.ForemanStatusTestCase (methodName='runTest')
    Tests for nailgun.entities.ForemanStatus.
```

```
    setUp()
        Set a server configuration at self.cfg.
```

```
    test_read()
        Ensure read and read_json are called once.
```

```
class tests.test_entities.ForemanTaskTestCase (methodName='runTest')
    Tests for nailgun.entities.ForemanTask.
```

```
    setUp()
        Set self.foreman_task.
```

```
    test_poll()
        Call nailgun.entities.ForemanTask.poll().
```

```
class tests.test_entities.GenericTestCase (methodName='runTest')
    Generic tests for the helper methods on entities.
```

```
    classmethod setUpClass()
        Create test data as cls.methods_requests.
```

methods_requests is a tuple of two-tuples, like so:

```
(
    (entity_obj1.method, 'post',
     entity_obj2.method, 'post',
     entity_obj3.method1, 'get',
     entity_obj3.method2, 'put',
    )
)
```

```
    test_generic()
        Check that a variety of helper methods are sane.
```

Assert that:

- Each method has a correct signature.
- Each method calls *client.** once.
- Each method passes the right arguments to *client.**.
- Each method calls *entities._handle_response* once.
- The result of *_handle_response(...)* is the return value.

```
    test_intelligent()
        Check that intelligent methods that send additional data are sane.
```

Assert that:

- Each method calls *client.** once.
- Each method passes the right arguments to *client.**.
- Each method calls *entities._handle_response* once.
- The result of *_handle_response(...)* is the return value.

```
class tests.test_entities.GetOrgTestCase (methodName='runTest')
    Test nailgun.entities._get_org.
```

```
    setUp()
        Set self.args, which can be passed to _get_org.
```

test_api_response_error()
Trigger an *nailgun.entities.APIResponseError*.

test_default()
Run the method with a sane and normal set of arguments.

test_to_json()
json serialization

class tests.test_entities.HandleResponseTestCase (*methodName='runTest'*)
Test *nailgun.entities._handle_response*.

test_accepted_v1()
Give the response an HTTP “ACCEPTED” status code.

Call *_handle_response* twice:

- Do not pass the *synchronous* argument.
- Pass *synchronous=False*.

test_accepted_v2()
Give the response an HTTP “ACCEPTED” status code.

Pass *synchronous=True* as an argument.

test_default()
Don’t give the response any special status code.

test_json_content()
Give the response JSON content type

test_no_content()
Give the response an HTTP “NO CONTENT” status code.

test_no_json_content()
Check if no JSON content type response return *response.content*.

class tests.test_entities.HostGroupTestCase (*methodName='runTest'*)
Tests for *nailgun.entities.HostGroup*.

setUp()
Hook method for setting up the test fixture before exercising it.

test_clone_hostgroup()
Test for *nailgun.entities.HostGroup.clone()* Assert that the method is called one with correct arguments

test_delete_puppetclass()
Check that helper method is sane.

Assert that:

- Method has a correct signature.
- Method calls *client.** once.
- **Method passes the right arguments to *client.** and special argument ‘puppetclass_id’ removed from data dict.**
- Method calls *entities._handle_response* once.
- The result of *_handle_response(...)* is the return value.

test_read()

Ensure `read`, `read_json` and `update_json` are called once.

This test is only appropriate for entities that override the `read` method in order to fiddle with the `attrs` argument.

test_rebuild_config()

Test for `nailgun.entities.HostGroup.rebuild_config()` Assert that the method is called one with correct arguments

class `tests.test_entities.HostTestCase` (*methodName='runTest'*)

Tests for `nailgun.entities.Host`.

setUp()

Set a server configuration at `self.cfg`.

test_delete_puppetclass()

Check that helper method is sane.

Assert that:

- Method has a correct signature.
- Method calls `client.*` once.
- **Method passes the right arguments to `client.*` and special** argument `'puppetclass_id'` removed from data dict.
- Method calls `entities._handle_response` once.
- The result of `_handle_response(...)` is the return value.

test_disassociate()

Disassociate host

test_init_with_owner()

Assert that both `id` or `entity` can be passed as a value for `owner` attribute.

test_init_with_owner_type()

Assert `owner` attribute is an entity of correct type, according to `owner_type` field value

test_no_facet_attributes()

Assert that `content_facet_attributes` attribute is ignored when `content_facet_attributes` attribute is not returned for host

test_owner_type_property()

Verify `owner_type` property works as expected.

Assert that:

- `owner_type` property reflects `_owner_type` attribute value
- `owner_type` property is included in attributes list, `_owner_type` attribute - is not

test_update_owner_type()

Ensure that in case `owner_type` value changes, `owner` changes it's type accordingly.

class `tests.test_entities.InitTestCase` (*methodName='runTest'*)

Tests for all of the `__init__` methods.

The tests in this class are a sanity check. They simply check to see if you can instantiate each entity.

classmethod `setUpClass()`

Set a server configuration at `cls.cfg`.

test_init_succeeds ()

Instantiate every entity.

Assert that the returned object is an instance of the class that produced it.

test_required_params ()

Instantiate entities that require extra parameters.

Assert that `TypeError` is raised if the required extra parameters are not provided.

class tests.test_entities.JobInvocationTestCase (*methodName='runTest'*)
Tests for *nailgun.entities.JobInvocation*.

classmethod setUpClass ()

Hook method for setting up class fixture before running tests in the class.

test_non_sync_run ()

Run job asynchronously with valid parameters and check that correct post request is sent

test_required_param ()

Check required parameters

test_sync_run ()

Check that sync run will result in ForemanTask poll

class tests.test_entities.JobTemplateTestCase (*methodName='runTest'*)
Tests for *nailgun.entities.JobTemplate*.

setUp ()

Hook method for setting up the test fixture before exercising it.

tearDown ()

Hook method for deconstructing the test fixture after testing it.

class tests.test_entities.JsonSerializableTestCase (*methodName='runTest'*)
Test regarding Json serializable on different object

test_boolean_datetime_float ()

Check serialization for boolean, datetime and float fields

test_date_field ()

Check date field serialization

test_entities ()

Testing nested entities serialization

test_nested_entities ()

Check nested entities serialization

test_regular_objects ()

Checking regular objects transformation

class tests.test_entities.ModuleStreamTestCase (*methodName='runTest'*)
Class with entity Module Stream tests

test_to_json ()

Check json serialisation on nested entities

class tests.test_entities.PackageGroupTestCase (*methodName='runTest'*)
Class with entity Package Group tests

test_to_json ()

Check json serialisation on nested entities

```

class tests.test_entities.PackageTestCase (methodName='runTest')
    Class with entity Package tests

    test_to_json()
        Check json serialisation on nested entities

class tests.test_entities.PathTestCase (methodName='runTest')
    Tests for extensions of nailgun.entity_mixins.Entity.path().

    setUp()
        Set self.cfg and self.id_.

    test_arfreport()
        Test nailgun.entities.ArfoReport.path(). Assert that the following return appropriate paths:
        * ArfoReport(id=...).path() * ArfoReport(id=...).path('download_html')

    test_capsule()
        Test nailgun.entities.Capsule.path().

        Assert that the following return appropriate paths:

        • Capsule().path('content_lifecycle_environments')
        • Capsule().path('content_sync')

    test_externalusergroup()
        Test nailgun.entities.ExternalUserGroup.path().

        Assert that the following return appropriate paths:

        • ExternalUserGroup(id=...,usergroup=...).path()
        • ExternalUserGroup(id=...,usergroup=...).path('refresh')

    test_hostsubscription()
        Test nailgun.entities.HostSubscription.path().

        Assert that the following return appropriate paths:

        • HostSubscription(host=...).path('add_subscriptions')
        • HostSubscription(host=...).path('remove_subscriptions')

    test_id_and_which()
        Execute entity(id=...).path(which=...).

    test_no_such_path_error()
        Trigger nailgun.entity_mixins.NoSuchPathError exceptions.

        Do this by calling entity().path(which=...).

    test_noid_and_which()
        Execute entity().path(which=...).

    test_nowhich()
        Execute entity().path() and entity(id=...).path().

    test_os_default_template()
        Test nailgun.entities.OSDefaultTemplate.path

        Assert that the following return appropriate paths:

        • OSDefaultTemplate(id=...).path()

    test_repository_set()
        Test nailgun.entities.RepositorySet.path().

```

Assert that the following return appropriate paths:

- `RepositorySet(id=...).path()`
- `RepositorySet(id=...).path('available_repositories')`
- `RepositorySet(id=...).path('disable')`
- `RepositorySet(id=...).path('enable')`

test_snapshot()

Test `nailgun.entities.Snapshot.path()`.

Assert that the following return appropriate paths:

- `Snapshot(id=...).path()`
- `Snapshot(id=...).path('revert')`

test_subscription()

Test `nailgun.entities.Subscription.path()`.

Assert that the following return appropriate paths:

- `Subscription(organization=...).path('delete_manifest')`
- `Subscription(organization=...).path('manifest_history')`
- `Subscription(organization=...).path('refresh_manifest')`
- `Subscription(organization=...).path('upload')`

test_sync_plan()

Test `nailgun.entities.SyncPlan.path()`.

Assert that the following return appropriate paths:

- `SyncPlan(id=...).path()`
- `SyncPlan(id=...).path('add_products')`
- `SyncPlan(id=...).path('remove_products')`

class `tests.test_entities.ProvisioningTemplateTestCase` (*methodName='runTest'*)

Tests for `nailgun.entities.ProvisioningTemplate`.

test_creation_and_update()

Check template combinations as json or entity is set on correct attribute `template_combinations_attributes` (check #333)

class `tests.test_entities.PuppetClassTestCase` (*methodName='runTest'*)

Tests for `nailgun.entities.PuppetClass`.

setUp()

Set `self.puppet_class`.

test_search_normalize()

Call `nailgun.entities.PuppetClass.search_normalize()`. Assert that returned value is a list and contains all subdictionaries.

class `tests.test_entities.ReadTestCase` (*methodName='runTest'*)

Tests for `nailgun.entity_mixins.EntityReadMixin.read()`.

setUp()

Set a server configuration at `self.cfg`.

test_attrs_arg_v1()

Ensure `read` and `read_json` are both called once.

This test is only appropriate for entities that override the `read` method in order to fiddle with the `attrs` argument.

test_attrs_arg_v2()

Ensure `read`, `read_json` and `client.put` are called once.

This test is only appropriate for entities that override the `read` method in order to fiddle with the `attrs` argument.

test_discovery_rule()

Call `nailgun.entities.DiscoveryRule.read()`.

Ensure that the `max_count` attribute is fetched.

test_entity_arg()

Call `read` on entities that require parameters for instantiation.

Some entities require extra parameters when being instantiated. As a result, these entities must extend `nailgun.entity_mixins.EntityReadMixin.read()` by providing a value for the `entity` argument. Assert that these entities pass their server configuration objects to the child entities that they create and pass in to the `entity` argument.

test_entity_ids()

Test cases where the server returns unusually named attributes.

Assert that the returned attributes are renamed to be more regular before calling `read()`.

test_host_with_interface()

Call `nailgun.entities.Host.read()`.

Assert that host will have interfaces initialized and assigned correctly.

test_hostgroup_ignore_root_pass()

Call `nailgun.entities.HostGroup.read()`.

Assert that the entity ignores the `root_pass` field.

test_http_proxy_ignore_arg()

Call `nailgun.entities.HTTPProxy.read()`. Assert that the entity ignores the `password`, `organization` and `location` field.

test_ignore_arg_v1()

Call `read` on a variety of entities.

Assert that the `ignore` argument is correctly passed on.

test_ignore_arg_v3()

Call `nailgun.entities.AuthSourceLDAP.read()`.

Assert that the entity ignores the 'account_password' field.

test_ignore_arg_v4()

Call `nailgun.entities.User.read()`.

Assert that entity's predefined values of `ignore` are always correctly passed on.

test_interface_ignore_arg()

Call `nailgun.entities.Interface.read()`.

Assert that entity's predefined values of `ignore` are always correctly passed on.

test_parameter_ignore_arg()

Call `nailgun.entities.Parameter.read()`.

Assert that entity's predefined values of `ignore` are always correctly passed on.

test_product_with_sync_plan()

Call `nailgun.entities.Product.read()` for a product with sync plan assigned.

Ensure that the sync plan entity was correctly fetched.

test_snapshot_ignore_arg()

Call `nailgun.entities.Snapshot.read()`.

Assert that entity's predefined values of `ignore` are always correctly passed on.

test_subnet()

Call `nailgun.entities.Subnet.read()`.

Ensure that the `from_` attribute is successfully set.

test_usergroup_with_external_usergroup()

Call `nailgun.entities.ExternalUserGroup.read()` for a usergroup with external usergroup assigned.

Ensure that the external usergroup entity was correctly fetched.

class tests.test_entities.ReportTemplateTestCase (*methodName='runTest'*)

Tests for `nailgun.entities.ReportTemplate`.

test_creation_and_update()

Check template combinations as json or entity is set on correct attribute `template_combinations_attributes` (check #333)

test_generate()

Generate template

test_report_data()

Schedule template

test_schedule()

Schedule template

class tests.test_entities.RepositorySetTestCase (*methodName='runTest'*)

Tests for `nailgun.entities.RepositorySet`.

setUp()

Set `self.product`.

class tests.test_entities.RepositoryTestCase (*methodName='runTest'*)

Tests for `nailgun.entities.Repository`.

setUp()

Set `self.repo`.

test_files()

Test for `nailgun.entities.Repository.files()` Assert that the method is called one with correct arguments

test_import_uploads_upload_ids()

Call `nailgun.entities.Repository.import_uploads()` with the `upload_ids` parameter.

Make the (mock) server return a "success" status. Make the same assertions as for `tests.test_entities.GenericTestCase.test_generic()`.


```

test_import_uploads_uploads()
    Call nailgun.entities.Repository.import_uploads() with the uploads parameter.

    Make the (mock) server return a “success” status. Make the same assertions as for tests.test_entities.GenericTestCase.test_generic().

test_upload_content_v1()
    Call nailgun.entities.Repository.upload_content().

    Make the (mock) server return a “success” status. Make the same assertions as for tests.test_entities.GenericTestCase.test_generic().

test_upload_content_v2()
    Call nailgun.entities.Repository.upload_content().

    Assert that nailgun.entities.APIResponseError is raised when the (mock) server fails to return a “success” status.

class tests.test_entities.ScapContentsTestCase (methodName='runTest')
    Tests for nailgun.entities.ScapContents.

    classmethod setUpClass()
        Set self.server_config.

    test_scap_tailoring_file()
        Test nailgun.entities.ScapContents.create.

class tests.test_entities.SearchNormalizeTestCase (methodName='runTest')
    Tests for nailgun.entity_mixins.EntitySearchMixin.search_normalize().

    classmethod setUpClass()
        Set a server configuration at cls.cfg.

    test_host_with_image()
        Call nailgun.entities.Host.read() for a host with image assigned.

        Ensure that the image entity was correctly fetched.

    test_interface()
        Test nailgun.entities.Interface.search_normalize().

        Assert that host_id was added with correct host’s id to search results.

    test_snapshot()
        Test nailgun.entities.Snapshot.search_normalize().

        Assert that host_id was added with correct user’s id to search results.

    test_sshkey()
        Test nailgun.entities.SSHKey.search_normalize().

        Assert that user_id was added with correct user’s id to search results.

class tests.test_entities.SearchPayloadTestCase (methodName='runTest')
    Tests for extensions of search_upload.

    classmethod setUpClass()
        Set a server configuration at cls.cfg.

    test_content_view_filter_rule()
        errata_id field should be Errata ID when sent to the server, not DB ID.

    test_generic()
        Instantiate a variety of entities and call search_payload.

```

```
class tests.test_entities.SearchTestCase (methodName='runTest')
    Tests for nailgun.entity_mixins.EntitySearchMixin.search().

    classmethod setUpClass ()
        Set a server configuration at cls.cfg.

    test_host_with_image ()
        Call nailgun.entities.Host.search() for a host with image assigned.

        Ensure that the image entity was correctly fetched.

    test_product_with_sync_plan ()
        Call nailgun.entities.Product.search() for a product with sync plan assigned.

        Ensure that the sync plan entity was correctly fetched.

class tests.test_entities.SmartProxyTestCase (methodName='runTest')
    Tests for nailgun.entities.SmartProxy.

    setUp ()
        Set self.smart_proxy.

    test_import_puppetclasses ()
        Call nailgun.entities.SmartProxy.import_puppetclasses().    Assert that *
        environment parameter is not sent to requests, * proper path is built

class tests.test_entities.SrpmsTestCase (methodName='runTest')
    Class with entity Srpms tests

    test_to_json ()
        Check json serialisation on nested entities

class tests.test_entities.SubscriptionTestCase (methodName='runTest')
    Tests for nailgun.entities.Subscription.

    setUp ()
        Set self.subscription.

    test__org_path ()
        Call nailgun.entities.Subscription._org_path.

    test_methods ()
        Check that several helper methods are sane.

        This method is just like tests.test_entities.GenericTestCase.test_generic(), but
        with a slightly different set of mocks. Test the following:

        

- nailgun.entities.Subscription.delete_manifest()
- nailgun.entities.Subscription.manifest_history()
- nailgun.entities.Subscription.refresh_manifest()
- nailgun.entities.Subscription.upload()



        It would be ideal if these method could be refactored such that this unit test could be dropped.

class tests.test_entities.TailoringFileTestCase (methodName='runTest')
    Tests for nailgun.entities.TailoringFile.

    classmethod setUpClass ()
        Set self.server_config.

    test_scap_tailoring_file ()
        Test nailgun.entities.TailoringFile.create.
```

```

class tests.test_entities.TemplateInputTestCase (methodName='runTest')
    Tests for nailgun.entities.TemplateInput.

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

class tests.test_entities.UpdatePayloadTestCase (methodName='runTest')
    Tests for extensions of update_payload.

    classmethod setUpClass()
        Set a server configuration at cls.cfg.

    test_content_view_filter_rule()
        errata_id field should be 'translated' from DB ID to Errata ID.

    test_discovery_rule_search()
        Check whether DiscoveryRule updates its search_ field.

        The field should be renamed from search_ to search when update_payload is called.

    test_generic()
        Instantiate a variety of entities and call update_payload.

    test_image()
        Check whether Image updates its path_ field.

        The field should be renamed from path_ to path when update_payload is called.

    test_job_template()
        Create a nailgun.entities.JobTemplate.

    test_media_path()
        Check whether Media updates its path_ field.

        The field should be renamed from path_ to path when update_payload is called.

    test_organization_rh_repo_url()
        Check whether Organization updates its redhat_repository_url field.

        The field should be copied from p['organization']['redhat_repository_url'] to
        p['redhat_repository_url'] when update_payload is called.

    test_os_default_template()
        Check, that os_default_template serves template_kind_id and
        provisioning_template_id only wrapped in sub dict See: Redmine #21169.

    test_subnet_from()
        Check whether Subnet updates its from_ field.

        The field should be renamed from from_ to from when update_payload is called.

    test_syncplan_sync_date()
        Test update_payload for different syncplan sync_date formats.

class tests.test_entities.UpdateTestCase (methodName='runTest')
    Tests for nailgun.entity_mixins.EntityUpdateMixin.update().

    classmethod setUpClass()
        Set a server configuration at cls.cfg.

    test_generic()
        Call update on a variety of entities.

```

class tests.test_entities.**VersionTestCase** (*methodName='runTest'*)

Tests for entities that vary based on the server's software version.

classmethod setUpClass()

Create several server configs with different versions.

test_missing_org_id()

Test methods for which no organization ID is returned.

Affected methods:

- `nailgun.entities.ContentView.read()`
- `nailgun.entities.Product.read()`

Assert that `read_json`, `_get_org` and `read` are all called once, and that the second is called with the correct arguments.

class tests.test_entities.**VirtWhoConfigTestCase** (*methodName='runTest'*)

Tests for `nailgun.entities.VirtWhoConfig`

classmethod setUpClass()

Hook method for setting up class fixture before running tests in the class.

test_methods()

Check that `get_organization_configs` helper method is sane.

This method is just like `tests.test_entities.GenericTestCase.test_generic()`, but with a slightly different set of mocks. Test the following:

- `nailgun.entities.VirtWhoConfig.get_organization_configs()`

tests.test_entities.**make_entity** (*cls, **kwargs*)

Helper function to create entity with dummy ServerConfig

2.2.4 tests.test_entity_fields

Unit tests for `nailgun.entity_fields`.

class tests.test_entity_fields.**GenValueTestCase** (*methodName='runTest'*)

Tests for the `gen_value` method on various `*Field` classes.

Classes with complex `gen_value` implementations are broken out into separate test cases.

test_boolean_field()

Test `nailgun.entity_fields.BooleanField.gen_value()`.

test_date_field()

Test `nailgun.entity_fields.DateField.gen_value()`.

test_datetime_field()

Test `nailgun.entity_fields.DateTimeField.gen_value()`.

test_dict_field()

Test `nailgun.entity_fields.DictField.gen_value()`.

Assert that an empty dict is returned by default. There are very few occurrences of dict fields in the entity classes, so it is hard to intelligently produce a randomized value that will be of use in a wide variety of entities. Instead, those few entities override or extend this method.

test_email_field()

Test `nailgun.entity_fields.EmailField.gen_value()`.

Ensure `nailgun.entity_fields.EmailField.gen_value()` returns a unicode string containing the character '@'.

test_float_field()

Test `nailgun.entity_fields.FloatField.gen_value()`.

test_gen_netmask()

Test `nailgun.entity_fields.NetmaskField.gen_value()`.

Assert that the result is in `fauxfactory.constants.VALID_NETMASKS`.

test_ip_address_field()

Test `nailgun.entity_fields.IPAddressField.gen_value()`.

Ensure the value returned is acceptable to `socket.inet_aton`.

test_mac_address_field()

Test `nailgun.entity_fields.MACAddressField.gen_value()`.

Ensure the value returned is a string containing 12 hex digits (either upper or lower case), grouped into pairs of digits and separated by colon characters. For example: '01:23:45:FE:dc:BA'

The regex used in this test is inspired by this Q&A: <http://stackoverflow.com/questions/7629643/how-do-i-validate-the-format-of-a-mac-address>

test_one_to_many_field()

Test `nailgun.entity_fields.OneToManyField.gen_value()`.

test_one_to_one_field()

Test `nailgun.entity_fields.OneToOneField.gen_value()`.

test_url_field()

Test `nailgun.entity_fields.URLField.gen_value()`.

Check that the result can be parsed by the `urlparse/urllib.parse` module and that the resultant object has a `netloc` attribute.

class `tests.test_entity_fields.IntegerFieldTestCase` (*methodName='runTest'*)

Tests for `nailgun.entity_fields.IntegerField`.

test_int_is_returned()

Enture the value returned is an int.

test_max_val_arg()

Ensure that the `max_val` argument is respected.

test_min_val_arg()

Ensure that the `min_val` argument is respected.

test_min_val_max_val_args()

Ensure that the `min_val` and `max_val` args are respected.

class `tests.test_entity_fields.StringFieldTestCase` (*methodName='runTest'*)

Tests for `nailgun.entity_fields.StringField`.

test_length_arg()

Ensure that the `length` argument is respected.

test_str_is_returned()

Ensure a unicode string at least 1 char long is returned.

test_str_type_arg()

Ensure that the `str_type` argument is respected.

class tests.test_entity_fields.**TestClass**
A class that is used when testing the OneTo{One,Many}Field classes.

2.2.5 tests.test_entity_mixins

Tests for *nailgun.entity_mixins*.

class tests.test_entity_mixins.**EntityCreateMixinTestCase** (*methodName='runTest'*)
Tests for *nailgun.entity_mixins.EntityCreateMixin*.

setUp()
Set self.entity = EntityWithCreate(...).

test_create()
Test *nailgun.entity_mixins.EntityCreateMixin.create()*.

test_create_json()
Test *nailgun.entity_mixins.EntityCreateMixin.create_json()*.

test_create_missing()
Call method *create_missing*.

test_create_raw_v1()
What happens if the *create_missing* arg is not specified?

nailgun.entity_mixins.EntityCreateMixin.create_raw() should default to *nailgun.entity_mixins.CREATE_MISSING*. We do not set *CREATE_MISSING* in this test. It is a process-wide variable, and setting it may prevent tests from being run in parallel.

test_create_raw_v2()
What happens if the *create_missing* arg is True?

test_create_raw_v3()
What happens if the *create_missing* arg is False?

class tests.test_entity_mixins.**EntityDeleteMixinTestCase** (*methodName='runTest'*)
Tests for *nailgun.entity_mixins.EntityDeleteMixin*.

setUp()
Set self.entity = EntityWithDelete(...).

test_delete_raw()
Call *nailgun.entity_mixins.EntityDeleteMixin.delete_raw()*.

test_delete_v1()
What happens if the server returns an error HTTP status code?

test_delete_v2()
What happens if the server returns an HTTP ACCEPTED status code?

test_delete_v3()
What happens if the server returns an HTTP NO_CONTENT status?

test_delete_v4()
What happens if the server returns some other success status?

test_delete_v5()
What happens if the server returns an HTTP OK status and empty content?

test_delete_v6()
What happens if the server returns an HTTP OK status and blank only content?

```

class tests.test_entity_mixins.EntityReadMixinTestCase (methodName='runTest')
    Tests for nailgun.entity_mixins.EntityReadMixin.

    setUp()
        Set self.entity = EntityWithRead(...).

    classmethod setUpClass()
        Set cls.test_entity.

        test_entity is a class having one to one and one to many fields.

    test_missing_value_error()
        Raise a nailgun.entity_mixins.MissingValueError.

    test_read_json()
        Call nailgun.entity_mixins.EntityReadMixin.read_json().

    test_read_raw()
        Call nailgun.entity_mixins.EntityReadMixin.read_raw().

    test_read_v1()
        Make read_json return hashes.

    test_read_v2()
        Make read_json return hashes, but with different field names.

    test_read_v3()
        Make read_json return IDs.

    test_read_v4()
        Do not ignore any fields.

class tests.test_entity_mixins.EntitySearchMixinTestCase (methodName='runTest')
    Tests for nailgun.entity_mixins.EntitySearchMixin.

    setUp()
        Set self.cfg and self.entity.

    test_search_filter_v1()
        Test nailgun.entity_mixins.EntitySearchMixin.search_filter().

        Pass a zero-length list of entities.

    test_search_filter_v2()
        Test nailgun.entity_mixins.EntitySearchMixin.search_filter().

        Try to filter on a foreign key field.

    test_search_filter_v3()
        Test nailgun.entity_mixins.EntitySearchMixin.search_filter().

        Pass an invalid filter.

    test_search_filter_v4()
        Test nailgun.entity_mixins.EntitySearchMixin.search_filter().

        Pass in valid entities and filters.

    test_search_json()
        Call nailgun.entity_mixins.EntitySearchMixin.search_json().

    test_search_normalize_v1()
        Call search_normalize.

        Pretend the server returns values for all fields, and an extra value.

```

test_search_normalize_v2()

Call `search_normalize`.

Pretend the server returns no values for any fields.

test_search_payload_v1()

Call `search_payload`. Generate an empty query.

test_search_payload_v2()

Call `search_payload`. Pass in a query.

test_search_payload_v3()

Call `search_payload`. Include a variety of fields in a search.

test_search_raw()

Call `nailgun.entity_mixins.EntitySearchMixin.search_raw()`.

test_search_v1()

Test `nailgun.entity_mixins.EntitySearchMixin.search()`.

Pass no arguments.

test_search_v2()

Test `nailgun.entity_mixins.EntitySearchMixin.search()`.

Provide each possible argument.

class `tests.test_entity_mixins.EntityTestCase` (*methodName='runTest'*)

Tests for `nailgun.entity_mixins.Entity`.

setUp()

Set `self.cfg`.

test_bad_value_error()

Try to raise a `nailgun.entity_mixins.BadValueError`.

test_compare()

Assert compare take only not unique fields into account

test_compare_to_null()

Assert entity comparison to None

test_compare_with_filter()

Assert compare can filter fields based on callable

test_entity_get_fields()

Test `nailgun.entity_mixins.Entity.get_fields()`.

test_entity_get_values()

Test `nailgun.entity_mixins.Entity.get_values()`.

test_entity_get_values_v2()

Test `nailgun.entity_mixins.Entity.get_values()`, ensure `_path_fields` are never returned.

test_eq()

Test method `nailgun.entity_mixins.Entity.__eq__`.

Assert that `__eq__` works comparing all attributes, even from nested structures.

test_eq_none()

Test method `nailgun.entity_mixins.Entity.__eq__` against None

Assert that `__eq__` returns False when compared to None.


```

test_init_v1 ()
    Provide no value for the server_config argument.

test_init_v2 ()
    Provide a server config object via DEFAULT_SERVER_CONFIG.

test_no_such_field_error ()
    Try to raise a nailgun.entity_mixins.NoSuchFieldError.

test_path ()
    Test nailgun.entity_mixins.Entity.path().

test_repr_v1 ()
    Test method nailgun.entity_mixins.Entity.__repr__.

    Assert that __repr__ works correctly when no arguments are passed to an entity.

test_repr_v2 ()
    Test method nailgun.entity_mixins.Entity.__repr__.

    Assert that __repr__ works correctly when an ID is passed to an entity.

test_repr_v3 ()
    Test method nailgun.entity_mixins.Entity.__repr__.

    Assert that __repr__ works correctly when one entity has a foreign key relationship to a second entity.

class tests.test_entity_mixins.EntityUpdateMixinTestCase (methodName='runTest')
    Tests for nailgun.entity_mixins.EntityUpdateMixin.

    setUp ()
        Set self.entity = EntityWithUpdate(...).

    test_update ()
        Test nailgun.entity_mixins.EntityUpdateMixin.update().

    test_update_json ()
        Call nailgun.entity_mixins.EntityUpdateMixin.update_json().

    test_update_payload_v1 ()
        Call nailgun.entity_mixins.EntityUpdateMixin.update_payload().

        Assert that the method behaves correctly given various values for the field argument.

    test_update_payload_v2 ()
        Call nailgun.entity_mixins.EntityUpdateMixin.update_payload().

        Assign None to a OneToOneField and call update_payload.

    test_update_raw ()
        Call nailgun.entity_mixins.EntityUpdateMixin.update_raw().

class tests.test_entity_mixins.EntityWithCreate (server_config=None, **kwargs)
    Inherits from nailgun.entity_mixins.EntityCreateMixin.

class tests.test_entity_mixins.EntityWithDelete (server_config=None, **kwargs)
    Inherits from nailgun.entity_mixins.EntityDeleteMixin.

class tests.test_entity_mixins.EntityWithRead (server_config=None, **kwargs)
    Inherits from nailgun.entity_mixins.EntityReadMixin.

class tests.test_entity_mixins.EntityWithSearch (server_config=None, **kwargs)
    Inherits from nailgun.entity_mixins.EntitySearchMixin.

```

```
class tests.test_entity_mixins.EntityWithSearch2 (server_config=None, **kwargs)
    An entity with integer, one to one and one to many fields.

class tests.test_entity_mixins.EntityWithUpdate (server_config=None, **kwargs)
    Inherits from nailgun.entity_mixins.EntityUpdateMixin.

class tests.test_entity_mixins.MakeEntitiesFromIdsTestCase (methodName='runTest')
    Tests for nailgun.entity_mixins._make_entities_from_ids().

    setUp()
        Set self.cfg.

    test_pass_in_both()
        Let entity_objs_and_ids be an iterable of integers and IDs.

    test_pass_in_empty_iterable()
        Let the entity_objs_and_ids argument be an empty iterable.

    test_pass_in_entity_ids()
        Let the entity_objs_and_ids arg be an iterable of integers.

    test_pass_in_entity_obj()
        Let the entity_objs_and_ids arg be an iterable of entities.

class tests.test_entity_mixins.MakeEntityFromIdTestCase (methodName='runTest')
    Tests for nailgun.entity_mixins._make_entity_from_id().

    setUp()
        Set self.cfg.

    test_pass_in_entity_id()
        Let the entity_obj_or_id argument be an integer.

    test_pass_in_entity_obj()
        Let the entity_obj_or_id argument be an entity object.

class tests.test_entity_mixins.PollTaskTestCase (methodName='runTest')
    Tests for nailgun.entity_mixins._poll_task().

    setUp()
        Create a bogus server configuration object.

    test_poll_task_failure()
        What happens when a foreman task completes but does not succeed?

        Assert that a nailgun.entity_mixins.TaskFailedError exception is raised.

    test_poll_task_success()
        What happens when a foreman task completes and does succeed?

        Assert that the server's response is returned.

    test_poll_task_timeout()
        What happens when a foreman task timesout? Assert that the task is still running.

class tests.test_entity_mixins.SampleEntity (server_config=None, **kwargs)
    Sample entity to be used in the tests

class tests.test_entity_mixins.SampleEntityThree (server_config=None, **kwargs)
    An entity with foreign key fields as One to One and ListField.

    This class has a nailgun.entity_fields.OneToOneField called "one_to_one" pointing to tests.test_entity_mixins.SampleEntityTwo.
```

This class has a *nailgun.entity_fields.ListField* called “list” containing instances of *tests.test_entity_mixins.SampleEntity*.

class tests.test_entity_mixins.**SampleEntityTwo** (*server_config=None, **kwargs*)

An entity with foreign key fields.

This class has a *nailgun.entity_fields.OneToManyField* called “one_to_many” pointing to *tests.test_entity_mixins.SampleEntity*.

This script demonstrates how to create and delete an organization, and how to save some of our work for later re-use:

```
>>> from nailgun.config import ServerConfig
>>> from nailgun.entities import Organization
>>> server_config = ServerConfig(
...     auth=('admin', 'changeme'),      # Use these credentials...
...     url='https://sat1.example.com', # ...to talk to this server.
... ) # More options are available, e.g. disabling SSL verification.
>>> org = Organization(server_config, name='junk org').create()
>>> org.name == 'junk org' # Access all attrs likewise, e.g. `org.label`
True
>>> org.delete()
>>> server_config.save() # Save to disk w/label 'default'. Read with get()
```

This example glosses over *many* features. The *Examples* and *API documentation* sections provide more in-depth documentation.

CHAPTER 4

Why NailGun?

NailGun exists to make working with the Satellite 6 API easier. Here are some of the challenges developers face:

- Existing libraries, such as the Python [Requests](#) library, are general purpose tools. As a result, client code can easily become excessively verbose. See the [Examples](#) document for an example.
- The Satellite 6 API is not RESTful in its design. As a result, even experienced developers may find the API hard to work with.
- The Satellite 6 API is not consistent in its implementation. For example, see the “Payload Generation” section of [this blog post](#).

All of the above issues are compounded by the size of the Satellite 6 API. As of this writing, there are 405 paths. This makes it tough to design compact and elegant client code.

NailGun addresses these issues. NailGun is specialized, it has a consistent design, it abstracts away many painful implementation details and it contains workarounds for certain bugs. Why use a hammer when you can use a nail gun?

Scope and Limitations

NailGun is not an officially supported product. NailGun is a Python-only library, and integration with other languages such as Java or Ruby is not currently a consideration. Although NailGun is developed with a broad audience in mind, it targets [Robottelo](#) first and foremost.

NailGun was originally conceived as a set of helper routines internal to [Robottelo](#). It has since been extracted from that code base and turned in to an independently useful library.

Warning: Until version 1.0 is released, functionality will be incomplete, and breaking changes may be introduced. Users are advised to read the release notes closely.

CHAPTER 6

Resources

The *Examples* and *API documentation* sections provide more in-depth documentation.

Join the #robbtelo channel on the [freenode](#) IRC network to chat with a human. The [Robottelo source code](#) contains many real-world examples how NailGun is used, especially the `tests/foreman/api/` directory. [This blog post](#) provides a glimpse in to the challenges that NailGun is designed to overcome.

Contributions are encouraged. The easiest way to contribute is to submit a pull request on GitHub, but patches are welcome no matter how they arrive.

You can use pip and make to quickly set up a development environment:

```
pip install -r requirements.txt -r requirements-dev.txt
pre-commit install-hooks
make test
make docs-html
```

Please adhere to the following guidelines:

- All PR's should follow the predetermined pull request template and explain the problem that is addressed. Issues should follow template and explain what the problem is.
- **Maintain Coding Standards**
 - Keep pep8 rules
 - **Follow the same stylistic and logical patterns used in the code**
 - * All entity class names and class attributes have to be in the singular format
 - * All required entity attributes have to have *required=True* parameter
 - * It is preferable to use *alpha* data type for default string values for easier debug procedure
 - * In case any workaround is introduced, it is necessary to provide corresponding BZ ID directly into the code docstring
 - * All linting (flake8) and formatting/style checks would be enforced by Travis-CI and PR would be considered broken until checks are passed successfully.
 - * Use of pre-commit configuration included with repo will ensure style compliance locally before commit, helping reduce travis failures.
- **Adhere to typical commit guidelines:**

- Commits should not cause NailGun’s unit test to fail. If it does, it will be the responsibility of contributor to review those failures and fix them in the same PR’s or raise another. The tracking of failures would be responsibility of contributor.
- Commits should be small and coherent. One commit should address one issue.
- Commits should have [good commit messages](#).
- [Rebasing](#) is encouraged. Rebasing produces a much nicer commit history than merging.
- To make the review process easy for all reviewers and anyone else interested in the new functionality, please provide some output making use of your changes. Having example of usage in docstring along with your code could really help others to build up on your code. You can add log from Python interactive shell or some tests results (from Robottelo / Foreman Ansible Modules) in PR message, or you can do something completely different - as long as it runs your code, it’s fine!
- If PR is applicable for many branches (e.g. master and one of ‘6.X.z’ branches), specify that information in PR message
- **Unit tests**
 - Unit tests are compulsory
 - Unit tests should cover all available actions, for the entity. For eg: Repository Sets, have enable, disable, list_available there should be unit tests exercising these actions.
- When in doubt, ask on IRC. Join #robottelo on [freenode](#)

Important to Note :

- **Define Foreman Version labels in Nailgun** if possible, the contributor should set the right version.
- **All PRs should be raised along with Unit tests** The unit tests should be added while adding a new entity or modifying the existing entity or modifying and adding to the core of Nailgun.
- **Test results from upstream devel or from upstream nightly** The API call results are required from PR author to make the review process more firm. Author can provide results from any library that uses the contributed code by running the changes on upstream nightly or from his/her devel box. The interactive python shell output would be acceptable as well.

7.1 Nailgun Review Process

- Travis CI is run, and any issues are resolved by contributor.
- If deemed necessary by contributors/reviewers, an automation run is triggered.
- At least two ACKs are required to merge a pull request.
- At least one ACK must be from a Tier 2 reviewer.
- If a PR requires changes to the CI environment, the “CI Owner” must also provide an ACK.
- Pull request can be merged only when all comments are in resolved state (Resolve conversation button is pressed)

Reviewers & Responsibilities :

- **Both Tiers**
 - Consistently check your projects for new pull requests.
 - Check code for consistency with project guidelines.
 - Pin code dependencies (external libraries), against the version it was tested.

- Determine if CI and/or test infrastructure changes are required.
- Provide helpful feedback.
- Follow-up with any pending feedback, to ensure the PR is resolved quickly.
- **Tier 1 Reviewer**
 - Check the scenarios are valid for the feature or components
 - Suggestions on the feature that can be covered with minimal code additions/changes.
- **Tier 2 Reviewer**
 - Check for logical errors.
 - Guide the contributor on how to fix mistakes and any other improvements.
 - Ideally if not done by contributor, identify code that may impact third-party projects (e.g Nailgun -> Robottelo , FAM), file issues if PR causes breakages in relevant projects

7.2 Nailgun Release Process

Projects that require nailgun, would often rely on the released Nailgun from Pypi. We intended to make the release process more formal and standard to deliver timely and stable code base to consumer projects.

- Nailgun Releases should be performed against stable branches.
- No historical release support.
- Nailgun will follow request based minor releases.

n

nailgun, 15
nailgun.client, 94
nailgun.config, 91
nailgun.entities, 15
nailgun.entity_fields, 89
nailgun.entity_mixins, 75

t

tests, 95
tests.test_client, 95
tests.test_config, 96
tests.test_entities, 97
tests.test_entity_fields, 112
tests.test_entity_mixins, 114

Symbols

- `_get_config_file_path()` (in module `nailgun.config`), 94
 - `_get_entity_id()` (in module `nailgun.entity_mixins`), 87
 - `_get_entity_ids()` (in module `nailgun.entity_mixins`), 87
 - `_get_server_config()` (in module `nailgun.entity_mixins`), 87
 - `_make_entities_from_ids()` (in module `nailgun.entity_mixins`), 87
 - `_make_entity_from_id()` (in module `nailgun.entity_mixins`), 88
 - `_payload()` (in module `nailgun.entity_mixins`), 88
 - `_poll_task()` (in module `nailgun.entity_mixins`), 88
- ## A
- `AbstractComputeResource` (class in `nailgun.entities`), 16
 - `AbstractContentViewFilter` (class in `nailgun.entities`), 18
 - `ActivationKey` (class in `nailgun.entities`), 18
 - `add()` (`nailgun.entities.ContentViewComponent` method), 25
 - `add_host_collection()` (`nailgun.entities.ActivationKey` method), 18
 - `add_products()` (`nailgun.entities.SyncPlan` method), 71
 - `add_puppetclass()` (`nailgun.entities.Host` method), 34
 - `add_puppetclass()` (`nailgun.entities.HostGroup` method), 42
 - `add_subscriptions()` (`nailgun.entities.ActivationKey` method), 18
 - `add_subscriptions()` (`nailgun.entities.HostSubscription` method), 45
 - `APIResponseError`, 16
 - `Architecture` (class in `nailgun.entities`), 20
 - `ArfReport` (class in `nailgun.entities`), 21
 - `associate()` (`nailgun.entities.AbstractComputeResource` method), 16
 - `Audit` (class in `nailgun.entities`), 21
 - `AuthSourceLDAP` (class in `nailgun.entities`), 21
 - `auto_provision()` (`nailgun.entities.DiscoveredHost` method), 27
 - `auto_provision_all()` (`nailgun.entities.DiscoveredHost` method), 28
 - `available_flavors()` (`nailgun.entities.AbstractComputeResource` method), 16
 - `available_images()` (`nailgun.entities.AbstractComputeResource` method), 16
 - `available_networks()` (`nailgun.entities.AbstractComputeResource` method), 16
 - `available_repositories()` (`nailgun.entities.RepositorySet` method), 64
 - `available_zones()` (`nailgun.entities.AbstractComputeResource` method), 17
 - `AzureRMComputeResource` (class in `nailgun.entities`), 22
- ## B
- `BadValueError`, 75
 - `BaseServerConfig` (class in `nailgun.config`), 91
 - `BaseServerConfigTestCase` (class in `tests.test_config`), 96
 - `Bookmark` (class in `nailgun.entities`), 22
 - `BooleanField` (class in `nailgun.entity_fields`), 89
 - `build_pxe_default()` (`nailgun.entities.ProvisioningTemplate` method), 56
 - `bulk_add_subscriptions()` (`nailgun.entities.Host` method), 34
 - `bulk_available_incremental_updates()` (`nailgun.entities.Host` method), 35
 - `bulk_destroy()` (`nailgun.entities.Host` method), 35

- bulk_remove_subscriptions() (*nailgun.entities.Host method*), 35
 bulk_resolve_traces() (*nailgun.entities.Host method*), 35
 bulk_traces() (*nailgun.entities.Host method*), 36
- ## C
- cancel() (*nailgun.entities.RecurringLogic method*), 58
 Capsule (*class in nailgun.entities*), 22
 ClientTestCase (*class in tests.test_client*), 95
 clone() (*nailgun.entities.HostGroup method*), 43
 clone() (*nailgun.entities.ProvisioningTemplate method*), 56
 clone() (*nailgun.entities.ReportTemplate method*), 59
 clone() (*nailgun.entities.Role method*), 65
 CommonParameter (*class in nailgun.entities*), 23
 compare() (*nailgun.entities.Errata method*), 31
 compare() (*nailgun.entity_mixins.Entity method*), 76
 CompliancePolicies (*class in nailgun.entities*), 23
 ComputeAttribute (*class in nailgun.entities*), 23
 ComputeProfile (*class in nailgun.entities*), 23
 ConfigFileError, 93
 ConfigGroup (*class in nailgun.entities*), 23
 content_add_lifecycle_environment() (*nailgun.entities.Capsule method*), 22
 content_get_sync() (*nailgun.entities.Capsule method*), 22
 content_lifecycle_environments() (*nailgun.entities.Capsule method*), 22
 content_override() (*nailgun.entities.ActivationKey method*), 18
 content_sync() (*nailgun.entities.Capsule method*), 23
 ContentCredential (*class in nailgun.entities*), 23
 ContentTypeIsJsonTestCase (*class in tests.test_client*), 95
 ContentUpload (*class in nailgun.entities*), 23
 ContentUploadTestCase (*class in tests.test_entities*), 97
 ContentView (*class in nailgun.entities*), 24
 ContentViewComponent (*class in nailgun.entities*), 25
 ContentViewComponentTestCase (*class in tests.test_entities*), 98
 ContentViewFilterRule (*class in nailgun.entities*), 26
 ContentViewTestCase (*class in tests.test_entities*), 98
 ContentViewVersion (*class in nailgun.entities*), 27
 copy() (*nailgun.entities.ActivationKey method*), 19
 copy() (*nailgun.entities.ContentView method*), 24
 create() (*nailgun.entities.DiscoveryRule method*), 30
 create() (*nailgun.entities.Domain method*), 30
 create() (*nailgun.entities.Host method*), 36
 create() (*nailgun.entities.HostCollection method*), 42
 create() (*nailgun.entities.HostGroup method*), 43
 create() (*nailgun.entities.Location method*), 48
 create() (*nailgun.entities.Media method*), 48
 create() (*nailgun.entities.Organization method*), 50
 create() (*nailgun.entities.Realm method*), 58
 create() (*nailgun.entities.ScapContents method*), 66
 create() (*nailgun.entities.TailoringFile method*), 72
 create() (*nailgun.entities.UserGroup method*), 74
 create() (*nailgun.entity_mixins.EntityCreateMixin method*), 78
 create_json() (*nailgun.entity_mixins.EntityCreateMixin method*), 79
 CREATE_MISSING (*in module nailgun.entity_mixins*), 75
 create_missing() (*nailgun.entities.AuthSourceLDAP method*), 21
 create_missing() (*nailgun.entities.Domain method*), 30
 create_missing() (*nailgun.entities.Host method*), 36
 create_missing() (*nailgun.entities.LifecycleEnvironment method*), 48
 create_missing() (*nailgun.entities.ProvisioningTemplate method*), 56
 create_missing() (*nailgun.entities.Repository method*), 61
 create_missing() (*nailgun.entity_mixins.EntityCreateMixin method*), 79
 create_payload() (*nailgun.entities.AbstractComputeResource method*), 17
 create_payload() (*nailgun.entities.Architecture method*), 20
 create_payload() (*nailgun.entities.ContentViewFilterRule method*), 26
 create_payload() (*nailgun.entities.DiscoveredHost method*), 28
 create_payload() (*nailgun.entities.DiscoveryRule method*), 30
 create_payload() (*nailgun.entities.Domain method*), 30
 create_payload() (*nailgun.entities.Environment method*), 31
 create_payload() (*nailgun.entities.Filter method*), 32
 create_payload() (*nailgun.entities.Host method*), 36

create_payload() (*nailgun.entities.HostCollection method*), 42
 create_payload() (*nailgun.entities.HostGroup method*), 43
 create_payload() (*nailgun.entities.HTTPProxy method*), 34
 create_payload() (*nailgun.entities.Image method*), 46
 create_payload() (*nailgun.entities.JobTemplate method*), 47
 create_payload() (*nailgun.entities.Location method*), 48
 create_payload() (*nailgun.entities.Media method*), 48
 create_payload() (*nailgun.entities.OperatingSystem method*), 49
 create_payload() (*nailgun.entities.OverrideValue method*), 52
 create_payload() (*nailgun.entities.ProvisioningTemplate method*), 56
 create_payload() (*nailgun.entities.RegistrationCommand method*), 59
 create_payload() (*nailgun.entities.ReportTemplate method*), 59
 create_payload() (*nailgun.entities.Role method*), 65
 create_payload() (*nailgun.entities.SmartVariable method*), 68
 create_payload() (*nailgun.entities.Subnet method*), 69
 create_payload() (*nailgun.entities.SyncPlan method*), 71
 create_payload() (*nailgun.entities.TailoringFile method*), 72
 create_payload() (*nailgun.entities.User method*), 73
 create_payload() (*nailgun.entities.UserGroup method*), 74
 create_payload() (*nailgun.entities.VirtWhoConfig method*), 74
 create_payload() (*nailgun.entity_mixins.EntityCreateMixin method*), 79
 create_raw() (*nailgun.entity_mixins.EntityCreateMixin method*), 79
 CreateMissingTestCase (*class in tests.test_entities*), 98
 CreatePayloadTestCase (*class in tests.test_entities*), 100
 CreateTestCase (*class in tests.test_entities*), 100

D

DateField (*class in nailgun.entity_fields*), 89
 DateTimeField (*class in nailgun.entity_fields*), 89
 DEFAULT_SERVER_CONFIG (*in module nailgun.entity_mixins*), 75
 delete() (*in module nailgun.client*), 94
 delete() (*nailgun.config.BaseServerConfig class method*), 92
 delete() (*nailgun.entity_mixins.EntityDeleteMixin method*), 79
 delete_from_environment() (*nailgun.entities.ContentView method*), 25
 delete_manifest() (*nailgun.entities.Subscription method*), 69
 delete_puppetclass() (*nailgun.entities.Host method*), 37
 delete_puppetclass() (*nailgun.entities.HostGroup method*), 43
 delete_raw() (*nailgun.entity_mixins.EntityDeleteMixin method*), 80
 deploy() (*nailgun.entities.RHCIDeployment method*), 58
 deploy_script() (*nailgun.entities.VirtWhoConfig method*), 74
 destroy() (*nailgun.entities.ProductBulkAction method*), 54
 DictField (*class in nailgun.entity_fields*), 89
 disable() (*nailgun.entities.RepositorySet method*), 64
 disassociate() (*nailgun.entities.Host method*), 37
 DiscoveredHost (*class in nailgun.entities*), 27
 DiscoveryRule (*class in nailgun.entities*), 30
 DockerContentViewFilter (*class in nailgun.entities*), 30
 Domain (*class in nailgun.entities*), 30
 download_debug_certificate() (*nailgun.entities.Organization method*), 50
 download_html() (*nailgun.entities.ArjReport method*), 21

E

EmailField (*class in nailgun.entity_fields*), 89
 enable() (*nailgun.entities.RepositorySet method*), 64
 enc() (*nailgun.entities.Host method*), 37
 Entity (*class in nailgun.entity_mixins*), 75
 EntityCreateMixin (*class in nailgun.entity_mixins*), 78
 EntityCreateMixinTestCase (*class in tests.test_entity_mixins*), 114
 EntityDeleteMixin (*class in nailgun.entity_mixins*), 79
 EntityDeleteMixinTestCase (*class in tests.test_entity_mixins*), 114

- EntityReadMixin (class in *nailgun.entity_mixins*), 80
- EntityReadMixinTestCase (class in *tests.test_entity_mixins*), 114
- EntitySearchMixin (class in *nailgun.entity_mixins*), 81
- EntitySearchMixinTestCase (class in *tests.test_entity_mixins*), 115
- EntityTestCase (class in *tests.test_entity_mixins*), 116
- EntityUpdateMixin (class in *nailgun.entity_mixins*), 85
- EntityUpdateMixinTestCase (class in *tests.test_entity_mixins*), 117
- EntityWithCreate (class in *tests.test_entity_mixins*), 117
- EntityWithDelete (class in *tests.test_entity_mixins*), 117
- EntityWithRead (class in *tests.test_entity_mixins*), 117
- EntityWithSearch (class in *tests.test_entity_mixins*), 117
- EntityWithSearch2 (class in *tests.test_entity_mixins*), 117
- EntityWithUpdate (class in *tests.test_entity_mixins*), 118
- Environment (class in *nailgun.entities*), 31
- Errata (class in *nailgun.entities*), 31
- errata() (*nailgun.entities.Host* method), 37
- errata() (*nailgun.entities.Repository* method), 61
- errata_applicability() (*nailgun.entities.Host* method), 38
- errata_apply() (*nailgun.entities.Host* method), 38
- ErratumContentViewFilter (class in *nailgun.entities*), 32
- exports() (*nailgun.entities.Template* method), 72
- ExternalUserGroup (class in *nailgun.entities*), 32
- ## F
- facts() (*nailgun.entities.DiscoveredHost* method), 28
- Field (class in *nailgun.entity_fields*), 90
- File (class in *nailgun.entities*), 32
- files() (*nailgun.entities.Repository* method), 61
- FileTestCase (class in *tests.test_entities*), 100
- Filter (class in *nailgun.entities*), 32
- FloatField (class in *nailgun.entity_fields*), 90
- ForemanStatus (class in *nailgun.entities*), 33
- ForemanStatusTestCase (class in *tests.test_entities*), 100
- ForemanTask (class in *nailgun.entities*), 33
- ForemanTaskTestCase (class in *tests.test_entities*), 101
- ## G
- GCEComputeResource (class in *nailgun.entities*), 34
- gen_value() (*nailgun.entity_fields.BooleanField* method), 89
- gen_value() (*nailgun.entity_fields.DateField* method), 89
- gen_value() (*nailgun.entity_fields.DateTimeField* method), 89
- gen_value() (*nailgun.entity_fields.DictField* method), 89
- gen_value() (*nailgun.entity_fields.EmailField* method), 89
- gen_value() (*nailgun.entity_fields.FloatField* method), 90
- gen_value() (*nailgun.entity_fields.IntegerField* method), 90
- gen_value() (*nailgun.entity_fields.IPAddressField* method), 90
- gen_value() (*nailgun.entity_fields.MACAddressField* method), 90
- gen_value() (*nailgun.entity_fields.NetmaskField* method), 90
- gen_value() (*nailgun.entity_fields.OneToManyField* method), 90
- gen_value() (*nailgun.entity_fields.OneToOneField* method), 91
- gen_value() (*nailgun.entity_fields.StringField* method), 91
- gen_value() (*nailgun.entity_fields.URLField* method), 91
- generate() (*nailgun.entities.ReportTemplate* method), 60
- GenericTestCase (class in *tests.test_entities*), 101
- GenValueTestCase (class in *tests.test_entity_fields*), 112
- get() (in module *nailgun.client*), 94
- get() (*nailgun.config.BaseServerConfig* class method), 92
- get() (*nailgun.config.ServerConfig* class method), 93
- get_client_kwargs() (*nailgun.config.ServerConfig* method), 93
- get_facts() (*nailgun.entities.Host* method), 38
- get_fields() (*nailgun.entity_mixins.Entity* method), 77
- get_labels() (*nailgun.config.BaseServerConfig* class method), 92
- get_organization_configs() (*nailgun.entities.VirtWhoConfig* method), 74
- get_values() (*nailgun.entities.Host* method), 39
- get_values() (*nailgun.entity_mixins.Entity* method), 77
- GetOrgTestCase (class in *tests.test_entities*), 101
- GPGKey (class in *nailgun.entities*), 34

H

HandleResponseTestCase (class in *tests.test_entities*), 102
 head() (in module *nailgun.client*), 94
 Host (class in *nailgun.entities*), 34
 HostCollection (class in *nailgun.entities*), 42
 HostCollectionErrata (class in *nailgun.entities*), 42
 HostCollectionPackage (class in *nailgun.entities*), 42
 HostGroup (class in *nailgun.entities*), 42
 HostGroupTestCase (class in *tests.test_entities*), 102
 HostPackage (class in *nailgun.entities*), 45
 HostSubscription (class in *nailgun.entities*), 45
 HostTestCase (class in *tests.test_entities*), 103
 http_proxy() (*nailgun.entities.ProductBulkAction* method), 54
 HTTPProxy (class in *nailgun.entities*), 34

I

Image (class in *nailgun.entities*), 46
 images() (*nailgun.entities.AbstractComputeResource* method), 17
 import_puppetclasses() (*nailgun.entities.SmartProxy* method), 67
 import_uploads() (*nailgun.entities.Repository* method), 61
 imports() (*nailgun.entities.Template* method), 73
 incremental_update() (*nailgun.entities.ContentViewVersion* method), 27
 InitTestCase (class in *tests.test_entities*), 103
 install_content() (*nailgun.entities.Host* method), 39
 IntegerField (class in *nailgun.entity_fields*), 90
 IntegerFieldTestCase (class in *tests.test_entity_fields*), 113
 Interface (class in *nailgun.entities*), 46
 IPAddressField (class in *nailgun.entity_fields*), 90

J

JobInvocation (class in *nailgun.entities*), 47
 JobInvocationTestCase (class in *tests.test_entities*), 104
 JobTemplate (class in *nailgun.entities*), 47
 JobTemplateTestCase (class in *tests.test_entities*), 104
 JsonSerializerizableTestCase (class in *tests.test_entities*), 104

K

KatelloStatus (class in *nailgun.entities*), 47

L

LibvirtComputeResource (class in *nailgun.entities*), 48
 LifecycleEnvironment (class in *nailgun.entities*), 48
 list_scparams() (*nailgun.entities.Environment* method), 31
 list_scparams() (*nailgun.entities.Host* method), 39
 list_scparams() (*nailgun.entities.HostGroup* method), 44
 list_scparams() (*nailgun.entities.PuppetClass* method), 57
 list_smart_variables() (*nailgun.entities.Host* method), 39
 list_smart_variables() (*nailgun.entities.HostGroup* method), 44
 list_smart_variables() (*nailgun.entities.PuppetClass* method), 57
 ListField (class in *nailgun.entity_fields*), 90
 Location (class in *nailgun.entities*), 48

M

MACAddressField (class in *nailgun.entity_fields*), 90
 make_entity() (in module *tests.test_entities*), 112
 MakeEntitiesFromIdsTestCase (class in *tests.test_entity_mixins*), 118
 MakeEntityFromIdTestCase (class in *tests.test_entity_mixins*), 118
 manifest_history() (*nailgun.entities.Subscription* method), 69
 Media (class in *nailgun.entities*), 48
 MissingValueError, 86
 Model (class in *nailgun.entities*), 49
 module_streams() (*nailgun.entities.Host* method), 39
 module_streams() (*nailgun.entities.Repository* method), 62
 ModuleStream (class in *nailgun.entities*), 49
 ModuleStreamContentViewFilter (class in *nailgun.entities*), 49
 ModuleStreamTestCase (class in *tests.test_entities*), 104

N

nailgun (module), 15
 nailgun.client (module), 94
 nailgun.config (module), 91
 nailgun.entities (module), 15
 nailgun.entity_fields (module), 89
 nailgun.entity_mixins (module), 75
 NetmaskField (class in *nailgun.entity_fields*), 90
 NoSuchFieldError, 86
 NoSuchPathError, 86

O

OneToManyField (class in *nailgun.entity_fields*), 90
 OneToOneField (class in *nailgun.entity_fields*), 91
 OperatingSystem (class in *nailgun.entities*), 49
 OperatingSystemParameter (class in *nailgun.entities*), 49
 Organization (class in *nailgun.entities*), 50
 OSDefaultTemplate (class in *nailgun.entities*), 49
 OverrideValue (class in *nailgun.entities*), 52
 OVirtComputeResource (class in *nailgun.entities*), 49
 owner_type (*nailgun.entities.Host* attribute), 40

P

Package (class in *nailgun.entities*), 53
 PackageGroup (class in *nailgun.entities*), 53
 PackageGroupContentViewFilter (class in *nailgun.entities*), 53
 PackageGroupTestCase (class in *tests.test_entities*), 104
 packages () (*nailgun.entities.Host* method), 40
 packages () (*nailgun.entities.Repository* method), 62
 PackageTestCase (class in *tests.test_entities*), 104
 Parameter (class in *nailgun.entities*), 53
 PartitionTable (class in *nailgun.entities*), 53
 patch () (in module *nailgun.client*), 94
 path () (*nailgun.entities.AbstractComputeResource* method), 17
 path () (*nailgun.entities.ActivationKey* method), 19
 path () (*nailgun.entities.ArfReport* method), 21
 path () (*nailgun.entities.Capsule* method), 23
 path () (*nailgun.entities.ContentUpload* method), 23
 path () (*nailgun.entities.ContentView* method), 25
 path () (*nailgun.entities.ContentViewComponent* method), 26
 path () (*nailgun.entities.ContentViewVersion* method), 27
 path () (*nailgun.entities.DiscoveredHost* method), 28
 path () (*nailgun.entities.Environment* method), 31
 path () (*nailgun.entities.Errata* method), 32
 path () (*nailgun.entities.ExternalUserGroup* method), 32
 path () (*nailgun.entities.ForemanTask* method), 33
 path () (*nailgun.entities.Host* method), 40
 path () (*nailgun.entities.HostGroup* method), 44
 path () (*nailgun.entities.HostSubscription* method), 45
 path () (*nailgun.entities.Organization* method), 50
 path () (*nailgun.entities.Product* method), 53
 path () (*nailgun.entities.ProductBulkAction* method), 55
 path () (*nailgun.entities.ProvisioningTemplate* method), 56
 path () (*nailgun.entities.PuppetClass* method), 57
 path () (*nailgun.entities.RecurringLogic* method), 59

path () (*nailgun.entities.ReportTemplate* method), 60
 path () (*nailgun.entities.Repository* method), 62
 path () (*nailgun.entities.RepositorySet* method), 65
 path () (*nailgun.entities.RHCIDeployment* method), 58
 path () (*nailgun.entities.Role* method), 66
 path () (*nailgun.entities.ScapContents* method), 66
 path () (*nailgun.entities.SmartProxy* method), 67
 path () (*nailgun.entities.Snapshot* method), 68
 path () (*nailgun.entities.Subscription* method), 70
 path () (*nailgun.entities.SyncPlan* method), 71
 path () (*nailgun.entities.Template* method), 73
 path () (*nailgun.entities.VirtWhoConfig* method), 75
 path () (*nailgun.entity_mixins.Entity* method), 77
 PathTestCase (class in *tests.test_entities*), 105
 Permission (class in *nailgun.entities*), 53
 Ping (class in *nailgun.entities*), 53
 poll () (*nailgun.entities.ForemanTask* method), 33
 PollTaskTestCase (class in *tests.test_entity_mixins*), 118
 post () (in module *nailgun.client*), 94
 power () (*nailgun.entities.Host* method), 40
 Product (class in *nailgun.entities*), 53
 product_content () (*nailgun.entities.ActivationKey* method), 19
 ProductBulkAction (class in *nailgun.entities*), 54
 promote () (*nailgun.entities.ContentViewVersion* method), 27
 ProvisioningTemplate (class in *nailgun.entities*), 55
 ProvisioningTemplateTestCase (class in *tests.test_entities*), 106
 publish () (*nailgun.entities.ContentView* method), 25
 PuppetClass (class in *nailgun.entities*), 57
 PuppetClassTestCase (class in *tests.test_entities*), 106
 put () (in module *nailgun.client*), 94

R

read () (*nailgun.entities.AuthSourceLDAP* method), 21
 read () (*nailgun.entities.AzureRMComputeResource* method), 22
 read () (*nailgun.entities.ContentUpload* method), 23
 read () (*nailgun.entities.ContentView* method), 25
 read () (*nailgun.entities.ContentViewComponent* method), 26
 read () (*nailgun.entities.ContentViewFilterRule* method), 26
 read () (*nailgun.entities.DiscoveredHost* method), 29
 read () (*nailgun.entities.DiscoveryRule* method), 30
 read () (*nailgun.entities.Domain* method), 30
 read () (*nailgun.entities.Errata* method), 32
 read () (*nailgun.entities.ExternalUserGroup* method), 32
 read () (*nailgun.entities.Filter* method), 33

- read() (*nailgun.entities.Host* method), 41
 read() (*nailgun.entities.HostGroup* method), 44
 read() (*nailgun.entities.HTTPProxy* method), 34
 read() (*nailgun.entities.Image* method), 46
 read() (*nailgun.entities.Interface* method), 47
 read() (*nailgun.entities.JobTemplate* method), 47
 read() (*nailgun.entities.Location* method), 48
 read() (*nailgun.entities.Media* method), 49
 read() (*nailgun.entities.OperatingSystemParameter* method), 49
 read() (*nailgun.entities.Organization* method), 51
 read() (*nailgun.entities.OSDefaultTemplate* method), 49
 read() (*nailgun.entities.OverrideValue* method), 52
 read() (*nailgun.entities.OVirtComputeResource* method), 49
 read() (*nailgun.entities.Parameter* method), 53
 read() (*nailgun.entities.Product* method), 53
 read() (*nailgun.entities.ProvisioningTemplate* method), 56
 read() (*nailgun.entities.RegistrationCommand* method), 59
 read() (*nailgun.entities.Repository* method), 63
 read() (*nailgun.entities.RepositorySet* method), 65
 read() (*nailgun.entities.RHCIDeployment* method), 58
 read() (*nailgun.entities.ScapContents* method), 66
 read() (*nailgun.entities.Setting* method), 67
 read() (*nailgun.entities.SmartClassParameters* method), 67
 read() (*nailgun.entities.SmartProxy* method), 67
 read() (*nailgun.entities.SmartVariable* method), 68
 read() (*nailgun.entities.Snapshot* method), 68
 read() (*nailgun.entities.SSHKey* method), 66
 read() (*nailgun.entities.Subnet* method), 69
 read() (*nailgun.entities.Subscription* method), 70
 read() (*nailgun.entities.SyncPlan* method), 71
 read() (*nailgun.entities.TailoringFile* method), 72
 read() (*nailgun.entities.TemplateInput* method), 73
 read() (*nailgun.entities.User* method), 73
 read() (*nailgun.entities.UserGroup* method), 74
 read() (*nailgun.entities.VirtWhoConfig* method), 75
 read() (*nailgun.entities.VMWareComputeResource* method), 74
 read() (*nailgun.entity_mixins.EntityReadMixin* method), 80
 read_json() (*nailgun.entity_mixins.EntityReadMixin* method), 81
 read_raw() (*nailgun.entity_mixins.EntityReadMixin* method), 81
 ReadTestCase (class in *tests.test_entities*), 106
 Realm (class in *nailgun.entities*), 58
 reboot() (*nailgun.entities.DiscoveredHost* method), 29
 reboot_all() (*nailgun.entities.DiscoveredHost* method), 29
 rebuild_config() (*nailgun.entities.HostGroup* method), 45
 RecurringLogic (class in *nailgun.entities*), 58
 refresh() (*nailgun.entities.ExternalUserGroup* method), 32
 refresh() (*nailgun.entities.SmartProxy* method), 68
 refresh_facts() (*nailgun.entities.DiscoveredHost* method), 29
 refresh_manifest() (*nailgun.entities.Subscription* method), 70
 RegistrationCommand (class in *nailgun.entities*), 59
 remove() (*nailgun.entities.ContentViewComponent* method), 26
 remove_content() (*nailgun.entities.Repository* method), 63
 remove_host_collection() (*nailgun.entities.ActivationKey* method), 20
 remove_products() (*nailgun.entities.SyncPlan* method), 72
 remove_subscriptions() (*nailgun.entities.ActivationKey* method), 20
 remove_subscriptions() (*nailgun.entities.HostSubscription* method), 46
 Report (class in *nailgun.entities*), 59
 report_data() (*nailgun.entities.ReportTemplate* method), 60
 ReportTemplate (class in *nailgun.entities*), 59
 ReportTemplateTestCase (class in *tests.test_entities*), 108
 Repository (class in *nailgun.entities*), 61
 RepositorySet (class in *nailgun.entities*), 64
 RepositorySetTestCase (class in *tests.test_entities*), 108
 RepositoryTestCase (class in *tests.test_entities*), 108
 ReprTestCase (class in *tests.test_config*), 96
 request() (in module *nailgun.client*), 94
 resolve_traces() (*nailgun.entities.Host* method), 41
 revert() (*nailgun.entities.Snapshot* method), 69
 rh_cloud_download_report() (*nailgun.entities.Organization* method), 51
 rh_cloud_generate_report() (*nailgun.entities.Organization* method), 51
 rh_cloud_inventory_sync() (*nailgun.entities.Organization* method), 51
 RHCIDeployment (class in *nailgun.entities*), 58
 Role (class in *nailgun.entities*), 65
 RoleLDAPGroups (class in *nailgun.entities*), 66
 RPMContentViewFilter (class in *nailgun.entities*), 58

`run()` (*nailgun.entities.JobInvocation* method), 47

S

`SampleEntity` (class in *tests.test_entity_mixins*), 118

`SampleEntityThree` (class in *tests.test_entity_mixins*), 118

`SampleEntityTwo` (class in *tests.test_entity_mixins*), 119

`save()` (*nailgun.config.BaseServerConfig* method), 92

`sca_disable()` (*nailgun.entities.Organization* method), 51

`sca_eligible()` (*nailgun.entities.Organization* method), 52

`sca_enable()` (*nailgun.entities.Organization* method), 52

`ScapContents` (class in *nailgun.entities*), 66

`ScapContentsTestCase` (class in *tests.test_entities*), 109

`schedule_report()` (*nailgun.entities.ReportTemplate* method), 60

`search()` (*nailgun.entities.ContentView* method), 25

`search()` (*nailgun.entities.Host* method), 41

`search()` (*nailgun.entities.Product* method), 54

`search()` (*nailgun.entity_mixins.EntitySearchMixin* method), 81

`search_filter()` (*nailgun.entity_mixins.EntitySearchMixin* static method), 83

`search_json()` (*nailgun.entity_mixins.EntitySearchMixin* method), 83

`search_normalize()` (*nailgun.entities.Interface* method), 47

`search_normalize()` (*nailgun.entities.PuppetClass* method), 57

`search_normalize()` (*nailgun.entities.Snapshot* method), 69

`search_normalize()` (*nailgun.entities.SSHKey* method), 66

`search_normalize()` (*nailgun.entity_mixins.EntitySearchMixin* method), 83

`search_payload()` (*nailgun.entities.ContentViewFilterRule* method), 27

`search_payload()` (*nailgun.entity_mixins.EntitySearchMixin* method), 84

`search_raw()` (*nailgun.entity_mixins.EntitySearchMixin* method), 85

`SearchNormalizeTestCase` (class in *tests.test_entities*), 109

`SearchPayloadTestCase` (class in *tests.test_entities*), 109

`SearchTestCase` (class in *tests.test_entities*), 109

`ServerConfig` (class in *nailgun.config*), 93

`ServerConfigTestCase` (class in *tests.test_config*), 97

`SetContentTypeTestCase` (class in *tests.test_client*), 95

`Setting` (class in *nailgun.entities*), 67

`setUp()` (*tests.test_client.ClientTestCase* method), 95

`setUp()` (*tests.test_entities.ContentUploadTestCase* method), 97

`setUp()` (*tests.test_entities.ContentViewComponentTestCase* method), 98

`setUp()` (*tests.test_entities.ContentViewTestCase* method), 98

`setUp()` (*tests.test_entities.ForemanStatusTestCase* method), 101

`setUp()` (*tests.test_entities.ForemanTaskTestCase* method), 101

`setUp()` (*tests.test_entities.GetOrgTestCase* method), 101

`setUp()` (*tests.test_entities.HostGroupTestCase* method), 102

`setUp()` (*tests.test_entities.HostTestCase* method), 103

`setUp()` (*tests.test_entities.JobTemplateTestCase* method), 104

`setUp()` (*tests.test_entities.PathTestCase* method), 105

`setUp()` (*tests.test_entities.PuppetClassTestCase* method), 106

`setUp()` (*tests.test_entities.ReadTestCase* method), 106

`setUp()` (*tests.test_entities.RepositorySetTestCase* method), 108

`setUp()` (*tests.test_entities.RepositoryTestCase* method), 108

`setUp()` (*tests.test_entities.SmartProxyTestCase* method), 110

`setUp()` (*tests.test_entities.SubscriptionTestCase* method), 110

`setUp()` (*tests.test_entities.TemplateInputTestCase* method), 111

`setUp()` (*tests.test_entity_mixins.EntityCreateMixinTestCase* method), 114

`setUp()` (*tests.test_entity_mixins.EntityDeleteMixinTestCase* method), 114

`setUp()` (*tests.test_entity_mixins.EntityReadMixinTestCase* method), 115

`setUp()` (*tests.test_entity_mixins.EntitySearchMixinTestCase* method), 115

`setUp()` (*tests.test_entity_mixins.EntityTestCase* method), 116

`setUp()` (*tests.test_entity_mixins.EntityUpdateMixinTestCase* method), 117

`setUp()` (*tests.test_entity_mixins.MakeEntitiesFromIdsTestCase*

- method), 118
- setUp () (*tests.test_entity_mixins.MakeEntityFromIdTestCase* method), 118
- setUp () (*tests.test_entity_mixins.PollTaskTestCase* method), 118
- setUpClass () (*tests.test_entities.CreateMissingTestCases* class method), 98
- setUpClass () (*tests.test_entities.CreatePayloadTestCases* class method), 100
- setUpClass () (*tests.test_entities.CreateTestCase* class method), 100
- setUpClass () (*tests.test_entities.GenericTestCase* class method), 101
- setUpClass () (*tests.test_entities.InitTestCase* class method), 103
- setUpClass () (*tests.test_entities.JobInvocationTestCase* class method), 104
- setUpClass () (*tests.test_entities.ScapContentsTestCase* class method), 109
- setUpClass () (*tests.test_entities.SearchNormalizeTestCase* class method), 109
- setUpClass () (*tests.test_entities.SearchPayloadTestCase* class method), 109
- setUpClass () (*tests.test_entities.SearchTestCase* class method), 110
- setUpClass () (*tests.test_entities.TailoringFileTestCase* class method), 110
- setUpClass () (*tests.test_entities.UpdatePayloadTestCases* class method), 111
- setUpClass () (*tests.test_entities.UpdateTestCase* class method), 111
- setUpClass () (*tests.test_entities.VersionTestCase* class method), 112
- setUpClass () (*tests.test_entities.VirtWhoConfigTestCase* class method), 112
- setUpClass () (*tests.test_entity_mixins.EntityReadMixinTestCase* class method), 115
- SmartClassParameters (class in *nailgun.entities*), 67
- SmartProxy (class in *nailgun.entities*), 67
- SmartProxyTestCase (class in *tests.test_entities*), 110
- SmartVariable (class in *nailgun.entities*), 68
- Snapshot (class in *nailgun.entities*), 68
- Srpms (class in *nailgun.entities*), 69
- SrpmsTestCase (class in *tests.test_entities*), 110
- SSHKey (class in *nailgun.entities*), 66
- Status (class in *nailgun.entities*), 69
- StringField (class in *nailgun.entity_fields*), 91
- StringFieldTestCase (class in *tests.test_entity_fields*), 113
- Subnet (class in *nailgun.entities*), 69
- Subscription (class in *nailgun.entities*), 69
- subscriptions () (*nailgun.entities.ActivationKey* method), 20
- subscriptions () (*nailgun.entities.HostSubscription* method), 46
- SubscriptionTestCase (class in *tests.test_entities*), 110
- summary () (*nailgun.entities.ForemanTask* method), 33
- sync () (*nailgun.entities.Product* method), 54
- sync () (*nailgun.entities.ProductBulkAction* method), 55
- sync () (*nailgun.entities.Repository* method), 63
- sync_plan () (*nailgun.entities.ProductBulkAction* method), 55
- SyncPlan (class in *nailgun.entities*), 71
- ## T
- TailoringFile (class in *nailgun.entities*), 72
- TailoringFileTestCase (class in *tests.test_entities*), 110
- TASK_POLL_RATE (in module *nailgun.entity_mixins*), 86
- TASK_TIMEOUT (in module *nailgun.entity_mixins*), 86
- TaskFailedError, 87
- TaskTimedOutError, 87
- tearDown () (*tests.test_entities.JobTemplateTestCase* method), 104
- tearDown () (*tests.test_entities.TemplateInputTestCase* method), 111
- Template (class in *nailgun.entities*), 72
- TemplateCombination (class in *nailgun.entities*), 73
- TemplateInput (class in *nailgun.entities*), 73
- TemplateInputTestCase (class in *tests.test_entities*), 110
- TemplateKind (class in *nailgun.entities*), 73
- test_org_path () (*tests.test_entities.SubscriptionTestCase* method), 110
- test_poll_task_failure () (*tests.test_entity_mixins.PollTaskTestCase* method), 118
- test_poll_task_success () (*tests.test_entity_mixins.PollTaskTestCase* method), 118
- test_poll_task_timeout () (*tests.test_entity_mixins.PollTaskTestCase* method), 118
- test_accepted_v1 () (*tests.test_entities.HandleResponseTestCase* method), 102
- test_accepted_v2 () (*tests.test_entities.HandleResponseTestCase* method), 102
- test_add () (*tests.test_entities.ContentViewComponentTestCase* method), 98

`test_api_response_error()`
(*tests.test_entities.GetOrgTestCase* method), 102

`test_arfreport()` (*tests.test_entities.PathTestCase* method), 105

`test_attrs_arg_v1()`
(*tests.test_entities.ReadTestCase* method), 106

`test_attrs_arg_v2()`
(*tests.test_entities.ReadTestCase* method), 107

`test_auth_source_ldap_v1()`
(*tests.test_entities.CreateMissingTestCase* method), 99

`test_auth_source_ldap_v2()`
(*tests.test_entities.CreateMissingTestCase* method), 99

`test_auth_source_ldap_v3()`
(*tests.test_entities.CreateMissingTestCase* method), 99

`test_bad_value_error()`
(*tests.test_entity_mixins.EntityTestCase* method), 116

`test_boolean_datetime_float()`
(*tests.test_entities.JsonSerializableTestCase* method), 104

`test_boolean_field()`
(*tests.test_entity_fields.GenValueTestCase* method), 112

`test_bsc_v1()` (*tests.test_config.ReprTestCase* method), 96

`test_bsc_v2()` (*tests.test_config.ReprTestCase* method), 96

`test_bsc_v3()` (*tests.test_config.ReprTestCase* method), 96

`test_capsule()` (*tests.test_entities.PathTestCase* method), 105

`test_client_request()`
(*tests.test_client.ClientTestCase* method), 95

`test_clients()` (*tests.test_client.ClientTestCase* method), 95

`test_clone_hostgroup()`
(*tests.test_entities.HostGroupTestCase* method), 102

`test_compare()` (*tests.test_entity_mixins.EntityTestCase* method), 116

`test_compare_to_null()`
(*tests.test_entity_mixins.EntityTestCase* method), 116

`test_compare_with_filter()`
(*tests.test_entity_mixins.EntityTestCase* method), 116

`test_content_upload_create()`
(*tests.test_entities.ContentUploadTestCase* method), 97

`test_content_upload_delete()`
(*tests.test_entities.ContentUploadTestCase* method), 97

`test_content_upload_no_filename()`
(*tests.test_entities.ContentUploadTestCase* method), 98

`test_content_upload_update()`
(*tests.test_entities.ContentUploadTestCase* method), 98

`test_content_upload_upload()`
(*tests.test_entities.ContentUploadTestCase* method), 98

`test_content_view_filter_rule()`
(*tests.test_entities.CreatePayloadTestCase* method), 100

`test_content_view_filter_rule()`
(*tests.test_entities.SearchPayloadTestCase* method), 109

`test_content_view_filter_rule()`
(*tests.test_entities.UpdatePayloadTestCase* method), 111

`test_create()` (*tests.test_entity_mixins.EntityCreateMixinTestCase* method), 114

`test_create_json()`
(*tests.test_entity_mixins.EntityCreateMixinTestCase* method), 114

`test_create_missing()`
(*tests.test_entity_mixins.EntityCreateMixinTestCase* method), 114

`test_create_raw_v1()`
(*tests.test_entity_mixins.EntityCreateMixinTestCase* method), 114

`test_create_raw_v2()`
(*tests.test_entity_mixins.EntityCreateMixinTestCase* method), 114

`test_create_raw_v3()`
(*tests.test_entity_mixins.EntityCreateMixinTestCase* method), 114

`test_creation_and_update()`
(*tests.test_entities.ProvisioningTemplateTestCase* method), 106

`test_creation_and_update()`
(*tests.test_entities.ReportTemplateTestCase* method), 108

`test_date_field()`
(*tests.test_entities.JsonSerializableTestCase* method), 104

`test_date_field()`
(*tests.test_entity_fields.GenValueTestCase* method), 112

`test_datetime_field()`
(*tests.test_entity_fields.GenValueTestCase* method), 112

method), 112
test_default() (*tests.test_entities.GetOrgTestCase method*), 102
test_default() (*tests.test_entities.HandleResponseTestCase method*), 102
test_delete() (*tests.test_config.BaseServerConfigTestCase method*), 96
test_delete_puppetclass() (*tests.test_entities.HostGroupTestCase method*), 102
test_delete_puppetclass() (*tests.test_entities.HostTestCase method*), 103
test_delete_raw() (*tests.test_entity_mixins.EntityDeleteMixinTestCase method*), 114
test_delete_v1() (*tests.test_entity_mixins.EntityDeleteMixinTestCase method*), 114
test_delete_v2() (*tests.test_entity_mixins.EntityDeleteMixinTestCase method*), 114
test_delete_v3() (*tests.test_entity_mixins.EntityDeleteMixinTestCase method*), 114
test_delete_v4() (*tests.test_entity_mixins.EntityDeleteMixinTestCase method*), 114
test_delete_v5() (*tests.test_entity_mixins.EntityDeleteMixinTestCase method*), 114
test_delete_v6() (*tests.test_entity_mixins.EntityDeleteMixinTestCase method*), 114
test_dict_field() (*tests.test_entity_fields.GenValueTestCase method*), 112
test_disassociate() (*tests.test_entities.HostTestCase method*), 103
test_discovery_rule() (*tests.test_entities.CreatePayloadTestCase method*), 100
test_discovery_rule() (*tests.test_entities.ReadTestCase method*), 107
test_discovery_rule_search() (*tests.test_entities.UpdatePayloadTestCase method*), 111
test_domain_v1() (*tests.test_entities.CreateMissingTestCase method*), 99
test_domain_v2() (*tests.test_entities.CreateMissingTestCase method*), 99
test_email_field() (*tests.test_entity_fields.GenValueTestCase method*), 112
test_entities() (*tests.test_entities.JsonSerializableTestCase method*), 104
test_entity_arg() (*tests.test_entities.ReadTestCase method*), 107
test_entity_get_fields() (*tests.test_entity_mixins.EntityTestCase method*), 116
test_entity_get_values() (*tests.test_entity_mixins.EntityTestCase method*), 116
test_entity_get_values_v2() (*tests.test_entity_mixins.EntityTestCase method*), 116
test_entity_ids() (*tests.test_entities.ReadTestCase method*), 107
test_eq() (*tests.test_entity_mixins.EntityTestCase method*), 116
test_eq_none() (*tests.test_entity_mixins.EntityTestCase method*), 116
test_existing_value() (*tests.test_client.SetContentTypeTestCase method*), 96
test_external_usergroup() (*tests.test_entities.CreateMissingTestCase method*), 99
test_external_usergroup_payload() (*tests.test_entities.CreatePayloadTestCase method*), 100
test_external_usergroup() (*tests.test_entities.PathTestCase method*), 105
test_false() (*tests.test_client.ContentTypeIsJsonTestCase method*), 95
test_false_with_no_headers() (*tests.test_client.ContentTypeIsJsonTestCase method*), 95
test_files() (*tests.test_entities.RepositoryTestCase method*), 108
test_files_in_kwargs() (*tests.test_client.SetContentTypeTestCase method*), 96
test_float_field() (*tests.test_entity_fields.GenValueTestCase method*), 113
test_gen_netmask() (*tests.test_entity_fields.GenValueTestCase method*), 113
test_generate() (*tests.test_entities.ReportTemplateTestCase method*), 108
test_generic() (*tests.test_entities.CreateTestCase method*), 100
test_generic() (*tests.test_entities.GenericTestCase method*), 101
test_generic() (*tests.test_entities.SearchPayloadTestCase method*), 109
test_generic() (*tests.test_entities.UpdatePayloadTestCase method*), 109

method), 111
 test_generic() (*tests.test_entities.UpdateTestCase method*), 111
 test_get() (*tests.test_config.BaseServerConfigTestCase method*), 96
 test_get() (*tests.test_config.ServerConfigTestCase method*), 97
 test_get_client_kwargs() (*tests.test_config.ServerConfigTestCase method*), 97
 test_get_labels() (*tests.test_config.BaseServerConfigTestCase method*), 96
 test_host_collection() (*tests.test_entities.CreatePayloadTestCase method*), 100
 test_host_v1() (*tests.test_entities.CreateMissingTestCase method*), 99
 test_host_v2() (*tests.test_entities.CreateMissingTestCase method*), 99
 test_host_v3() (*tests.test_entities.CreateMissingTestCase method*), 99
 test_host_with_image() (*tests.test_entities.SearchNormalizeTestCase method*), 109
 test_host_with_image() (*tests.test_entities.SearchTestCase method*), 110
 test_host_with_interface() (*tests.test_entities.ReadTestCase method*), 107
 test_hostgroup_ignore_root_pass() (*tests.test_entities.ReadTestCase method*), 107
 test_hostssubscription() (*tests.test_entities.PathTestCase method*), 105
 test_http_proxy_ignore_arg() (*tests.test_entities.ReadTestCase method*), 107
 test_id_and_which() (*tests.test_entities.PathTestCase method*), 105
 test_identical_args() (*tests.test_client.ClientTestCase method*), 95
 test_ignore_arg_v1() (*tests.test_entities.ReadTestCase method*), 107
 test_ignore_arg_v3() (*tests.test_entities.ReadTestCase method*), 107
 test_ignore_arg_v4() (*tests.test_entities.ReadTestCase method*), 107
 test_image() (*tests.test_entities.CreatePayloadTestCase method*), 100
 test_image() (*tests.test_entities.UpdatePayloadTestCase method*), 111
 test_import_puppetclasses() (*tests.test_entities.SmartProxyTestCase method*), 110
 test_import_uploads_upload_ids() (*tests.test_entities.RepositoryTestCase method*), 108
 test_import_uploads_uploads() (*tests.test_entities.RepositoryTestCase method*), 108
 test_init() (*tests.test_config.BaseServerConfigTestCase method*), 96
 test_init() (*tests.test_config.ServerConfigTestCase method*), 97
 test_init_succeeds() (*tests.test_entities.InitTestCase method*), 103
 test_init_v1() (*tests.test_entity_mixins.EntityTestCase method*), 116
 test_init_v2() (*tests.test_entity_mixins.EntityTestCase method*), 117
 test_init_with_owner() (*tests.test_entities.HostTestCase method*), 103
 test_init_with_owner_type() (*tests.test_entities.HostTestCase method*), 103
 test_int_is_returned() (*tests.test_entity_fields.IntegerFieldTestCase method*), 113
 test_intelligent() (*tests.test_entities.GenericTestCase method*), 101
 test_interface() (*tests.test_entities.SearchNormalizeTestCase method*), 109
 test_interface_ignore_arg() (*tests.test_entities.ReadTestCase method*), 107
 test_ip_address_field() (*tests.test_entity_fields.GenValueTestCase method*), 113
 test_job_template() (*tests.test_entities.CreatePayloadTestCase method*), 100
 test_job_template() (*tests.test_entities.UpdatePayloadTestCase method*), 111
 test_json_content() (*tests.test_entities.HandleResponseTestCase method*), 102

test_length_arg() (tests.test_entity_fields.StringFieldTestCase method), 113
 test_lifecycle_environment_v1() (tests.test_entities.CreateMissingTestCase method), 99
 test_lifecycle_environment_v2() (tests.test_entities.CreateMissingTestCase method), 99
 test_lifecycle_environment_v3() (tests.test_entities.CreateMissingTestCase method), 99
 test_mac_address_field() (tests.test_entity_fields.GenValueTestCase method), 113
 test_max_val_arg() (tests.test_entity_fields.IntegerFieldTestCase method), 113
 test_media() (tests.test_entities.CreatePayloadTestCase method), 100
 test_media_path() (tests.test_entities.UpdatePayloadTestCase method), 111
 test_methods() (tests.test_entities.SubscriptionTestCase method), 110
 test_methods() (tests.test_entities.VirtWhoConfigTestCase method), 112
 test_min_val_arg() (tests.test_entity_fields.IntegerFieldTestCase method), 113
 test_min_val_max_val_args() (tests.test_entity_fields.IntegerFieldTestCase method), 113
 test_missing_org_id() (tests.test_entities.VersionTestCase method), 112
 test_missing_value_error() (tests.test_entity_mixins.EntityReadMixinTestCase method), 115
 test_nested_entities() (tests.test_entities.JsonSerializableTestCase method), 104
 test_no_attributes() (tests.test_entities.CreatePayloadTestCase method), 100
 test_no_content() (tests.test_entities.HandleResponseTestCase method), 102
 test_no_facet_attributes() (tests.test_entities.HostTestCase method), 103
 test_no_json_content() (tests.test_entities.HandleResponseTestCase method), 102
 test_no_such_field_error() (tests.test_entity_mixins.EntityTestCase method), 117
 test_no_such_path_error() (tests.test_entities.PathTestCase method), 105
 test_no_value() (tests.test_client.SetContentTypeTestCase method), 96
 test_noid_and_which() (tests.test_entities.PathTestCase method), 105
 test_non_sync_run() (tests.test_entities.JobInvocationTestCase method), 104
 test_nowhich() (tests.test_entities.PathTestCase method), 105
 test_one_to_many_field() (tests.test_entity_fields.GenValueTestCase method), 113
 test_one_to_one_field() (tests.test_entity_fields.GenValueTestCase method), 113
 test_organization_rh_repo_url() (tests.test_entities.UpdatePayloadTestCase method), 111
 test_os_default_template() (tests.test_entities.PathTestCase method), 105
 test_os_default_template() (tests.test_entities.UpdatePayloadTestCase method), 111
 test_override_value() (tests.test_entities.CreatePayloadTestCase method), 100
 test_owner_type_property() (tests.test_entities.HostTestCase method), 103
 test_parameter_ignore_arg() (tests.test_entities.ReadTestCase method), 107
 test_pass_in_both() (tests.test_entity_mixins.MakeEntitiesFromIdsTestCase method), 118
 test_pass_in_empty_iterable() (tests.test_entity_mixins.MakeEntitiesFromIdsTestCase method), 118
 test_pass_in_entity_id() (tests.test_entity_mixins.MakeEntityFromIdTestCase method), 118
 test_pass_in_entity_ids() (tests.test_entity_mixins.MakeEntitiesFromIdsTestCase method), 118
 test_pass_in_entity_obj() (tests.test_entity_mixins.MakeEntitiesFromIdsTestCase method), 118

method), 118
test_pass_in_entity_obj() (*tests.test_entity_mixins.MakeEntityFromIdTestCase method*), 118
test_path() (*tests.test_entity_mixins.EntityTestCase method*), 117
test_poll() (*tests.test_entities.ForemanTaskTestCase method*), 101
test_product_with_sync_plan() (*tests.test_entities.ReadTestCase method*), 108
test_product_with_sync_plan() (*tests.test_entities.SearchTestCase method*), 110
test_provisioning_template_v1() (*tests.test_entities.CreateMissingTestCase method*), 99
test_provisioning_template_v2() (*tests.test_entities.CreateMissingTestCase method*), 99
test_provisioning_template_v3() (*tests.test_entities.CreateMissingTestCase method*), 99
test_raise_config_file_error() (*tests.test_config.ServerConfigTestCase method*), 97
test_read() (*tests.test_entities.ContentViewTestCase method*), 98
test_read() (*tests.test_entities.ForemanStatusTestCase method*), 101
test_read() (*tests.test_entities.HostGroupTestCase method*), 102
test_read_json() (*tests.test_entity_mixins.EntityReadMixinTestCase method*), 115
test_read_raw() (*tests.test_entity_mixins.EntityReadMixinTestCase method*), 115
test_read_v1() (*tests.test_entity_mixins.EntityReadMixinTestCase method*), 115
test_read_v2() (*tests.test_entity_mixins.EntityReadMixinTestCase method*), 115
test_read_v3() (*tests.test_entity_mixins.EntityReadMixinTestCase method*), 115
test_read_v4() (*tests.test_entity_mixins.EntityReadMixinTestCase method*), 115
test_rebuild_config() (*tests.test_entities.HostGroupTestCase method*), 103
test_regular_objects() (*tests.test_entities.JsonSerializableTestCase method*), 104
test_remove() (*tests.test_entities.ContentViewComponentTestCase method*), 98
test_report_data() (*tests.test_entities.ReportTemplateTestCase method*), 108
test_report_template_v1() (*tests.test_entities.CreateMissingTestCase method*), 99
test_report_template_v2() (*tests.test_entities.CreateMissingTestCase method*), 99
test_report_template_v3() (*tests.test_entities.CreateMissingTestCase method*), 99
test_report_template_v4() (*tests.test_entities.CreateMissingTestCase method*), 99
test_repository_set() (*tests.test_entities.PathTestCase method*), 105
test_repository_v1() (*tests.test_entities.CreateMissingTestCase method*), 99
test_repository_v2() (*tests.test_entities.CreateMissingTestCase method*), 99
test_repr_v1() (*tests.test_entity_mixins.EntityTestCase method*), 117
test_repr_v2() (*tests.test_entity_mixins.EntityTestCase method*), 117
test_repr_v3() (*tests.test_entity_mixins.EntityTestCase method*), 117
test_required_param() (*tests.test_entities.JobInvocationTestCase method*), 104
test_required_params() (*tests.test_entities.InitTestCase method*), 104
test_run() (*tests.test_config.BaseServerConfigTestCase method*), 96
test_run_v1() (*tests.test_config.ReprTestCase method*), 96
test_run_v2() (*tests.test_config.ReprTestCase method*), 97
test_run_v3() (*tests.test_config.ReprTestCase method*), 97
test_run_v4() (*tests.test_config.ReprTestCase method*), 97
test_scap_tailoring_file() (*tests.test_entities.ScapContentsTestCase method*), 109
test_scap_tailoring_file() (*tests.test_entities.TailoringFileTestCase method*), 110
test_schedule() (*tests.test_entities.ReportTemplateTestCase method*), 108
test_search() (*tests.test_entities.ContentViewTestCase method*), 98

test_search_filter_v1 () *method*), 113
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 115

test_search_filter_v2 () *method*), 108
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 115

test_search_filter_v3 () *method*), 111
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 115

test_search_filter_v4 () *method*), 106
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 115

test_search_json () *method*), 100
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 115

test_search_normalize () *method*), 104
 (*tests.test_entities.PuppetClassTestCase*
 method), 106

test_search_normalize_v1 () *method*), 111
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 115

test_search_normalize_v2 () *method*), 100
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 115

test_search_payload_v1 () *method*), 104
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 116

test_search_payload_v2 () *method*), 104
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 116

test_search_payload_v3 () *method*), 110
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 116

test_search_raw () *method*), 95
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 116

test_search_v1 () *method*), 116
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 116

test_search_v2 () *method*), 117
 (*tests.test_entity_mixins.EntitySearchMixinTestCase*
 method), 116

test_snapshot () *method*), 103
 (*tests.test_entities.PathTestCase*
 method), 106

test_snapshot () *method*), 109
 (*tests.test_entities.SearchNormalizeTestCase*
 method), 109

test_snapshot_ignore_arg () *method*), 108
 (*tests.test_entities.ReadTestCase*
 method), 108

test_sshkey () *method*), 117
 (*tests.test_entities.SearchNormalizeTestCase*
 method), 109

test_str_is_returned () *method*), 117
 (*tests.test_entity_fields.StringFieldTestCase*
 method), 113

test_str_type_arg () *method*), 109
 (*tests.test_entity_fields.StringFieldTestCase*
 method), 109

test_subnet () *method*), 100
 (*tests.test_entities.CreatePayloadTestCase*
 method), 100

test_subnet_from () *method*), 108
 (*tests.test_entities.ReadTestCase*
 method), 108

test_subscription () *method*), 111
 (*tests.test_entities.UpdatePayloadTestCase*
 method), 111

test_sync_plan () *method*), 106
 (*tests.test_entities.PathTestCase*
 method), 106

test_sync_run () *method*), 104
 (*tests.test_entities.JobInvocationTestCase*
 method), 104

test_syncplan_sync_date () *method*), 111
 (*tests.test_entities.UpdatePayloadTestCase*
 method), 111

test_to_json () *method*), 102
 (*tests.test_entities.FileTestCase*
 method), 102

test_to_json () *method*), 104
 (*tests.test_entities.GetOrgTestCase*
 method), 102

test_to_json () *method*), 104
 (*tests.test_entities.ModuleStreamTestCase*
 method), 104

test_to_json () *method*), 104
 (*tests.test_entities.PackageGroupTestCase*
 method), 104

test_to_json () *method*), 105
 (*tests.test_entities.PackageTestCase*
 method), 105

test_to_json () *method*), 110
 (*tests.test_entities.SrpmsTestCase*
 method), 110

test_true () *method*), 95
 (*tests.test_client.ContentTypeIsJsonTestCase*
 method), 95

test_update () *method*), 117
 (*tests.test_entity_mixins.EntityUpdateMixinTestCase*
 method), 117

test_update_json () *method*), 117
 (*tests.test_entity_mixins.EntityUpdateMixinTestCase*
 method), 117

test_update_owner_type () *method*), 103
 (*tests.test_entities.HostTestCase*
 method), 103

test_update_payload_v1 () *method*), 117
 (*tests.test_entity_mixins.EntityUpdateMixinTestCase*
 method), 117

test_update_payload_v2 () *method*), 117
 (*tests.test_entity_mixins.EntityUpdateMixinTestCase*
 method), 117

test_update_raw () *method*), 117
 (*tests.test_entity_mixins.EntityUpdateMixinTestCase*
 method), 117

test_upload_content_v1 () *method*), 109
 (*tests.test_entities.RepositoryTestCase*
 method), 109

test_upload_content_v2() (*tests.test_entities.RepositoryTestCase method*), 109
 test_url_field() (*tests.test_entity_fields.GenValueTestCase method*), 31
 test_url_field() (*tests.test_entity_fields.GenValueTestCase method*), 113
 test_usergroup_with_external_usergroup() (*tests.test_entities.ReadTestCase method*), 108
 TestClass (*class in tests.test_entity_fields*), 113
 tests (*module*), 95
 tests.test_client (*module*), 95
 tests.test_config (*module*), 96
 tests.test_entities (*module*), 97
 tests.test_entity_fields (*module*), 112
 tests.test_entity_mixins (*module*), 114
 to_json() (*nailgun.entity_mixins.Entity method*), 77
 to_json_dict() (*nailgun.entity_mixins.Entity method*), 78
 to_json_serializable() (*in module nailgun.entity_mixins*), 89
 traces() (*nailgun.entities.Host method*), 41

U

update() (*nailgun.entities.AbstractComputeResource method*), 18
 update() (*nailgun.entities.Architecture method*), 21
 update() (*nailgun.entities.CompliancePolicies method*), 23
 update() (*nailgun.entities.ContentUpload method*), 24
 update() (*nailgun.entities.DiscoveryRule method*), 30
 update() (*nailgun.entities.Domain method*), 30
 update() (*nailgun.entities.Environment method*), 31
 update() (*nailgun.entities.Host method*), 42
 update() (*nailgun.entities.HostGroup method*), 45
 update() (*nailgun.entities.Location method*), 48
 update() (*nailgun.entities.Media method*), 49
 update() (*nailgun.entities.Organization method*), 52
 update() (*nailgun.entities.ScapContents method*), 66
 update() (*nailgun.entities.SmartProxy method*), 68
 update() (*nailgun.entities.TailoringFile method*), 72
 update() (*nailgun.entities.User method*), 73
 update() (*nailgun.entity_mixins.EntityUpdateMixin method*), 86
 update_json() (*nailgun.entity_mixins.EntityUpdateMixin method*), 86
 update_payload() (*nailgun.entities.AbstractComputeResource method*), 18
 update_payload() (*nailgun.entities.ContentViewFilterRule method*), 27
 update_payload() (*nailgun.entities.DiscoveredHost method*), 29
 update_payload() (*nailgun.entities.DiscoveryRule method*), 30
 update_payload() (*nailgun.entities.Domain method*), 31
 update_payload() (*nailgun.entities.Environment method*), 31
 update_payload() (*nailgun.entities.Filter method*), 33
 update_payload() (*nailgun.entities.Host method*), 42
 update_payload() (*nailgun.entities.HostGroup method*), 45
 update_payload() (*nailgun.entities.HTTPProxy method*), 34
 update_payload() (*nailgun.entities.Image method*), 46
 update_payload() (*nailgun.entities.JobTemplate method*), 47
 update_payload() (*nailgun.entities.Location method*), 48
 update_payload() (*nailgun.entities.Media method*), 49
 update_payload() (*nailgun.entities.OperatingSystem method*), 49
 update_payload() (*nailgun.entities.Organization method*), 52
 update_payload() (*nailgun.entities.OSDefaultTemplate method*), 49
 update_payload() (*nailgun.entities.ProvisioningTemplate method*), 57
 update_payload() (*nailgun.entities.ReportTemplate method*), 61
 update_payload() (*nailgun.entities.Role method*), 66
 update_payload() (*nailgun.entities.Setting method*), 67
 update_payload() (*nailgun.entities.SmartProxy method*), 68
 update_payload() (*nailgun.entities.SmartVariable method*), 68
 update_payload() (*nailgun.entities.Subnet method*), 69
 update_payload() (*nailgun.entities.SyncPlan method*), 72
 update_payload() (*nailgun.entities.User method*), 74
 update_payload() (*nailgun.entities.UserGroup method*), 74
 update_payload() (*nailgun.entities.VirtWhoConfig method*), 75
 update_payload() (*nailgun.entity_mixins.EntityUpdateMixin method*),

86
update_raw() (nailgun.entity_mixins.EntityUpdateMixin method), 86
UpdatePayloadTestCase (class in tests.test_entities), 111
UpdateTestCase (class in tests.test_entities), 111
upload() (nailgun.entities.ContentUpload method), 24
upload() (nailgun.entities.Subscription method), 70
upload_content() (nailgun.entities.Repository method), 63
upload_facts() (nailgun.entities.Host method), 42
URLField (class in nailgun.entity_fields), 91
User (class in nailgun.entities), 73
UserGroup (class in nailgun.entities), 74

V

VersionTestCase (class in tests.test_entities), 111
VirtWhoConfig (class in nailgun.entities), 74
VirtWhoConfigTestCase (class in tests.test_entities), 112
VMWareComputeResource (class in nailgun.entities), 74

X

xml() (nailgun.entities.ScapContents method), 66